

# VEMS

## Specifications

<b>Application</b>	Online Measurement
<b>Power Input</b>	24V, DC, 65mA max
<b>Size</b>	1 3/8" dia x 4 .5" L
<b>Weight</b>	0.5 lb
<b>Connector Type</b>	Type N
<b>Ultrasonic Range</b>	38 kHz – 42 kHz
<b>Housing</b>	Silicone Rubber and Plastic
<b>Operating Temperature</b>	-20°C to +50°C (-4°F to 120°F)
<b>Storage Temperature</b>	-40°C to +85°C (-40°F to 185°F)
<b>Hazardous Area Rating</b>	Class 1 Division 2, Groups A-D, T4A, IP65
<b>Certifications &amp; Approvals</b>	ISA-12.12.01; CAN/CSA C22.2 No 213-15, Class 1 Division2 UL 61010-1, FCC



Image for reference only

## Part Number

<b>Stock Product</b>	VEMS
----------------------	------

2023, Resonance Systems. All rights reserved.

The contents of this publication are presented for informational purposes only, and while diligent efforts have been made to ensure their accuracy, they should not be considered as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

**Resonance Systems**  
8609 Kingston Pike  
Ste 201  
Knoxville, TN 37923 USA  
+1-865-248-24