D.2 -- EQUIPMENT REQUIREMENTS

Equipment (saw(s) and vehicle(s)) shall meet all standards established by specification or incorporated by reference and shall be maintained in good repair by the Contractor.

D.2.1 -- CONTRACTOR PROVIDED EQUIPMENT.

- (a) Personal Protective Equipment (PPE). Contractor shall be responsible for ensuring all personnel arrive at the incident with the proper Personal Protective Clothing and Equipment as prescribed in the agreement. Contractor shall be responsible for ensuring the PPE is operable and maintained in good repair throughout the duration of any assignment. Personal Protective Clothing will be maintained in good repair and be cleaned at sufficient intervals to preclude unsafe working conditions. All personnel shall be wearing Personal Protective Clothing, including boots, upon arrival at the incident. Contractor shall be responsible for ensuring that all personnel arrive with the following PPE:
- (1) BOOTS: All Leather uppers, lace-up type, minimum of 8 inches high with lug type sole in good condition (steel toed boots are not acceptable).
- (2) HARD HAT: Hardhat meeting NFPA Standard 1977 is required.
- (3) GLOVES: One pair of heavy-duty leather per person.
- (4) CHAPS: One pair per person. Chaps or cut-resistant pants for chain saw use shall meet the requirements of ASTM F-1897 (current version). Chaps meeting Forest Service 6170-4 meet the ASTM standard and are acceptable. Chaps shall overlap boots at least 2".