



SOLID - PVC VINYL FLOORING

www.unclesshopdubai.com

Uncle's Shop



دكان العم

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	SOLID FLOORING
THICKNESS (mm)	EN 428	1 / 1.5 / 2.0
ROLL WIDTH (mtr)	EN426	1.5 / 2.0
ROLL LENGTH (mtr)	EN426	15
TOTAL WEIGHT (kgs / sq mtr)	EN 430	1.95 / 2.9 / 3.9
RESIDUAL INDENTATION (mm)	EN 433	0.10 mm (Max)
FLEXIBILITY LOW TEMP.	EN 435	PASSES
REACTION TO FIRE	EN 13501	B fl-s 1
DIMENSIONAL STABILITY (%)	EN 434	≤ 0.40 %
CASTOR CHAIR CONTINUOUS USE	EN 425	SUITABLE
STAIN RESISTANCE	EN 423 / ISO 26987	1, VERY GOOD RESISTANCE
SLIP RESISTANCE	DIN – 51130	R 9
ABRASION RESISTANCE	EN 649	Group T
COMMERCIAL / RESIDENTIAL USE	EN – 685	33
INDUSTRIAL USE	EN 685	42
RESISTANCE TO CHEMICALS	EN 423	Good Resistance
COLOUR FASTNESS TO DAY LIGHT	ISO 105-B02	≥ 6
FUNGI & BACTERIAL RESISTANCE	EN ISO 846 – A/C	Optional
SOUND ABSORPTION	ISO 140 – EN ISO 717-2	5 db
UNDER FLOOR HEATING	-	YES
THERMAL CONDUCTIVITY	EN 12524	0.25 W /m-K