





What if we could apply all our knowledge and expert craftsmanship to create a new type of wooden floor with enhanced properties?




KÄHRS LIFE NEW RANGE OF WOOD FLOORING

HARDWOOD FLOORS

- Natural and beautiful look
- High level of comfort and feel
- Wooden floor natural materials
- Authenticity

VINYL

- Easy to install and renovate
- Resilient
- Easy to maintain
- Affordable
- Water resistant



Kährs

KÄHRS LIFE **FILLING THE GAP**

We are introducing a concept of products which bridges the gap between high-quality wood flooring and functional vinyl flooring.

Combining the best of two worlds – the look of a natural wood floor with properties close to vinyl flooring, at more affordable price-points than that of existing wood flooring - we introduce **Kährs Life**.





KÄHRS LIFE IDEAL FOR LIVING

REAL LIFE

- Outstanding durability
- Outstanding scratch resistance with top lacquer of highest standard
- Impact resistant due to the hardness of the middle core
- Dirt resistant and easy to clean
- Resists water on the surface



At least, you don't have to worry about the floor







KÄHRS LIFE **THE IDEAL FEELING**

REAL WOOD


- An affordable hardwood floor with properties close to a vinyl floor
- A hardwood floor which does not require sanding with a guaranteed lasting look
- Thin real wood wear layer means optimal use of the raw material
- 8 stained alternatives and 2 natural choices







KÄHRS LIFE IDEAL COMFORT



Kährs

REAL COMFORT

- Climate stable in terms of variations of temperature and humidity in an indoor climate
- Suitable to install over radiant heat, by large windows, and close to a fireplace, all due to its stability
- Real Wood for a real comfortable feeling



KÄHRS LIFE IDEAL FOR RENOVATION

REAL EASY RENOVATION


- Can be installed on top of existing floor*
- 7 mm (9/32") floor, fitting easily with existing thresholds and doors
- Fast and easy to install with the 5G joint
- Easy to handle due to the light weight and manageable sizes
- * If requirements specified by Kährs are being fulfilled





KÄHRS LIFE NEW RANGE OF WOOD FLOORING

6 REASONS TO LOVE KÄHRS LIFE

- 1. A hardwood floor for real life
- 2. Wear class 33 Heavy Commercial Use
- 3. Fast and easy installation with the 5G joint Floating or glue down installation
- 4. 15 Year Guarantee & 10 Year Heavy Commercial Guarantee
- 5. Ideal for renovation
- 6. 10 trendy colors















KÄHRS LIFE 10 TRENDY COLORS





KÄHRS LIFE IN THREE FORMATS

10 modern colors in three formats:

- Wide Plank (5 7/8")
- Narrow Plank (4 5/8")
- 2-Strip



| | Wide Plank | Narrow Plank | 2-Strip | |
|----------------|-----------------|------------------|------------------|--|
| Size | 71 1/4" x 5 7/8 | 48 1/4" x 4 5/8" | 48 1/4" × 7 5/8" | |
| Thickness | 7mm | 7mm | 7mm | |
| Wear layer | 0.6mm | 0.6mm | 0.6mm | |
| Micro bevel | Yes | Yes | No | |
| ft2 per bundle | 35.069 | 18.730 | 30.483 | |
| ft2 per pallet | 1893.716 | 1123.752 | 1219.336 | |

KÄHRS LIFE INNOVATIVE FINISH


Easy to love – harder to damage

A matte acrylic urethane finish of highest class for a natural wood feeling with outstanding performance.

Made to last in heavy commercial use

Outstanding durability:


- 1. Best in Class scratch resistance
- 2. Impact resistance Class 33
- 3. Wear resistance Class 33
- 4. Resistance to water on the surface
- 5. Dirt resistance with an easy-to-clean surface



KÄHRS LIFE **REAL WOOD**

For the feel of natural wood


- 1. Real wood of the finest selection for a calm, authentic look and feel.
- 2. Available in pure oak and pure walnut as well as in 8 stained alternatives.
- 3. Renewable wear layer



KÄHRS LIFE **STABLE MIDDLE CORE**

For true stability


- 1. Next generation middle core for a more stable floor
- 2. Increased water resistance with minimum swelling
- 3. Stable throughout variations in humidity and in all seasons
- 4. Increased hardness for outstanding durability and impact resistance
- 5. 5G joint for fast and easy installation




KÄHRS LIFE **REAL WOOD BACKING**

For true stability

- 1. Balances and provides stability
- 2. Pure wood







MATCHED ACCESSORIES

Coordinating moldings available as well as installation and maintenance products.



You'll get a 20 DB sound reduction if used with Kährs Combo System Underlayment



MATT LACQUE REFRESHE

KÄHRS LIFE **THE RANGE**



| Name | Art No Wide Plank | Art No Narrow Plank | Art No 2-strip | Wood | Grade | Surface Treatment | Stained |
|---------------|-----------------------------|-------------------------------|-------------------|--------|-------|-------------------|---------|
| Coconut Cream | LTCLRW3001-150 | LTCLRW3001-118 | LTCLRW3001-193 | Oak | Calm | Matte Finish | X |
| Light Suede | LTCLRW3002-150 | LTCLRW3002-118 | LTCLRW3002-193 | Oak | Calm | Matte Finish | X |
| Pure Oak | LTCLRW3003-150 | LTCLRW3003-118 | LTCLRW3003-193 | Oak | Calm | Matte Finish | |
| Whole Grain | LTCLRW3004-150 | LTCLRW3004-118 | LTCLRW3004-193 | Oak | Calm | Matte Finish | X |
| Driftwood | LTCLRW3005-150 | LTCLRW3005-118 | LTCLRW3005-193 | Oak | Calm | Matte Finish | X |
| Earl Grey | LTCLRW3006-150 | LTCLRW3006-118 | LTCLRW3006-193 | Oak | Calm | Matte Finish | X |
| Butterscotch | LTCLRW3007-150 | LTCLRW3007-118 | LTCLRW3007-193 | Oak | Calm | Matte Finish | X |
| Faded Black | LTCLRW3008-150 | LTCLRW3008-118 | LTCLRW3008-193 | Oak | Calm | Matte Finish | X |
| Pure Walnut | LTCLRW3010-150 | LTCLRW3010-118 | LTCLRW3010-193 | Walnut | Calm | Matte Finish | |
| Cocoa Bean | LTCLRW3011-150 | LTCLRW3011-118 | LTCLRW3011-193 | Oak | Calm | Matte Finish | X |

A HARDWOOD FLOOR FOR REAL LIFE – THE CAMPAIGN

- Kahrs.com
- Kahrsflooring.com
- Social media campaign, facebook, instagram
- Consumer brochure
- Samples
- Images
- Ads/banners
- Added to Kährs new virtual showroom







































































LIFE PASSES ALL TESTS FOR CLASS 33 – WITH GOOD MARGIN

Heavy Commercial Use – Class 33



Table 2 — Classification requirements for elements with lacquered surfaces ex-factory

| Class | 21 | 22 | 23 | 31 | 32 | 33 | |
|--|------------------------|--------------------------|------------|--|--|--------------------------|-------------|
| Symbol | A Å | | | ###################################### | ###################################### | | Test method |
| Level of use | Domestic | | Commercial | | | | |
| | Moderate | General | Heavy | Moderate | General | Heavy | |
| Resistance to indentation | ≥ 10 N/mm ² | 2 ≥ 20 N/mm ² | | ≥ 30 N/mm ² | ≥ 40 N/mm ² | | EN 1534 |
| Thickness swelling | ≤ 15 % | | | ≤ 10 % | | EN 13329:2016 Annex G | |
| Impact resistance (Elasticity) | EC 0 | EC 1 | | EC 2 | EC 3 | | Annex C |
| Wear resistance Top layer ≤ 1,0 mm | | | | 000 olutions | 4 000 revolutions | 6 000 revolutions | Annex D |
| Locking strength | No requirement | | | _ | 1,0 KN/m ≥ 2,0 KN/m | ISO 24334 (| |

About the tests

Resistance to indentation

Measures the hardness of the material. An increasing force is pressing an iron ball until the material is indented. The indention mark is measured and based on the force needed a result is calculated in newton/mm2.

Thickness swelling

The material is measured before and after being soaked in water for 24 hours.

Impact resistance

A falling iron ball of 324 g with a diameter of 42.8 is used. The falling height increases successively. The height used when the lacquer cracks gives the result.

EC3 corresponds to 1400 mm or above.

Wear resistance

Two leather pulleys are rotating while fine standardized sand is being added continuously. The amount of rotations is measured when the lacquer is being worn out.

Locking strength


Two planks are locked with the 5G joint. A force of constant speed is pulling the planks apart until the joint breaks.

WHAT DO WE MEAN WITH MOISTURE RESISTANCE

Two aspects of moisture resistance:

- 1. Resistance to water on the surface due to an innovative urethane finish, joints excluded
- 2. Minimum swelling of the middle core as shown in Class 33 tests

Maximum swelling allowed 10%, latest Kährs Life test results was around 5%



SHERWOOD DBW 152 vs. KÄHRS LIFE

KÄHRS LVT vs. KÄHRS LIFE

Performed Martindale test – Microscratches

Both products reach the highest requirement MSR-B1 according to EN 16094:2012 Laminate floor coverings





Sherwood DBW 152 - Kährs LVT

Kährs Life



Table B.1 — Classification for visual assessment according to procedure B

| Resistance class | Scratch picture Explanation | |
|------------------|-----------------------------|---|
| MSR-B1 | | No visible scratches |
| MSR-B2 | | Only few scratches |
| MSR-B3 | | Many well visible scratches |
| MSR-B4 | | A great many well visible raw and fine scratches, Lissajous figure partly visible |
| MSR-B5 | | Mix of Lissajous figure and great many scratches, mat abrasion like area in the middle |

KÄHRS LIFE **SUMMARY**

- New range of wooden floor
- Wooden floor with properties close to vinyl floor
- Class 33 Heavy Commercial Use
- Perfect for renovation
- 5G joint for fast and easy install
- 15 Year Residential Guarantee
- 10 Year Heavy Commercial Guarantee
- 10 new trendy colors

