

BILL OF MATERIALS		
ITEM	DESCRIPTION	MATERIALS
1	BODY	A106 STD BORE
2	FLANGES	A105, 150# RF S/O
3	COVER	A105, 150# RF
4	SCREEN	PERFORATED 304SS
5	GASKET	316LSS SPIRAL WOUND
6	BOLTING	A193 B7/A194-2H


PRESSURE - TEMPERATURE RATINGS
285 PSI @ 100 DEG F.

SIZE	A	B	C
2"	8.00"	7.00"	.50"
2 1/2"	9.75"	7.50"	1.00"
3"	10.062"	9.00"	1.00"
4"	16.00"	12.00"	1.50"
6"	22.00"	16.00"	2.00"
8"	26.00"	19.00"	2.00"
10"	30.00"	24.00"	2.00"
12"	35.00"	26.00"	2.00"
14"	39.00"	30.00"	2.00"
16"	45.00"	34.00"	2.00"
18"	46.00"	38.00"	2.00"
20"	52.00"	40.00"	2.00"
24"	60.00"	44.00"	2.00"

ALSO AVAILABLE IN 304SS/316SS/LTCS/MONEL
AND OTHER EXOTIC ALLOYS.

DIMS CAN BE ALTERED TO SUIT APPLICATION

HYDROTESTED AT 450 PSI PER B16.5
(FOR 30 MINUTES MIN)

TOLERANCES (EXCEPT AS NOTED)		FABROTECH INDUSTRIES, INC 2089 NINTH AVENUE RONKONKOMA, NY 11779			
DECIMAL +		SCALE	REVISION	BY	DRAWN BY
-	NONE	NONE	-	CHECKED BY	
FRACTIONAL	TITLE				
+ -	C8-150-FAB				
ANGULAR	DATE	DRAWING No.			
+ -	4/29/2021	042921-jmr-012			