



ALSO AVAILABLE IN 304SS/316SS/LTCS/MONEL
AND OTHER EXOTIC ALLOYS.

DIMS CAN BE ALTERED TO SUIT
APPLICATION

HYDROTESTED AT 450 PSI PER B16.5
(FOR 30 MINUTES MIN)

BILL OF MATERIALS		
ITEM	DESCRIPTION	MATERIALS
1	BODY	A106 STD BORE
2	FLANGES	A105, 150# RF S/O
3	COVER	A105, 150# RF
4	SCREEN	PERFORATED 304SS
5	GASKET	316LSS SPIRAL WOUND
6	BOLTING	A193 B7/A194-2H

PRESSURE - TEMPERATURE RATINGS

285 PSI @ 100 DEG F.

SIZE	A	B	C
2"	8.00"	7.00"	.50"
2 1/2"	9.75"	7.50"	1.00"
3"	10.062"	9.00"	1.00"
4"	16.00"	12.00"	1.50"
6"	22.00"	16.00"	2.00"
8"	26.00"	19.00"	2.00"
10"	30.00"	24.00"	2.00"
12"	35.00"	26.00"	2.00"
14"	39.00"	30.00"	2.00"
16"	45.00"	34.00"	2.00"
18"	46.00"	38.00"	2.00"
20"	52.00"	40.00"	2.00"
24"	60.00"	44.00"	2.00"

TOLERANCES (EXCEPT AS NOTED)		FABROTECH INDUSTRIES, INC 2089 NINTH AVENUE RONKONKOMA, NY 11779			
DECIMAL +		SCALE	REVISION(S)	BY	DRAWN BY
-	NONE	NONE	-	CHECKED BY	
-					
FRACTIONAL +	TITLE				
-	<p align="center">C8-150-FAB</p>				
ANGULAR +	DATE		DRAWING No.		
-	01/12/20		011220-jmr-02		