

| BILL OF MATERIALS |             |                                 |
|-------------------|-------------|---------------------------------|
| ITEM              | DESCRIPTION | MATERIALS                       |
| 1                 | BODY        | A106 XS BORE                    |
| 2                 | FLANGES     | A105, 600# RF S/O               |
| 3                 | COVER       | A105, 600# RF                   |
| 4                 | SCREEN      | 1/8" PERF, 100 MESH LINED 304SS |
| 5                 | GASKET      | 304SS SPIRAL WOUND              |
| 6                 | BOLTING     | A193 B7/A194-2H                 |
| 7                 | NPT TAPS    | 1/4" 3M HALF COUPLING, A105     |

|                                |
|--------------------------------|
| PRESSURE - TEMPERATURE RATINGS |
| 1480 PSI @ 100 DEG F.          |


| SIZE | A      | B      | C      |
|------|--------|--------|--------|
| 2"   | 11.00" | 9.00"  | 1/2"   |
| 3"   | 14.00" | 11.00" | 1"     |
| 4"   | 18.00" | 14.00" | 1 1/2" |
| 6"   | 25.50" | 23.00" | 2"     |
| 8"   | 31.75" | 27.00" | 2"     |
| 10"  | 37.75" | 31.00" | 2"     |
| 12"  | 45.50" | 36.50" | 2"     |
| 14"  | 50.00" | 39.50" | 2"     |
| 16"  | 55.50" | 44.50" | 2"     |

ALSO AVAILABLE IN 304SS/316SS/LTCS/MONEL AND OTHER EXOTIC ALLOYS.

DIMS CAN BE ALTERED TO SUIT APPLICATION

HYDROTESTED AT 2225 PSIG FOR 4 HOURS

HYDROTESTED AT 2225 PSI PER B16.5 (FOR 30 MINUTES MIN)

|                                 |   |   |             |
|---------------------------------|---|---|-------------|
| TOLERANCES<br>(EXCEPT AS NOTED) |  | FABROTECH INDUSTRIES, INC                 |             |
|                                 |   | 2089 NINTH AVENUE<br>RONKONKOMA, NY 11779 |             |
| DECIMAL +                       | SCALE   | REVISION (BY                              | DRAWN BY JR |
| -                               | NONE  | NONE -                                    | CHECKED BY  |
| FRACTIONAL +                    | TITLE   |   |             |
| -                               | C8-600-FAB  |   |             |
| ANGULAR +                       | DATE  | DRAWING No.                               |             |
| -                               | 4/29/2021   | 042921-JMR-06                             |             |