



ALSO AVAILABLE IN 304SS/316SS/LTCS/MONEL
AND OTHER EXOTIC ALLOYS.

DIMS CAN BE ALTERED TO SUIT
APPLICATION

BILL OF MATERIALS		
ITEM	DESCRIPTION	MATERIALS
1	BODY	A106 XS (MIN) BORE
2	FLANGES	A105, 600# RF S/O
3	COVER	A105, 600# RF
4	SCREEN	AS REQUIRED
5	GASKET	304SS SPIRAL WOUND
6	BOLTING	A193 B7/A194-2H HEAVY HEX

PRESSURE - TEMPERATURE RATINGS

1480 PSI @ 100 DEG F.

SIZE	A	B	C
2"	11.00"	9.00"	1/2"
3"	14.00"	11.00"	1"
4"	18.00"	14.00"	1 1/2"
6"	25.50"	23.00"	2"
8"	31.75"	27.00"	2"
10"	37.75"	31.00"	2"
12"	45.50"	36.50"	2"
16"	55.50"	44.50"	2"

HYDROTESTED AT 2225 PSIG FOR 30 MINUTES MIN.

TOLERANCES (EXCEPT AS NOTED)		FABROTECH INDUSTRIES, INC 2089 NINTH AVENUE RONKONKOMA, NY 11779			
DECIMAL +		SCALE	REVISION(S)	BY	DRAWN BY JR
-	NONE	NONE	-	CHECKED BY	
-					
FRACTIONAL +	TITLE				
-	C8-600-FAB				
ANGULAR +	DATE		DRAWING No.		
-	04/04/19		040419-jmr-02		