



**ALSO AVAILABLE IN 304SS/316SS/LTCS/MONEL
AND OTHER EXOTIC ALLOYS.**

**DIMS CAN BE ALTERED TO SUIT
APPLICATION**

HYDROTESTED AT 1125 PSI PER B16.5
(FOR 30 MINUTES MIN)

BILL OF MATERIALS

ITEM	DESCRIPTION	MATERIALS
1	BODY	A106 STD BORE
2	FLANGES	A105, 300# RF S/O
3	COVER	A105, 300# RF
4	SCREEN	AS REQUIRED
5	GASKET	304SS SPIRAL WOUND
6	BOLTING	A193 B7/A194-2H

PRESSURE - TEMPERATURE RATINGS

740 PSI @ 100 DEG F.

SIZE	A	B	C
2"	15.00"	12.00"	1/2"
3"	16.00"	12.00"	1"
4"	18.00"	13.00"	1 1/2"
6"	24.00"	19.00"	2"
8"	28.00"	22.00"	2"
10"	31.00"	24.00"	2"
12"	36.00"	27.00"	2"
16"	41.00"	32.00"	2"
18"	50.00"	36.00"	2"
20"	55.00"	40.00"	2"

TOLERANCES (EXCEPT AS NOTED)		FABROTECH INDUSTRIES, INC 2089 NINTH AVENUE RONKONKOMA, NY 11779			
DECIMAL +		SCALE	REVISION(S)	BY	DRAWN BY
-		NONE	NONE	-	CHECKED BY
FRACTIONAL +	TITLE				
-	C8-300-FAB				
ANGULAR +	DATE		DRAWING No.		
-	04/04/20		040420-jmr-06		