

SERVICE PRO[®] GLOBAL FULL SYNTHETIC MULTI- VEHICLE ATF

Manufactured with highly refined base oils and industry leading additive chemistry

DESCRIPTION:

SERVICE PRO[®] Global Full Synthetic Multi-Vehicle ATF represents the latest technology in full synthetic automatic transmission fluids. It is specifically formulated for the newest generation of high efficiency transmissions and is also a fuel efficient choice for older models as well.

SERVICE PRO[®] Global Full Synthetic Multi-Vehicle ATF meets the requirements of JASO M315-2013 1A-LV specification. Also suitable for use in many applications including many General Motors, Ford, FCA/Chrysler, Toyota/Lexus/ Scion (T-III, IV, WS), Nissan/Infiniti (Matic D, J, K, S, W), and Honda/Acura (ATF Z-1, DW-1) transmissions, as well as transmissions installed in Hyundai/ Kia (SP-II, III, IV, Red-1K), Isuzu (SCS, ATF II, III), Jaguar, Land Rover, Mazda(F-1, FZ, M3, T-IV, M5), Mercedes-Benz (236.10, 236.5 and 236.15), Mitsubishi (Diamond SP, II, III, ATF J2, J3), Porsche, BMW(LA2634, LT71141), MINI, SAAB, Subaru (HP), Suzuki, Volvo and VW/Audi (G052 990 A2, G055 025 A2, G055 540 A2) cars and light trucks. It is also suitable for transfer case applications calling for Ford XL-12 fluid.

This product is NOT recommended for Ford Type F, Continuously Variable Transmissions (CVT) or Double Clutch Transmissions (DCT) which require specialized OEM fluids. Check owner's manual for specific recommendations.

PERFORMANCE BENEFITS:

- Improved oxidation and thermal stability
- Full synthetic formula
- Outstanding low temperature performance
- Superior anti-wear protection
- Improved torque transfer

Note: This product is not for sale or use in the State of California.

TYPICAL PROPERTIES*:

API Gravity	34.8
Sp. Gr. @ 60° F	0.8468
Flash. COC. ° F	400
Pour Pt.. ° F	-55
Viscosity. cP @ -40° C	12100
Viscosity, cSt @ 40° C	32
cSt @ 100° C	6.3
Viscosity Index	152
Color	Red

* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



Revised 08/2025 page 1
SPWNGLATF

SERVICE PRO® GLOBAL FULL SYNTHETIC MULTI- VEHICLE ATF

Manufactured with highly refined base oils and industry leading additive chemistry

Service Pro Global Full Synthetic Multi-Vehicle Automatic Transmission Fluid is suitable for use in the following applications:

OEM/ ATF	APPLICATION	OEM/ ATF	APPLICATION
AISIN	AW-2	FCA	Fiat 9.55550-AV6
	JWS 3309 ATF, ATF-OT4		MB 236.10/12, P/N 05127382AA
	JWS 3324 ATF, ATF-OWS		P/N 05127382
Allison	C2		P/N 68157995AA/AB
	C3		P/N 68333587AA
	C4		SP-4, P/N 68171866AA/AB/AC
ATF	134		SP-III
	3353		SP-IV, P/N 68171866AA
	3100 PL085		SP-IV, P/N 68171869AA
	3403-M115		Type 7176E
	D971		Type 9602
	ETL-7045 E	Ford	ESP-M2C138-CJ
	K17		ESP-M2C166-H
	L12108		P/N XT-10-QLV [LV]
	LA 2634		P/N XT-12-ULV [ULV]
	M-1375.4		P/N XT-2-QDX [M]
	M-1375.6		P/N XT-2-QSM [Syn]
	N402		P/N XT-5-QM [V]
	SP-III		P/N XT-5-QSM [V Syn]
Bentley	P/N PY112995PA		P/N XT-6-QSP [SP]
			P/N XT-8-QAW [Premium]
BMW	ATF 3+	P/N XT-9-QMM5 [FNR5]	
	ATF 7	Spec WSS-M2C922-A1	
	ATF4	ATF Z1, Saturn P/N 22717466	
	ATF6	AW-1, P/N 19256039	
	ETL-7045	Dex [GM 6032M]	
	ETL-7045 E	Dex ULV, P/N 19352619	
	ETL-8072B	Dex-B [GM 6032M]	
	LA 2634	Dex-IIC [6137M]	
	LT 71141	Dex-IID [GM 6137M]	
	M-L12108	Dex-IIIE [GM 6137M]	
	P/N 81 22 9 400 272/275	Dex-IIIF [GM 6297M]	
	P/N 81 22 9 407 858/859	Dex-IIIG [GM 6417M]	
	P/N 83 22 0 024 249	Dex-IIIH [GM N10055]	
	P/N 83 22 0 024 359	Dex-VI [GMW 16444]	
	P/N 83 22 0 026 922	Dex HP* [GMW 16974] P/N 19355656	
	P/N 83 22 0 142 516	P/N 19 40 700	
	P/N 83 22 0 397 114	P/N 19 40 767	
	P/N 83 22 0 402 413	P/N 21005966	
	P/N 83 22 0 403 248/249	P/N 88900925	
	P/N 83 22 2 152 426	P/N 9985010	
	P/N 83 22 2 163 514	P/N 9986195	
	P/N 83 22 2 220 438/440	Saturn T-IV Fluid, Saturn P/N 22689186	
	P/N 83 22 2 220 442	Type A Suffix A	
	P/N 83 22 2 289 720	WS, P/N 88863400 / 88863401	
	P/N 83 22 2 305 396	Honda/Acura	ATF DW-1 P/N 08200-9008
	P/N 83 22 2 305 397		ATF Type 3.0 P/N 08200-9016-A
	P/N 83 22 2 355 599		ATF Type 3.1 P/N 08200-9017
	P/N 83 22 2 413 477		ATF Z1, P/N 08200-9001
	P/N 83 22 7 542 290		ATF Z1, P/N 08200-9001A
	P/N 83 22 9 407 765		ATF RED-1K
	P/N 83 22 9 407 807		ATF SP-IV
			Genuine ATF
Bosch	Bosch TE-ML 09	JWS 3314	
Citroen	Z 000169756	P/N 00232-19023	
DAIHATSU	D3-SP	P/N 040000C90SG	
FCA	8 & 9 Speed ATF, P/N 68218925AA/AB	P/N 04500-00140	
	ASRC	P/N UM040 CH20 Red-1	
	ATF+	SP	
	ATF+2	SP4-M1	
	ATF+3	SPH-IV	
	ATF+4	SP-II	
	AW-1, P/N 68092912AA	SP-III	
	Dex-VI, P/N 68043742AA	SP-IV	
	Fiat 9.55550-AV1	SP-IV-RR	
	Fiat 9.55550-AV2	WS, spec NWS-9638	
	Fiat 9.55550-AV4		
	Fiat 9.55550-AV5		
	* State of California does not approve this as suitable for use.		



SERVICE PRO® GLOBAL FULL SYNTHETIC MULTI- VEHICLE ATF

Manufactured with highly refined base oils and industry leading additive chemistry

Service Pro Global Full Synthetic Multi-Vehicle Automatic Transmission Fluid is suitable for use in the following applications:

OEM/ ATF	APPLICATION	OEM/ ATF	APPLICATION
Isuzu	ATF II	Peugeot	P/N Z 000169756
	ATF III		PSA 16 350 560 80
	ATF WSI		JWS 3309, P/N 000 043 205 28
	Genuine ATF		LT 71141
	P/N 08200-9001		P/N 000 043 204 41
Jaguar	SCS		P/N 000 043 204 63
	02JDE 26444	Porsche	P/N 000 043 304 00/01
	Fluid 8432		P/N 000 043 305 42
	JLM 20238		P/N 000 043 305 43
	JLM 20292		P/N 000 043 305 54
	JLM 21044		P/N 000 043 306 24
	K17, Jatco 3100 PL085		P/N 958 300 540 00
	LT 71141		P/N 958 300 901 00
	WSS-M2C922-A1		P/N 999 917 547 00 (A2) or P/N 000 043 205 09
JAMA	JASO M315, Class 1-A	PSA	AL4 / 4HP20, P/N 9730AE
	JASO M315, Class 1-A-LV		B71 2340
Land Rover	ATF N402	Renault	DP-0
	AW-1 P/N LR0022460: LV		Matic D2
	JWS3309US		SATF-D
	P/N TYK500050	Rolls Royce	Oil No. PL 31493PA
	LR023288/023289		ATF HP
MAN	339A	Saab	JWS 3309
	339D		P/N 93 160 393
	339F		P/N 93 165 147
Maserati	Oil No. 231603	Saturn	Dex-III G
Mazda	ATF A7		T-IV Fluid, P/N 22689186
	ATF FZ	Ssangyong	DSIH 5M-52
	ATF M-5 P/N 0000-23-ATF -M5		DSIH 5M-66
	ATF N-1	Subaru	ATF HP, P/N K0140Y0700, P/N SOA635040
	ATF S-1		ATF-WS
	F-1	Suzuki	ATF 2326
	JWS3317		ATF 2384K
	M3		ATF 3314
	Type T-IV, JWS 3309 ATF		ATF 3317
Mercedes	A 0019892203		ATF 5D06
	ATF 3403-M115	Toyota	Matic D
	Sheet 236.1		Matic J
	Sheet 236.10		Matic S
	Sheet 236.11		ATF FZ
	Sheet 236.12		JWS 3309, Type T-IV, P/N 08886-81015
	Sheet 236.14		JWS 3324, ATF WS (or NWS9638)
	Sheet 236.15	Volvo	Type D-II
	Sheet 236.16		Type T
	Sheet 236.17		Type T-II
	Sheet 236.2		Type T-III
	Sheet 236.41		P/N 1161521
	Sheet 236.5		P/N 1161621
Mini	ATF JWS 3309, P/N 83 22 0 402 413	VW/Audi	P/N 1161640; P/N 1161540
Mitsubishi	ATF-J2		P/N 31 256 774, 31 256 775
	ATF-J3		P/N 31 492 172, 31 492 173
	Dia Queen ATF-MA1, P/N MZ320775		G 052 162 (-A1, -A2) [AG4]
	Dia Queen ATF-PA, P/N 4030401		G 052 533
	Dia Queen AW		G 052 990 A2
	DII/DIII		G 053 001 A2
	SP, P/N MS991156		G 055 005 A2
	SP-II		G 055 025 (-A2)
	SP-III	ZF	G 055 162 A2 or A6
Nissan	SP-IV		G 055 540 A2
	Fluid A		G 060 162 A2
	Matic D		G 060 540 A2
	Matic J, P/N 999MP-MTJ00P		G US 000 162
	Matic K		LT 71141
	Matic P, P/N 999MP-MTP10P		LifeguardFluid 5 (ZF No. S671 090 170)
	Matic R, P/N 999MP-MTRO0P		LifeguardFluid 6 (ZF No. S671 090 255)
	Matic S, P/N 999MP-MTS00P		LifeguardFluid 8 (ZF No. S671 090 312)
	Matic W		LifeguardFluid 9 (ZF No. AA01.500.001)
	N402		TE-ML 11A
			TE-ML 11B