## UTILITY TRACTOR

## 30HP | 4WD | Power Steering & 4 in 1 Bucket

## **DFS304** Tractor + Front End Loader NEW 2021 MODEL

# \$19,950.00



#### TRACTOR SPECIFICATIONS:

- Australian designed bucket with side teeth and lifting jig
- Longest selling Asian tractors in Australia
- 26 Years Australian development and sales
- 30HP, 4WD Tractor
- ✓ 4-in-1 Front End Loader
- Single Italian Joystick & Control valve
- Power Steering
- Step Through Deck
- 2 Speed PTO
- Folding ROPS & Canopy
- Full Access Bonnet
- Rear Hydraulic Remotes
- Suspension Seat
- Synchromesh Shuttle-Shift
- ✓ 1.81 Litre, 3 Cyl Diesel Engine
- ✓ 12 Month Factory Warranty



### ENQUIRE WITH OUR CUSTOMER SERVICE TEAM TODAY ABOUT PACKAGE DEALS!

07 3888 2186 parts@brismac.com.au



Tel. 07 3888 2186 | brismac.com.au scott@brismac.com.au cam@brismac.com.au parts@brismac.com.au



### **EAST WIND DFS304 SPECIFICATIONS**

Tractor Model	DFS304
Drive type:	4WD
Horsepower:	30HP
Overall length (front weight to link end): (mm)	3130
Overall width (outer wheel tread): (mm)	1690
Height to canopy (top): (mm)	2311
Height to steering wheel: (mm)	1573
Ground clearance: (mm)	310
Tractor weight with ballast: (kg)	1650
Tractor & Loader Weight	2380
Minimum turning radius: (m)	3.15
Speed: forward (km/hr)	1.48-26.84
reverse (km/hr)	1.49-27.03
Engine Model	ZN390T
Туре:	Direct injection, vertical Liquid Cooled 3 Cyl Diesel
Gross power (12hr rated power kw/hp):	22.4/30
Cylinders:	3 Cyl
Bore and stroke: (mm)	90X95
Compression:	22.0:1.0
Displacement: (L)	1.813L
Speed rated at: (rpm)	2500
Gearbox:	Synchro Shuttle Shift
Gears:	8 Forward, 8 Reverse
Brake type:	Dry Multi Disc
Clutch type:	Dry Type Dual Stage
Rear differential lock:	Mechanical
P.T.O. type:	Live
P.T.O. rotating speed:	540/1000
P.T.O. kW/HP:	20.16/27
3PL capacity at Ball End: (kg)	496
Hydraulics: Main pump:	27.6 L/min
Fuel capacity: (L)	28L
Front tyre size - Turf:	26X7.5-12
Rear tyre size - Turf:	11.2-20
Front tyre size - Agricultural:	6.00-16
Front tyre size - Agricultural:	11.2-24
4 in 1 Loader	SL-30
Bucket width	1570mm
(A) Lift height at pivot point:	2424mm
(B) Dump clearance:	1656mm
Lifting capacity:	440kg

\*Specifications subject to change without notice

V 2016.09.08



Tel. 07 3888 2186 | brismac.com.au scott@brismac.com.au cam@brismac.com.au parts@brismac.com.au