

UTILITY TRACTOR

45HP | 4WD | Power Steering & 4 in 1 Bucket

DFS454

Tractor + Front End Loader

\$25,990

NEW 2022 MODEL



TRACTOR SPECIFICATIONS:

- Single Italian Joystick & Control valve
- Australian designed bucket with side teeth and lifting jig
- Longest selling Asian tractors in Australia
- 27 Years Australian development and sales
- 45HP, 4WD
- 2.8L, 4 Cyl Diesel
- 4-in-1 Front End Loader
- Synchronesh Shuttle-Shift
- 12 Month Factory Warranty
- Power Steering
- New certified, folding Roll Over Protective Structure (ROPS) and Canopy
- Dual Remote Hydraulics
- Digital Dash
- 2 Speed PTO
- Battery Isolator Switch
- Easy Access Bonnet
- New, Larger Head Lights and Tail Lights
- New Rear Work Light

ENQUIRE WITH OUR CUSTOMER SERVICE TEAM TODAY ABOUT PACKAGE DEALS!

07 3888 2186
parts@brismac.com.au



588 Old Gympie Road, Narangba 4504

Tel. 07 3888 2186 | brismac.com.au
scott@brismac.com.au
cam@brismac.com.au
parts@brismac.com.au

EAST WIND DFS454 SPECIFICATIONS

Tractor Model	DFS454
Drive type:	4WD
Horsepower:	45HP
Overall length (front weight to link end):	3460mm
Overall width (outer wheel tread):	1550mm
Height to Canopy (top):	2390mm
Height to steering wheel:	1650mm
Ground clearance:	405mm
Tractor weight with ballast:	2000kg
Tractor & loader weight:	2520kg
Minimum turning radius:	3.85m
Speed: forward (km/hr)	Forward(1.75-32.20 km/h)
reverse (km/hr)	Reverse(2.30-11.92 km/h)
Engine Model	4L68
Type:	Direct injection, vertical liquid cooled 4cyl diesel
Gross power (12hr rated power kW/hp):	36.8/45
Cylinders:	4
Bore and stroke:	95X100
Compression:	18.0:1.0
Displacement:	2.83L
Speed rated at:	2400 rpm
Gearbox:	SynchroShuttleShift
Gears:	8 Forward, 8 Reverse
Brake type:	Dry multi disc
Clutch type:	Dry type dual stage
Rear differential lock:	Mechanical
PTO type:	Live
PTO rotating speed:	540/1000 rpm
PTO kW/HP:	33.12/40.5
3PL capacity at Ball End:	665kg
Hydraulics: Main pump:	33.6 L/min
Fuel capacity:	28L
Front tyre size - Agricultural:	7.50-16
Rear tyre size-Agricultural:	12.4-24
4 in 1 Loader:	SL-45
Bucket width	1700mm
(A) Lift height at pivot point:	2699mm
(B) Dump clearance:	1930mm
Lifting capacity:	500kg

*Specifications subject to change without notice