TOUGH TERRAIN TRACTORS

EASTWIND YCT356S-S · YCT356S-SL



The East Wind YCT Series Dozer is a truly unique machine. It brings together a package of compact design, user friendliness, versatility and outstanding value never seen before in a dozer.

Developed specifically for the Australian lifestyle farmer it has captured the imagination of many farmers looking to develop and maintain their property.

East Wind delivers a compact, easy to handle machine with the awesome power to make light work of various jobs around the small acreage farm.

A power take off (PTO) and three point linkage fitted standard to the YCT Series sets it apart from other dozers on the market. This gives you the versatility to drive a slasher, fit a ripper, run a post hole digger and many other implements you would attach to a wheeled tractor.

And the giant footprint afforded by the long, wide tracks combined with the low centre of gravity gives you "go anywhere"

traction and stability. It's sure to be the envy of any wheeled tractor owner in steep and slippery conditions.

We understand that not all lifestyle farmers are experienced operators. That's why our dozers are designed to be comfortable and easy to use.

- Unlike other machines, steering is controlled with simple foot pedals leaving the hands free for operating the blade or bucket. A "left" steering pedal makes the machine turn left and a "right" steering pedal makes it turn right.
- A single intuitive joystick enables the dozer blade to be moved 6 ways – up/down, angle left/angle right, tilt left/tilt right. The joystick also has a "float" position for easier leveling while backblading.
- The easy to read instrument panel show you everything you need to know.
- The multi-adjustable, suspension seat accommodates small and large operators and softens the bumps of dozer work.




Tel. 07 3888 2186 | brismac.com.au scott@brismac.com.au cam@brismac.com.au parts@brismac.com.au



EASTWIND YCT356S-S - YCT356S-SL Specifications


Dozer Model	YCT356S-S	YCT356S-SL	
Overall length blade / loader (mm)	2980	3360	
Overall width (with straight blade) (mm)	1740	1550	
Overall height to top of ROPS (mm)	2370		
Track width (mm)	1450		
Shoe width (mm)	290		
Ground clearance (mm)	240		
Operating weight (kg)	3150	3320	
Turning Circle (mm)	140	00	
Lift height of blade (mm) / Loader dump height	500	2200mm	
Blade capacity / Bucket volume	0.67 m ³	0.3m ³	
Engine Model	4L22TA		
Туре	Direct injection, vertical liquid cooled 4 cyl diesel, EPA4 approved.		
Cylinders / Bore and Stroke	4 / 85 x 95mm		
Displacement	2.16L		
Transmission: Manual Shift	(4+1) x 2; 8 Forward x 2 Reverse		
Speeds. Forward / Reverse (Km/Hr)	0.9 - 11.5		
Clutch	Dry disc		
Brake / Steering	Band brakes, pedal control / Multiple Disc		
Undercarriage:	Semi - ridgid		
Track rollers each side	5+2		
Number of shoes	43 (109mm pitch)		
Track tension device	Helical spring, mechanical adjustment		
PTO type	Single clutch		
PTO speed	2 speeds - 540 & 1000		
3PL Capacity at ball end / Category	750Kg / Cat 1		
Hydraulics: Main pump	29.4	29.4 lpm	
Fuel capacity	28	28L	



MODEL Bucket Width Working Length (A) Digging Depth (B) Extend Height (extend Height (extend Height (form)) BHEF-195 300mm 2900mm 1950mm 3170mm Unload Height Leg Spread "Swing Angle (boom)" Weight	FACTOR	Y OPTION BA	ACKHOE -	3 POI	NT LINKAGE (CATEGORY 1)
	MODEL	Bucket Width	Working Le	ngth (A)	Digging Depth (B	Extend Height (C)
Unload Height Leg Spread "Swing Angle (boom)" Weight	BHEF-195	300mm	2900m	nm	1950mm	3170mm
	Unload H	Height Le	g Spread	" Swi	ng Angle (boom)	" Weight
1951 mm 1800mm 140° 494kg	1951 n	nm	1800mm		140°	494kg

" FRONT END LOADER - 4 in 1, SELF LEVELLING					
Bucket Width	Lift Height (A)	Dump Clearance (B)			
1550 mm	2730 mm	1973 mm			
Crowd Angle (D)	Dump Angle (E)	Lifting Capacity			
40°	45°	550kg			

^{*}Specifications subject to change without notice



V 2013.02.05



Tel. 07 3888 2186 | brismac.com.au scott@brismac.com.au cam@brismac.com.au parts@brismac.com.au