

EASTWIND DFS304

TRACTOR & 4 IN 1 FRONT END LOADER

\$ 22,990



30+ YEARS
OF SALES ON THE
AUSTRALIAN MARKET

30HP
4WD

4 IN 1
BUCKET

24 MONTH
FACTORY
WARRANTY



DFS304 SPECIFICATIONS

- ✓ Longest-selling Asian tractors in Australia
- ✓ 30 years Australian development and sales
- ✓ 1.8L, 3 Cylinder direct injection diesel engine
- ✓ Synchromesh shuttle-shift transmission
- ✓ Power steering and deluxe suspension seat with arm rests
- ✓ Australian-designed 4 in 1 bucket with side teeth and lifting jig
- ✓ Single Italian joystick and control valve with button operated 4 in 1 motion
- ✓ New certified folding rollover protective structure (ROPS) and canopy
- ✓ Dual remote hydraulics
- ✓ 2 speed PTO
- ✓ Battery isolator switch
- ✓ Easy access bonnet with under bonnet exhaust and air intake
- ✓ New larger lights and work light
- ✓ 440kg front end loader lift capacity

BUY DIRECT
Local Service Backup


Deal direct
with the owners

BRISMAC
TRACTORS & MACHINERY

FOR SALES ENQUIRIES
CONTACT SCOTT

0414 840 305

scott@brismac.com.au



EASTWIND DFS304

TRACTOR & 4 IN 1 FRONT END LOADER

| Tractor Model | DFS304 |
|---|---|
| Drive type: | 4WD |
| Horsepower: | 30HP |
| Overall length (front weight to link end): (mm) | 3130 |
| Overall width (outer wheel tread): (mm) | 1690 |
| Height to canopy (top): (mm) | 2311 |
| Height to steering wheel: (mm) | 1573 |
| Ground clearance: (mm) | 310 |
| Tractor weight with ballast: (kg) | 1650 |
| Tractor & Loader Weight | 2380 |
| Minimum turning radius: (m) | 3.15 |
| Speed: forward (km/hr) | 1.48-26.84 |
| reverse (km/hr) | 1.49-27.03 |
| Engine Model | ZN390T |
| Type: | Direct injection, vertical Liquid Cooled 3 Cyl Diesel |
| Gross power (12hr rated power kw/hp): | 22.4/30 |
| Cylinders: | 3 Cyl |
| Bore and stroke: (mm) | 90X95 |
| Compression: | 22.0:1.0 |
| Displacement: (L) | 1.813L |
| Speed rated at (rpm) | 2500 |
| Gearbox: | Synchro Shuttle Shift |
| Gears: | 8 Forward, 8 Reverse |
| Brake type: | Dry Multi Disc |
| Clutch type: | Dry Type Dual Stage |
| Rear differential lock: | Mechanical |
| P.T.O. type: | Live |
| P.T.O. rotating speed: | 540/1000 |
| P.T.O. kW/HP: | 20.16/27 |
| 3PL capacity at Ball End: (kg) | 496 |
| Hydraulics: Main pump: | 27.6 L/min |
| Fuel capacity: (L) | 28L |
| Front tyre size - Turf: | 26X75-12 |
| Rear tyre size - Turf: | 11.2-20 |
| Front tyre size - Agricultural: | 6.00-16 |
| Front tyre size - Agricultural: | 11.2-24 |
| 4 in 1 Loader | SL-30 |
| Bucket width | 1570mm |
| (A) Lift height at pivot point: | 2424mm |
| (B) Dump clearance: | 1656mm |
| Lifting capacity: | 440kg |

*Specifications subject to change without notice

V 2016.09.08



BRISMAC

TRACTORS & MACHINERY

FOR SALES ENQUIRIES
CONTACT SCOTT

0414 840 305

scott@brismac.com.au