

EASTWIND DFS454

TRACTOR & 4 IN 1 FRONT END LOADER

\$ 25,990



30+ YEARS
STRONG SALES ON
AUSTRALIAN MARKET



45HP
4WD

4 IN 1
BUCKET

24 MONTH
FACTORY
WARRANTY

DFS454 SPECIFICATIONS

- ✓ Longest-selling Asian tractors in Australia
- ✓ 30 years Australian development and sales
- ✓ Single Italian joystick and control valve with button operated 4 in 1 motion
- ✓ 550kg front end loader lift capacity
- ✓ Australian-designed 4 in 1 bucket with side teeth and lifting jig
- ✓ 2.8L, 4 Cylinder direct injection diesel engine
- ✓ Synchronesh shuttle-shift transmission
- ✓ Power steering and deluxe suspension seat with arm rests
- ✓ New certified folding rollover protective structure (ROPS) and canopy
- ✓ Dual remote hydraulics
- ✓ 2 speed PTO
- ✓ Battery isolator switch
- ✓ Easy access bonnet with under bonnet exhaust and air intake
- ✓ New larger headlights and work light
- ✓ Farm Lug tyres 12.4-24 / 7.50-16 with 1720mm rear wheel width

BUY DIRECT
Local Service Backup

 Deal direct
with the owners

BRISMAC
TRACTORS & MACHINERY

FOR SALES ENQUIRIES
CONTACT SCOTT

0414 840 305

scott@brismac.com.au



EASTWIND DFS454

TRACTOR & 4 IN 1 FRONT END LOADER

Tractor Model	DFS454
Drive type:	4WD
Horsepower:	45HP
Overall length (front weight to link end):	3460mm
Overall width (outer wheel tread):	1720mm
Height to Canopy (top):	2390mm
Height to steering wheel:	1650mm
Ground clearance:	405mm
Tractor weight with ballast:	2000kg
Tractor & loader weight:	2520kg
Minimum turning radius:	3.85m
Speed: forward (km/hr)	Forward(1.75-32.20 km/h)
reverse (km/hr)	Reverse(2.30-11.92 km/h)
Engine Model	4L68
Type:	Direct injection, vertical liquid cooled 4cyl diesel
Gross power (12hr rated power kW/hp):	36.8/45
Cylinders:	4
Bore and stroke:	95X100
Compression:	18.0:1.0
Displacement:	2.83L
Speed rated at:	2400 rpm
Gearbox:	Synchro Shuttle Shift
Gears:	8 Forward, 8 Reverse
Brake type:	Dry multi disc
Clutch type:	Dry type dual stage
Rear differential lock:	Mechanical
PTO type:	Live
PTO rotating speed:	540/1000 rpm
PTO kW/HP:	33.12/40.5
3PL capacity at Ball End:	665kg
Hydraulics: Main pump:	33.6 L/min
Fuel capacity:	28L
Front tyre size - Agricultural:	7.50-16
Rear tyre size-Agricultural:	12.4-24
4 in 1 Loader:	SL-45
Bucket width	1700mm
(A) Lift height at pivot point:	2699mm
(B) Dump clearance:	1930mm
Lifting capacity:	550kgs

*Specifications subject to change without notice



BRISMAC
TRACTORS & MACHINERY

FOR SALES ENQUIRIES
CONTACT SCOTT

0414 840 305

scott@brismac.com.au