

EASTWIND DF 554 G3

TRACTOR & 4 IN 1 FRONT END LOADER

\$28,990



30+ YEARS
STRONG SALES ON
AUSTRALIAN MARKET

55HP
4WD

4 IN 1
BUCKET

24 MONTH
FACTORY
WARRANTY

DFS554 SPECIFICATIONS

- ✓ Dual remote hydraulics
- ✓ 2 speed PTO
- ✓ Battery isolator switch
- ✓ Longest-selling Asian tractors in Australia
- ✓ 30 years Australian development and sales
- ✓ 800kg front end loader lift capacity
- ✓ Single Italian joystick and control valve with button operated 4 in 1 motion
- ✓ Australian-designed 4 in 1 bucket with side teeth and lifting jig
- ✓ 3.2L 4 Cylinder direct injection diesel engine, 55L Fuel capacity
- ✓ Synchronesh shuttle-shift transmission
- ✓ Power steering and deluxe suspension seat with arm rests
- ✓ New certified folding rollover protective structure (ROPS) and canopy
- ✓ Easy access bonnet with under bonnet exhaust and air intake
- ✓ New larger headlights and work light
- ✓ Farm Lug tyres 13.6-28 / 9.5-20 with 1650mm rear wheel width

BUY DIRECT
Local Service Backup


Deal direct
with the owners

BRISMAC
TRACTORS & MACHINERY

FOR SALES ENQUIRIES
CONTACT SCOTT

0414 840 305

scott@brismac.com.au



EASTWIND DF 554 G3

TRACTOR & 4 IN 1 FRONT END LOADER

Tractor Model	DF 554 G3
Drive type:	4WD
Horsepower:	55HP
Overall length (front weight to link end):	3738mm
Overall width (outer wheel tread):	1650mm
Height to Canopy (top):	2600mm
Height to steering wheel:	1665mm
Ground clearance:	355mm
Tractor weight with ballast:	2440kg (with water in tyres)
Tractor & loader weight:	2990kg
Minimum turning radius:	3.7m
Speed: forward (km/hr)	Forward (1.86-32.81)
reverse (km/hr)	Reverse (1.94-15.12)
Engine Model	4G33
Type:	Direct Injection, Vertical liquid cooled 4cyl diesel
Gross power (12hr rated power kW/hp):	41.01/5
Cylinders:	4
Bore and stroke:	95x115
Compression:	18.5
Displacement:	3.26
Speed rated at:	2400rpm
Gearbox:	Synchro Shuttle Shift
Gears:	12 Forward 12 Reverse (creeper gears)
Brake type:	Wet Disc
Clutch type:	Dry Type - Single Stage
Rear differential lock:	Mechanical; Four bevel gears
PTO type:	Live
PTO rotating speed:	540/1000 rpm
PTO kW/HP:	47.3(34.8)
3PL capacity at Ball End:	1000 kgs
Hydraulics: Main pump:	38.4 L/min
Fuel capacity:	55 L
Front tyre size - Agricultural:	9.5-20
Rear tyre size-Agricultural:	13.6-28
4 in 1 Loader:	SL55
Bucket width	1700mm
(A) Lift height at pivot point:	2750mm
(B) Dump clearance:	2500mm
Lifting capacity:	800kg

*Specifications subject to change without notice



BRISMAC
TRACTORS & MACHINERY

FOR SALES ENQUIRIES
CONTACT SCOTT

0414 840 305

scott@brismac.com.au