

ZB28 SPECIFICATIONS

- 🗹 Longest-selling Asian tractors in Australia
- 30 years Australian development and sales
- 1.5L direct injection diesel engine
- ✓ Power steering
- $f ec{f v}$ New larger 11-2 24 6.50-16 Farm lug tyres
- ✓ New certified folding rollover protective structure (ROPS) and canopy
- Dual remote hydraulics
- ✓ Suspension seats
- 2 speed PTO
- ✓ Battery isolator switch
- ✓ Easy access bonnet and under bonnet air intake
- New larger headlights and tail lights







EASTWIND ZB28

TRACTOR FRONT END LOADER

Tractor Model	ZB28
Drive type:	4WD
Horsepower:	28HP
Overall length (front weight to link end):	3195mm
Overall width (outer wheel tread):	1360mm
Height to Canopy (top):	2253mm
Height to steering wheel:	1570mm
Ground clearance:	290mm
Tractor weight with ballast:	1530kg
Tractor & loader weight:	2010kg
Minimum turning radius:	3.15m
Speed: forward (km/hr)	0.98-21.97 km/h
reverse (km/hr)	1.16-5.99 km/h
Engine Model	KM385
Type:	Direct injection, vertical liquid cooled 3cyl diesel
Gross power (12hr rated power kW/hp):	20.8/28HP
Cylinders:	3
Bore and stroke:	85X95
Compression:	22.0:1.0
Displacement:	1.532L
Speed rated at:	2350 rpm
Gearbox: Sliding Gear	(4+1)X2
Gears:	8 x Forward/ 2 x Reverse
Brake type:	Sealed shoe brake
Clutch type:	Dry type single stage
Rear differential lock:	Mechanical
PTO type:	Single Clutch
PTO rotating speed:	540/730 rpm
PTO kW/HP:	18.64/25
3PL capacity at Ball End:	423kg
Hydraulics: Main pump:	27.6 L/min
Fuel capacity:	25L
Front tyre size - Agricultural:	6.50-16
Rear tyre size-Agricultural:	11.2-24
4 in 1 Loader:	BL-28
Bucket width	1420mm
(A) Lift height at pivot point:	2363mm
(B) Dump clearance:	1610mm
Lifting capacity:	350kg

*Specifications subject to change without notice



TRACTORS & MACHINERY scott@brismac.com.au

FOR SALES ENQUIRIES **CONTACT SCOTT** 0414 840 305