

16,000# Partial Tilt

G.V.W.R.	16,000#
G.A.W.R. (Ea. Axle)	8,000#
COUPLER	2 5/16 Adj Coupler
SAFETY CHAINS	3/8" Grd. 70 w/Safety Latch Hook (2 each)
JACK	10k Dropleg Jack (Bolted On)
TONGUE	6" @ 10.5 LB per ft. Channel Wrap Tongue
TOP RAIL	None
FRAME	6" HD Channel
CROSSMEMBERS	3" Channel
UPRIGHTS	None
FENDERS	Hard Fenders with Oversized Steps

]	AXLES	Two 8,000# EZ Lube Elec. Brake Slipper
	SUSPENSION	Spring with Equalizer
l	TIRE	ST235-75R-17.5 18 PLY
]	WHEEL	Solid Steel 17.5" 8 Hole Wheel
1	FLOOR	2" Pine
]	LIGHTS	D.O.T. Stop, Tail, Turn & Clearance
]	ELEC. PLUG	7-Way RV
]	FINISH (Prep)	Steel Grit Blasted, Degreased, Phosphatized, Hot Water Pressure Washed and Sealed
1	FINISH	Fully Powder Coated

Standard Features,

- Lockable Storage Box
- Reverse Dovetail
- Set Back Jack
- Lower Jack Support Plate

- Fully Adjustable Hydraulic System
- Wrap Tongue
- Solid Front Bump Rail
- Floor Secured w/Torx Screws
- Cambered EZ Lube Axles
- Two 8,000# Axles Electric Brake
- Complete Break-A-Way System w/Charger
- Hard Fenders
- Grommet Mount Sealed Lighting
- Fully Powder Coated



AVAILABLE SIZES

82" X 16+4 82" X 16+6