

# RICCE TRAILERS

## 16,000# Partial Tilt

<b>G.V.W.R.</b>	16,000#	<b>AXLES</b>	Two 8,000# EZ Lube Elec. Brake Slipper
<b>G.A.W.R. (Ea. Axle)</b>	8,000#	<b>SUSPENSION</b>	Spring with Equalizer
<b>COUPLER</b>	2 5/16 Adj Coupler	<b>TIRE</b>	ST235-75R-17.5 18 PLY
<b>SAFETY CHAINS</b>	3/8" Grd. 70 w/Safety Latch Hook (2 each)	<b>WHEEL</b>	Solid Steel 17.5" 8 Hole Wheel
<b>JACK</b>	10k Dropleg Jack (Bolted On)	<b>FLOOR</b>	2" Pine
<b>TONGUE</b>	6" @ 10.5LB per ft. Channel Wrap Tongue	<b>LIGHTS</b>	D.O.T. Stop, Tail, Turn & Clearance
<b>TOP RAIL</b>	None	<b>ELEC. PLUG</b>	7-Way RV
<b>FRAME</b>	6" HD Channel	<b>FINISH (Prep)</b>	Steel Grit Blasted, Degreased, Phosphatized, Hot Water Pressure Washed and Sealed
<b>CROSSMEMBERS</b>	3" Channel	<b>FINISH</b>	Fully Powder Coated
<b>UPRIGHTS</b>	None		
<b>FENDERS</b>	Hard Fenders with Oversized Steps		

### Standard Features

- Lockable Storage Box
- Fully Adjustable Hydraulic System
- Two 8,000# Axles Electric Brake
- Reverse Dovetail
- Wrap Tongue
- Complete Break-A-Way System w/Charger
- Set Back Jack
- Solid Front Bump Rail
- Hard Fenders
- Lower Jack Support Plate
- Floor Secured w/Torx Screws
- Grommet Mount Sealed Lighting
- Cambered EZ Lube Axles
- Fully Powder Coated

### AVAILABLE SIZES

82" X 16+4  
82" X 16+6