

SORB | ORLÉANS™

HIGH-END FAN HEATER FOR BATHROOMS



ORLÉANS™



FOR FAST COMFORT!

The °STELPRO family of high-end ORLÉANS convectors is growing. Treat yourself to our brand-new ORLÉANS high-end fan heater and enjoy a toasty warm bathroom even in winter. Thanks to its optimum heat output and rapid temperature rise, this model provides heat exactly when you need it. It is also the quietest fan heater in its category, allowing you to relax and enjoy some peace and quiet. Very similar to our ORLÉANS high-end convector, this fan heater has an optional built-in, smart-home-ready thermostat.

THE QUIETEST FAN HEATER IN ITS CATEGORY

HEAT "BOOST" MODE
FAST TEMPERATURE RISE
(1000 W TO 2000 W)†

STURDY, DURABLE AND RUST-RESISTANT

OPTIONAL BUILT-IN ELECTRONIC THERMOSTAT
PERFECT FOR THE SMART HOME

CONTROL THE TEMPERATURE OF YOUR HOME FROM YOUR SMARTPHONE, TABLET OR COMPUTER



 **zigbee**
COMPATIBLE CONTROLLER REQUIRED

FOR HOME AUTOMATED SYSTEM COMPATIBILITIES AND INSTRUCTIONS ON CONNECTING TO YOUR THERMOSTAT, REFER TO WWW.STELPRO.COM.

IDEAL FOR:

bathroom, entrance, vestibule, hallway, living space

COLOURS

- **standard:** white, soft white
- **ORORA (optional):** refer to www.stelpro.com/en-CA/orora

FINISH

- epoxy-polyester powdercoat

MANUFACTURING

- high performance polymer cabinet, 20-gauge satin-finish steel front with moulded aluminum edges
- centrifugal fan that ensures a quiet and efficient airflow
- thermal protection with automatic reset
- additional thermal protection with a thermal fuse (must be replaced if triggered)
- top front air intake and bottom front air discharge

ELEMENT

- high-quality nichrome element that generates instant heat

CONTROL

- MODEL WITHOUT A THERMOSTAT:
- an electronic wall thermostat is recommended

MODEL WITH A BUILT-IN THERMOSTAT:

- built-in MAESTRO smart thermostat featuring the Zigbee protocol
 - 1000 W to maintain temperature setpoint
 - 2000 W when "boost" mode is activated (with a timer)
 - colour-code feedback for responsible energy consumption
 - drastic temperature drop detection (open window function)
- ### INSTALLATION
- recessed or surface mounted (optional surface adapter)
 - on the wall, a minimum of 6 in. from the floor
 - front easy to install with only one mounting screw
 - power switch selector – 1000 W or 2000 W (model without a thermostat only)

WARRANTY

- five years, *three years on electronic components

† 5°C (9°F) temperature rise within five minutes. (Tests performed with the 2000 W model in a 70 ft² room.)

PART OF THE ORLÉANS FAMILY OF PRODUCTS

NEED A CONVECTOR?

SOR



°STELPRO

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_SORB_EN_311018



TECHNICAL SPECIFICATIONS

PRODUCT	THERMOSTAT HEATING	TIMER HEATING	WITHOUT THERMOSTAT	VOLTAGE	HEIGHT		LENGTH		WEIGHT		PRICE
CODE	WATTS	WATTS	WATTS	VOLTS	MM	IN.	MM	IN.	KG	LB	
SORB2002M	1000/750	2000/1500	---	240/208	398	15 11/16	322	12 11/16	4.3	9.4	464.00
SORB2002WC	---	---	2000/1500 OR 1000/750*	240/208	398	15 11/16	322	12 11/16	4.3	9.4	360.00

Add W for white or SW for soft white (consult the optional colour chart and contact your °STELPRO representative for all other colours).

* Selected when installed with a power switch

TECHNICAL DRAWINGS

