

10' TOWER FOR POT-BELLY BLIND

ASSEMBLY INSTRUCTIONS

(2 PERSONS NEEDED)

*The picture on the next page shows the pieces as described below on a finished tower.
The letters on this page correspond to the letters on the picture*

A – (4) **2"** angle iron pieces (forms base for blind to sit on) *47" long*

B - (4) **2"** angle iron pieces with attachment plates at one end (upper legs) *60" long*

C - (4) **2"** angle iron pieces (lower legs) *60" long*

I - (4) **1.5"** angle iron pieces (upper horizontal braces) *65.5" long*

G-H(8) **1.5"** angle iron pieces (lower horizontal braces) *47" long*

Note: G-H pieces are bundled in two sets of four each

E-F (4) **1.5"** angle iron pieces (upper diagonal braces) *65.5" long*

F-G (4) **1.5"** angle iron pieces (lower diagonal braces) *47" long*

Note: E-F, F-G pieces are bundled in two sets of two each.

(4) feet (marked **X**)

(2) ladders (one upper and one lower)

(1) rail

Bolts, Nuts, Flat washers and Lock washers

the (8) 3/8" X 2 1/2" nuts are for installation of the angle iron base

You will need a step ladder and wrenches or sockets for assembly!



A

A

A

D

A

D

B

B

B

B

E

E

E

E

E

E

C

C

F

F

F

G

G

H

G

H

X

G

C

G

X

H

H

F