



BUILDING SPECIFIER'S WORKSHEET

The Lonestar Prestress, Mfg. specifier's worksheet can be used as an aid to request a quote for a standard or custom building. Please complete all items that apply to your particular environment. Fax or email this form back to us at (713) 896-0762 or sales@lonestarprestress.com and a quote will be prepared for you. Please include a brief description of anything you would like included that is not listed. For further information or questions, please call us at (713) 896-0994 or toll free at (800) 600-1719.

GENERAL INFORMATION

Your Name: _____ Title: _____
 Company Name: _____
 Address: _____
 City: Houston State: _____ Zip Code: _____
 Phone: _____ Fax: _____ Email: _____

BUILDING INFORMATION

Project Name: _____
 Project Location: _____
 Intended Use: _____
 Expected Delivery Date: _____

BUILDING DESCRIPTION

1. EASI-SET™ Transportable Precast Buildings (Pre-Assembled)

Sizes Range from 6x8 to 14x24

Select Wall Panel Design

- Non-Insulated Solid Concrete Walls (Zero R Value 3-4" thick depending on height of walls) Insulated Sandwich Panel (R-26, 6.5" thick)

| Exterior | Interior (3" wall) | Interior (6.5" SP) | Interior Height | | | |
|------------------------------------|--------------------|--------------------|-----------------------------|-----------------------------|------------------------------|--------------------------------|
| <input type="checkbox"/> 8' x 8' | 7'-6"x7'-6" | 6'-11"x6'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |
| <input type="checkbox"/> 8' x 10' | 7'-6"x9'-6" | 6'-11"x8'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |
| <input type="checkbox"/> 8' x 12' | 7'-6"x9'-6" | 6'-11"x10'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |
| <input type="checkbox"/> 10' x 10' | 9'-6"x9'-6" | 8'-11"x8'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |
| <input type="checkbox"/> 10' x 12' | 9'-6"x11'-6" | 8'-11"x10'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |
| <input type="checkbox"/> 10' x 20' | 9'-6"x19'-6" | 8'-11"x18'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |
| | Interior (4" wall) | | | | | |
| <input type="checkbox"/> 12' x 16' | 11'-4" x 15'-4" | 10'-11"x14'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |
| <input type="checkbox"/> 12' x 18' | 11'-4" x 17'-4" | 10'-11"x16'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |
| <input type="checkbox"/> 12' x 20' | 11'-4" x 19'-4" | 10'-11"x18'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |
| <input type="checkbox"/> 12' x 24' | 11'-4" x 23'-4" | 10'-11"x22'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |
| <input type="checkbox"/> 14' x 24' | 13'-4" x 12'-4" | 12'-11"x22'-11" | <input type="checkbox"/> 8' | <input type="checkbox"/> 9' | <input type="checkbox"/> 10' | <input type="checkbox"/> Other |

Select Custom Size (exterior dimensions)

Width: _____ Length: _____ Interior Height: _____

2. EASI-SPAN™ Site Erect LARGE Pre-cast Building Dimensions

Select Wall Panel Design

- Non-Insulated Solid Concrete Walls (Zero R Value 3-4" thick depending on height of walls) Insulated Sandwich Panel Walls (R-26, 6.5" thick wall)

Width

- 20' 24'
 30' 40'

Length

In Units of 10' _____

Interior Height

- 8' 9' 10'
 Other

EXTERIOR FINISHES

- Rubbed Finish Trowel Finish
 Broom Finish Ceramic Roof Coating (R-19 insulation value)
 Exposed Aggregate
 Brick
 Red Gray Brown Desert Sand Other: _____

INTERIOR FINISHES

- Smooth Gray Concrete Only
 Painted Concrete Interior (2 part Epoxy Paint – ICI / Devoe)
 FRP (Fiberglass Reinforced Plastic)
 Insulation – Desired R-Value Ceiling: Walls:
 Other: _____

DOORS

- Single 3070 (3'0" x 7'0" x 1.75")
 Single 4070 (4'0" x 7'0" x 1.75")
 Double 6070 ((2)-3070 Doors)
 Double 8070 ((2) 4070 Doors)
 Painted Galvanized Steel Stainless Steel Fiberglass
 Overhead Rolling Steel Door – SIZE: _____
 Other: _____

DOOR HARDWARE

- Panic Hardware
 ADA Hardware
 Deadbolt Brand: _____

DOOR HANDLE

- Pullhandle Stainless Steel NRP Hinges Surface Bolts
 Thumbblatch Weather Strip Drip Cap
 Passage Knob Door Sweep Door Stop
 Lever Lock Threshold (Flat or Gasket)
 Closer Astragal
 Holdopen Arm Door Stop

ELECTRICAL

Service Size: 60 AMP 100 AMP 200 AMP 400 AMP Other: _____

Lighting

Incandescent – Description: _____

Fluorescent – Description: _____

Receptacles

Interior – Quantity: 10 _____

Exterior – Quantity: _____

Miscellaneous:

Description:

AIR CONDITIONING * HEATING * VENTILATION

Forced Air w/Air Conditioning – SIZE: _____

Heater – KW (ie-3, 5, 7 KW): _____

OTHER: _____

Roof/Wall Ventilation – Required CFM: _____

Exhaust

Intake

Exhaust Fan –SIZE: _____

Louvers

Intake – Size: _____

Motorized: Yes No

Exhaust—Size: _____

Motorized: Yes No

EQUIPMENT TYPE

Standard Explosion Proof – Class: _____ Division: _____ Group: _____

SPECIAL EQUIPMENT

Description: