

Type II Technical Chart

Used for Street Lighting, Parking Lot and Security Lighting, Recreational and Industrial Lighting

Direct Embedment

CATALOG NUMBER SMOOTH GRAY	MOUNTING HEIGHT (Ft.)	POLE WEIGHT (Lbs.)	OVERALL LENGTH (Ft.)	POLE SIZE (In.)		EPA AT POLE TIP (Sq. Ft.)					ULTIMATE GROUNDLINE MOMENT (Ft. Lbs.)	BREAKING LOAD 2 Ft. FROM TIP (Lbs.)
				TIP	BUTT	90 MPH	110 MPH	130 MPH	140 MPH	160 MPH		
252002	20.5	1667	25.0	6.0	10.06	102	65	44	37	26	38,100	2,059
302002	25.0	2,220	30.0	6.0	10.88	88	55	36	30	20	43,100	1,873
352002	29.5	2,863	35.0	6.0	11.69	77	47	30	24	15	47,900	1,741
402002	34.0	3,601	40.0	6.0	12.50	68	40	25	19	11	52,900	1,653
452002	38.5	4,442	45.0	6.0	13.31	61	35	20	15	7	57,700	1,580
502002	43.0	5,392	50.0	6.0	14.13	54	29	15	10	3	62,500	1,524
552002	47.5	6,537	55.0	6.0	14.94	98	58	35	27	15	114,900	2,525
602002	52.0	7,732	60.0	6.0	15.75	94	55	32	27	12	127,000	2,540
652002	56.5	9,055	65.0	6.0	16.56	89	50	28	20	9	137,900	2,530
702002	61.0	10,514	70.0	6.0	17.38	84	45	24	16	5	147,700	2,503

General Information

1. Different colors, finishes and exposed aggregates are available upon request.
2. Longer lengths of poles available upon request.
3. All corners are chamfered.
4. 7,000 PSI concrete is standard; higher strengths are available if required.
5. STRENGTH: In most cases a higher ground line moment and a higher breaking strength and EPA can be attained without going to a larger pole.
6. EFFECTIVE PROJECTED AREA (EPA): Lonestar Prestress Mfg. concrete poles and mounting arms have been designed in accordance with accepted engineering practices to be structurally capable of withstanding wind loads and velocity pressure per ASCE 7-05. Poles to meet higher wind loads are available.
7. HOLES: Holes are precast to meet your specifications and requirements for mounting attachments, most any desired arrangement can be provided. Contact Lonestar Prestress Mfg. for any questions about field drilling light poles.
8. INSTALLATION: Lonestar Prestress Mfg. concrete poles are designed for setting directly into the ground, without the use of precast foundations, similar to the setting of wood poles. After the hole is drilled, the pole is set and plumbed, the earth is then backfilled and tamped. The depth is dependent on the nature of the soil and the anticipated load. Where it is impossible to embed the poles in the ground, such as on bridges or overpasses, a bolt-down base plate is available.
9. To specify a base plate for base mounted poles add the suffix BP to catalog numbers. Customer to supply the bolt circle drawings or template.

