



BUILDING SPECIFIER'S WORKSHEET

The Lonestar Prestress, Mfg. specifier's worksheet can be used as an aid to request a quote for a standard or custom building. Please complete all items that apply to your particular environment. Fax or email this form back to us at (713) 896-0762 or ordersleo@lonestarprestress.com and a quote will be prepared for you. Please include a brief description of anything you would like included that is not listed. For further information or questions, please call us at (713) 896-0994 or toll free at (800) 600-1719.

GENERAL INFORMATION

Your Name: _____ Title: _____
 Company Name: _____
 Address: _____
 City: _____ State: _____ Zip Code: _____
 Phone: _____ Fax: _____ Email: _____

BUILDING INFORMATION

Project Name: _____ Title: _____
 Project Location: _____
 Intended Use: _____
 Expected Delivery Date: _____

BUILDING DESCRIPTION

Standard Precast Building Dimensions (Pre-Assembled)

<u>Exterior Dimensions</u>	<u>Interior Dimensions</u>	<u>Interior Height</u>				<u>Custom</u>
<input type="checkbox"/> 8' x 8'	<input type="checkbox"/> 7'-6" x 7'-6"	<input type="checkbox"/> 8'	<input type="checkbox"/> 9'	<input type="checkbox"/> 10'	<input type="checkbox"/>	_____
<input type="checkbox"/> 8' x 10'	<input type="checkbox"/> 7'-6" x 9'-6"	<input type="checkbox"/> 8'	<input type="checkbox"/> 9'	<input type="checkbox"/> 10'	<input type="checkbox"/>	_____
<input type="checkbox"/> 10' x 12'	<input type="checkbox"/> 9'-6" x 11'-6"	<input type="checkbox"/> 8'	<input type="checkbox"/> 9'	<input type="checkbox"/> 10'	<input type="checkbox"/>	_____
<input type="checkbox"/> 12' x 20'	<input type="checkbox"/> 11'-4" x 19'-4"	<input type="checkbox"/> 8'	<input type="checkbox"/> 9'	<input type="checkbox"/> 10'	<input type="checkbox"/>	_____
<input type="checkbox"/> 14' x 24'	<input type="checkbox"/> 13'-4" x 12'-4"	<input type="checkbox"/> 8'	<input type="checkbox"/> 9'	<input type="checkbox"/> 10'	<input type="checkbox"/>	_____

Standard "LARGE" Pre-cast Building Dimensions (SITE ERECTED)

Width 20' 24' 30' 40' Length In Units of 10' _____ Interior Height 8' 9' 10' Custom _____

CUSTOM BUILDING DIMENSIONS

Width: _____ Length: _____ Interior Height: _____

Concrete Panel Design

Non-Insulated Solid Concrete Walls
(typically 3-4" thick depending on building size)

Insulated Sandwich Panel Walls (R-26 value, 6.5" thick wall)

EXTERIOR FINISHES

Rubbed Finish

Trowel Finish

Broom Finish

Ceramic Roof Coating (R-19 insulation value)

Exposed Aggregate

Brick

Red Gray Brown Desert Sand Other: _____

INTERIOR FINISHES

Smooth Gray Concrete Only

Painted Concrete Interior (2 part Epoxy Paint – ICI / Devco)

FRP (Fiberglass Reinforced Plastic)

Insulation – Desired R-Value Ceiling: Walls:

Other: _____

DOORS

Single 3070 (3'0" x 7'0" x 1.75")

Single 4070 (4'0" x 7'0" x 1.75")

Double 6070 ((2)-3070 Doors)

Double 8070 ((2) 4070 Doors)

Painted Galvanized Steel Stainless Steel Fiberglass

Overhead Rolling Steel Door – SIZE: _____

Other: _____

DOOR HARDWARE

Panic Hardware

ADA Hardware

Deadbolt Brand: _____

DOOR HANDLE

Pullhandle

Stainless Steel NRP Hinges

Surface Bolts

Thumbblatch

Weather Strip

Drip Cap

Passage Knob

Door Sweep

Door Stop

Lever Lock

Threshold (Flat or Gasket)

Closer

Astragal

Holdopen Arm

Door Stop