

## Type I Simplex Technical Chart

Used for Street Lighting



### Direct Embedment

CATALOG NUMBER SMOOTH GRAY	MOUNTING HEIGHT (Ft.)	POLE WEIGHT (Lbs.)	OVERALL LENGTH (Ft.)	POLE SIZE (In.)		EPA AT POLE TIP (Sq. Ft.)					ULTIMATE GROUNDLINE MOMENT (Ft. Lbs.)	BREAKING LOAD 2 Ft. FROM TIP (Lbs.)
				TIP	BUTT	90 MPH	110 MPH	130 MPH	140 MPH	160 MPH		
181602	14.2	718	18.0	4.8	7.73	54	34	23	19	14	16,500	1,1352
231602	18.7	1,050	23.3	4.8	8.54	47	29	19	16	11	19,000	1,137
281602	23.2	1,451	28.0	4.8	9.35	40	24	15	12	7	21,500	1,014
301602	25.0	1,633	30.0	4.8	9.68	37	22	13	10	6	22,500	978
331602	27.7	1,929	33.0	4.8	10.16	34	20	11	9	4	24,000	933
361602	29.5	2,150	35.0	4.8	10.5							

### General Information

1. Different colors, finishes and exposed aggregates are available upon request.
2. Longer lengths of poles available upon request.
3. All corners are chamfered.
4. 7,000 PSI gray concrete is standard; higher strengths are available if required. The EPA's listed for poles using 7,000 psi concrete shall be reduced by 15% when decorative mixes are used.
5. STRENGTH: In most cases a higher ground line moment and a higher breaking strength and EPA can be attained without going to a larger pole.
6. EFFECTIVE PROJECTED AREA (EPA): Lonestar Prestress Mfg. concrete poles and mounting arms have been designed in accordance with accepted engineering practices to be structurally capable of withstanding wind loads and velocity pressure per ASCE 7-05. Poles to meet higher wind loads are available.
7. HOLES: Holes are precast to meet your specifications and requirements for mounting attachments, most any desired arrangement can be provided. Contact Lonestar Prestress Mfg. for any questions about field drilling light poles.
8. INSTALLATION: Lonestar Prestress Mfg. concrete poles are designed for setting directly into the ground, without the use of precast foundations, similar to the setting of wood poles. After the hole is drilled, the pole is set and plumbed, the earth is then backfilled and tamped. The depth is dependent on the nature of the soil and the anticipated load. Where it is impossible to embed the poles in the ground, such as on bridges or overpasses, a bolt-down base plate is available.
9. To specify a base plate for base mounted poles add the suffix BP to catalog numbers. Customer to supply the bolt circle drawings or template.



# Type I Simplex Pole

## Type I Simplex Typical Details

POLE	BUTT
18 FT.	7.73"x7.73"
23 FT.	8.54"x8.54"
28 FT.	9.35"x9.35"
30 FT.	9.68"x9.68"
33 FT.	10.16"x10.16"
38 FT.	10.98"x10.98"

- WE ARE NOT RESTRICTED TO THESE STANDARD DETAILS AND WELCOME ANY SPECIAL DESIGNS. YOU MAY USE THE STANDARD DRAWING TO MARK UP AND SEND TO YOUR SALES REPRESENTATIVE OR SEND DIRECTLY TO US.
- CABLE ENTRANCE AVAILABLE WITH CONDUIT COUPLINGS.

