

# Domain



<b>Construction</b>	Tufted Cut Pile Carpet
<b>Yarn</b>	100% Solution Dyed Nylon
<b>Width</b>	3.66m
<b>Standard Roll Length</b>	30m
<b>Yarn Weight</b>	1490g/m <sup>2</sup> / 44oz/yd <sup>2</sup>
<b>Total Weight</b>	2500g/m <sup>2</sup>
<b>Pile Height</b>	11.5mm
<b>Total Thickness</b>	13.5mm
<b>Machine Gauge</b>	1/8th
<b>Primary Backing</b>	Woven Polypropylene
<b>Secondary Backing</b>	Action Fleece
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	< 2kV
<b>Fire Rating</b>	CRF 4.6kW/m <sup>2</sup> (ISO 9239-1)
<b>Anti-allergenic Properties</b>	Will not shed or pill. Resistant to mould & mildew.
<b>Underfloor Heating</b>	Suitable
<b>Stair Rating</b>	Suitable
<b>Rating</b>	Extra Heavy Duty Residential Medium Duty Commercial
<b>Warranties</b>	10 Year Residential Warranty 5 Year Commercial Warranty
<b>Installation</b>	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
<b>Environmental</b>	CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

## A World of Perfect Choices