


ONTARIO - MONTCLAIR SCHOOL DISTRICT

TRANSPORTATION CENTER

CitySubmittal - Registration #B202301766

3/3/23





<u>OWNER</u>

Ontario - Montclair School District 950 W. D ST. Ontario, CA 91762 t: 909-345-6789 Contact: Brooke Murray

ARCHITECT

PBK Architects
8163 Rochester Avenue
Rancho Cucamonga, CA 91730
t: 909.987.0909
Contact: Juan Cervera

MEP ENGINEER

LEAF 8163 Rochester Avenue Rancho Cucamonga, CA 91730 t: 909.987.0909 Contact: Rex Wang

STRUCTURAL ENGINEER

RTM Engineering Consultants
9931 Muirlands Blvd
Irvine, CA 92626
t: 949.462.3200
Contact: Josh Randall

PBK


ATION CENTER


PROJECT ADDRESS:
1442 South Bon View
Ontario, Ca 91761
CitySubmittal - Registration #R






COVER SHEET







PBK

RANCHO CUCAMONGA
8163 Rochestser Avenue, Suite 100
Rancho Cucamonga
California 91730
P 909-987-0909

B202301766

City of Ontario | Building Department
APPROVED & REVIEWED
FOR CODE COMPLIANCE
The issuance of a permit and approval
of these plans shall not be construed to
permit or approve any violation of the
applicable codes or ordinances.

Date: <u>01/16/2024</u> 1:34:37 PM


REVIEWED


FOR


FOR
CODE COMPLIANCE
Dec 15, 2023
BPR CONSULTING GROUP


CENTER

PROJECT ADDRESS:
1442 South Bon View
Ontario, Ca 91761











D. 1
Dat
10/23/
12/08/
3017
3

G0.04




8163 Rochestser Avenue, Suite 100


City of Ontario | Building Department The issuance of a permit and approval of these plans shall not be construed to permit or approve any violation of the applicable codes or ordinances.





NORTH: PLAN TRUE




		ENT	
ONT	ARIO - MONTCLA		
	DATE 3/3/23	PROJECT 220	
REVIS	SIONS		
No.	Descript	tion	Da
City	Submittal - Regis	stration #B20	23017










RANCHO CUCAMONGA 8163 Rochestser Avenue, Suite 100


APPROVED & REVIEWED he issuance of a permit and approval of these plans shall not be construed to

NORTH: PLAN TRUE



ONTARIO - MONTCLAIR SCHOOL DISTRI PROJECT NUMBER 220316 CitySubmittal - Registration #B202301766

WALLS, DOORS & **MISCELLANEUS**



TITLE 24 NOTES THE FOLLOWING SHALL BE REQUIRED WHETHER OR NOT SPECIFICALLY SHOWN OR MENTIONED IN DRAWINGS AND/OR SPECIFICATIONS: EQUIPMENT SHALL MEET EFFICIENCY REQUIREMENTS OF TABLES 110.2-A THROUGH 110.2-K. ALL AIR-COOLED, UNITARY, DX UNITS (PACKAGED, SPLIT-SYSTEM, HEAT PUMPS AND VRF) WITH ECONOMIZERS SHALL BE EQUIPPED WITH FAULT DETECTION AND DIAGNOSTICS SYSTEMS PIPE INSULATION FOR SPACE CONDITIONING AND SERVICE WATER-HEATING WITH FLUID TEMPERATURES LISTED IN TABLE 120.3-A SHALL HAVE INSULATION LEVELS AS SPECIFIED IN SUBSECTION (A) AND (B) MECHANICAL HEATING AND COOLING EQUIPMENT SHALL BE THE SMALLEST SIZE, WITHIN THE AVAILABLE OPTIONS OF THE DESIRED EQUIPMENT LINE, NECESSARY TO MEET THE DESIGN HEATING AND COOLING LOADS OF THE BUILDING, AS CALCULATED ACCORDING TO THE REQUIREMENTS OF SECTION HVAC MOTORS FOR FANS THAT ARE LESS THAN 1 HP AND 1/12 HP OR GREATER SHALL BE ECM OR HAVE A MINIMUM MOTOR EFFICIENCY OF 70%. MOTORS SHALL ALSO HAVE MEANS TO ADJUST MOTOR SPEED FOR BALANCING OR REMOTE CONTROL ELECTRIC RESISTANCE HEATING SYSTEMS ARE NOT PROVIDED FOR SPACE IN DRIER CLIMATES AND WHEN LARGE OUTDOOR AIR FRACTIONS ARE REQUIRED. EVAPORATIVE PRE-COOLING PACKAGES WERE EVALUATED TO PRE-COOL OUTSIDE AIR AND COOL THE AIR FLOWING OVER THE DX CONDENSING UNIT. ZONE EACH AIR HANDLER TO SERVE ONLY AREAS WITH COMMON LOADS TO ALLOW MORE AGGRESSIVE CONTROL STRATEGIES AND IMPROVE COMFORT. HAVE DIFFERENT AHU'S SERVING CORE VS. PERIMETER AREAS. THE DESIGN ACCOMMODATES PARTIAL OCCUPANCY ENERGY SAVINGS WHEN THE OWNER'S REQUIREMENTS OR NARRATIVE DESCRIBE ANY POSSIBLITY OF PARTIAL OCCUPANCY. BY ZONING AIR HANDLERS BY FLOOR OR BY PART OF A FLOOR, OR BY INCORPORATING CONTROLLED FLOOR DAMPERS, OR VAV AIR TERMINALS GOING TOTALLY SHUT WHEN NOT OCCUPIED, ETC. EACH ZONE IS CONTROLLED BY AN INDIVIDUAL THERMOSTATIC CONTROL. CONTROLS SHALL BE CAPABLE OF SETTING TEMPERATURES TO 55 DEG F FOR HEATING AND 85 DEG F FOR COOLING AND PROVIDE A TEMPERATURE DEADBAND OF AT LEAST 5 DEG F IF CONTROLLING BOTH HEATING AND COOLING. EACH SPACE CONDITIONING SYSTEM SHALL BE EQUIPPED WITH CONTROLS TO SHUT THE SYSTEM OFF DURING PERIODS OF NONUSE AND WILL TEMPORARILY OPERATE THE SYSTEM TO MAINTAIN SETBACK AND SETUP TEMPERATURES WHILE KEEPING VENTILATION DAMPERS CLOSED SYSTEMS SERVING MULTIPURPOSE ROOMS LESS THAN 100 SF AND CLASSROOMS, CONFERENCE, AUDITORIUM OR MEETING CENTER ROOMS GREATER THAN 750 SF SHALL HAVE OCCUPANCY SENSORS THAT INTERFACE WITH HVAC CONTROLS TO AUTOMATICALLY SETUP THE COOLING SETPOINT BY 2F OR MORE AND AUTOMATICALLY RESET THE MINIMUM REQUIRED VENTILATION RATE. THESE OCCUPANT SENSOR VENTILATION CONTROL DEVICES MUST MEET THE REQUIREMENTS OF SECTION 120.1(C)5. OUTDOOR AIR SUPPLY AND EXHAUST EQUIPMENT SHALL BE INSTALLED WITH DAMPERS THAT AUTOMATICALLY CLOSE UPON EF FAN SHUTDOWN. HVAC SYSTEMS WITH DDC TO THE ZONE LEVEL SHALL BE PROGRAMMED TO ALLOW CENTRALIZED DEMAND SHED FOR NON-CRITICAL ZONES. ZONE CONTROLS PREVENT REHEATING, RECOOLING AND SIMULTANEOUS PROVISIONS OF HEATING AND COOLING TO THE SAME ZONE. EACH WALL MOUNTED THRMOSTAT SHALL BE LOCATED AWAY FROM POTENTIAL SOURCES THAT WOULD ADVERSELY AFFECT THE READING (CLOSE TO COPIERS, DIRECT SUNLIGHT. BELOW OR ABOVE A SUPPLY AIR DIFFUSER OR CONVECTOR, ETC.). ANY THERMOSTATS MOUNTED ON EXTERIOR WALLS SHALL BE INSTALLED IN SEALED AND INSULATED JUNCTION BOXES. CORNER OFFICE SHALL ALWAYS HAVE THEIR OWN THERMOSTATS, AIR TERMINAL BOXES OR FIN-TUBE RADIATORS. CONTROL SEQUENCES SHALL BE LISTED FOR EQUIPMENT OPERATED BY STAND-ALONE PACKAGED CONTROLS. UNOCCUPIED SEQUENCES SHALL BE INCLUDED. CONTROL SEQUENCES SHALL BE PROVIDED FOR EACH PIECE OF EQUIPMENT LISTED IN THE EQUIPMENT SCHEDULE THAT IS MONITORED OR CONTROLLED BY THE BUILDING AUTOMATION SYSTEM (BAS). UNOCCUPIED SEQUENCES SHALL BE INCLUDED OUTSIDE AIR TEMPERATURE SENSORS SHALL BE IN A COMMERCIALLY DESIGNED SOLAR SHIELD LOCATED ON A NORTH WALL OR SOME OTHER LOCATION OUT OF DIRECT SUNLIGHT AND AWAY FROM BUILDING EXHAUST OR HEAT REJECTION THE OUTDOOR AIR-VENTILATION RATE AND AIR-DISTRIBUTION ASSUMPTIONS MADE IN THE DESIGN OF THE VENTILATING SYSTEM ARE CLEARLY IDENTIFIED ON EACH SPACE IS DESIGNED TO HAVE NATURAL VENTILATION OR MECHANICAL VENTILATION THAT IS NO LESS THAN THE LARGER OF CONDITIONED FLOOR AREA TIMES THE REQUIREMENTS IN TABLE 120.1-A OR 15 CFM TIMES THE EXPECTED NUMBER OF OCCUPANTS THE MINIMUM AND MAXIMUM OUTDOOR AIR RATES FOR EACH AIR HANDLER ARE LISTED ON THE EQUIPMENT SCHEDULES THE OUTDOOR AIR-VENTILATION RATES ARE BASED ON PLANNED OWNER OCCUPANCY AS DEFINED IN OWNER'S DESIGN INTENT AND ARE NOT BASED ON MAXIMUM EGRESS OCCUPANCY RATES HVAC SYSTEMS THAT HAVE AN ECONOMIZER, SERVE A SPACE WITH A DESIGN OCCUPANT DENSITY GREATER THAN OR EQUAL TO 25 PEOPLE PER 1000 SF, AND ARE EITHER A SINGLE ZONE SYSTEM WITH ANY CONTROLS OR MULTIPLE ZONE SYSTEM WITH DDC CONTROLS TO THE ZONE LEVEL MUST HAVE DEMAND CONTROL VENTILATION CONTROLS. THE FOLLOWING MUST BE MET: A. CO2 SENSORS INSTALLED IN EACH ROOM SERVED BY SYSTEMS WITH DCV B. CO2 SENSORS ARE LOCATED BETWEEN 3 FT AND 6 FT ABOVE THE FLOOR. C. CO2 CONCENTRATIONS MAINTAINED AT LESS THAN OR EQUAL TO 600 PPM PLUS OUTDOOR PPM. D. DURING HOURS OF EXPECTED OCCUPANCY, CONTROLS MAINTAIN THE SYSTEM VENTILATION RATE. EACH COOLING FAN SYSTEM THAT HAS A DESIGN MECHANICAL COOLING CAPACITY OVER 54,000 BTU/H SHALL HAVE AN AIR ECONOMIZER OR A WATER ECONOMIZER. AIR ECONOMIZERS MUST COMPLY WITH THE HIGH LIMIT SHUTOFF CONTROLS SHOWN IN TABLE 140.4-B. INTEGRATED ECONOMIZER CONTROLS SHALL BE SET UP SUCH THAT PARTIAL COOLING IS PROVIDED BY THE ECONOMIZER EVEN WHEN ADDITIONAL MECHANICAL COOLING ID REQUIRED. ECONOMIZER DAMPERS SHALL BE DRIVEN BY DIRECT DRIVE ACTUATORS RATHER THAN ROD LINKAGES, WHICH CAN BE A MAJOR CAUSE OF ECONOMIZER BAROMETRIC RELIEF IS USED, IF POSSIBLE. IF NOT, RELIEF FANS (RATHER THAN RETURN FANS) SHALL BE USED IN MOST CASES. OUTDOOR AND RETURN AIR SENSORS SHALL BE PROPERLY SELECTED, PROPERLY LOCATED TO PROVIDE ACCURATE AND REPEATABLE MEASUREMENTS FOR CONTROLLING ECONOMIZER OPERATION. AVERAGING SENSORS COVER THE ENTIRE DUCT OR COIL FACE AREAS. ALL AIR DISTRIBUTION SYSTEM DUCTS AND PLENUMS MUST BE INSTALLED, SEALED AND INSULATED AS REQUIRED BY 120.4(A). DUCT SEALING LEAKAGE RATES SHALL BE NO MORE THAN 6% OF AIR FLOW FOR NEW DUCT SYSTEMS AND NO MORE THAN 15% OF AIR FLOW FOR ALTERED EXISTING DUCT SYSTEMS. DUCT SHALL UTILIZE LOW STATIC PRESSURE DESIGN. IDENTIFY THE MOST RESTRICTIVE BRANCH FROM THE FAN TO THE LAST AIR TERMINAL UNIT. IDENTIFY POSSIBLE MEANS OF SIGNIFICANTLY REDUCING THE PRESSURE DROP. BRANCH 45. CONTRACTOR SHALL COORDINATE ALL DUCTWORK ROUTING WITH WORK OF OTHER TRADES AND MAKE ANY OFFSET AS DUCT SYSTEMS SHALL DESIGNED FOR EQUAL PRESSURE DROP, WHEN POSSIBLE. DUCT BRANCHES WITH SIGNIFICANTLY DIFFERING STATIC PRESSURE 46. COORDINATE ALL EQUIPMENT VOLTAGES WITH ELECTRICAL PRIOR TO ORDERING ANY EQUIPMENT. REQUIREMENTS SHALL HAVE VOLUME CONTROL STRATEGICALLY PLACED TO FAN SHALL DISCHARGE INTO DUCT SECTIONS THAT REMAIN STRAIGHT FOR AS LONG AS POSSIBLE (IDEALLY 10 DUCT DIAMETERS) TO REDUCE FAN INEFFICIENCIES FROM SYSTEM EFFECTS DUCT VELOCITIES SHALL GENERALLY BE BELOW 2,000 FPM FOR DUCTS IN CEILING PLENUMS, 1500 FPM FOR EXPOSED DUCTS AND 3500 FPM IN MECHANICAL ROOMS AND NON-NOISE SENSITIVE SHAFTS AND DO NOT REDUCE ANY DUCT SIZES LISTED ON PLANS. DUCT FRICTION RATES SHALL GENERALLY BE LESS THAN 0.25" WC PER 100 LINEAL FEET NEARER THE FAN, 0.15 TO 0.20" IN THE MAIN DUCTS AND 0.08 TO 0.12" WC/100' NEARER THE END OF THE SYSTEM. DESIGNS OVER THESE RATES SHALL BE QUESTIONED. VERY ENERGY EFFICIENT DESIGN CAN LOWER THESE VALUES BY UP TO 40% CONTRACTOR SHOP DRAWINGS SHALL BE SUFFICIENTLY DETAILED TO ENSURE THAT DISTRIBUTION SYSTEM DESIGN INTENT IS ADEQUATELY CONVEYED TO MATCH PLANS. IF SUFFICIENT DETAIL IS NOT INCLUDED IN DRAWINGS, INSTALLATIONS MAY RESULT IN SIGNIFICANTLY HIGHER PRESSURE DROPS AND HENCE HIGHER ENERGY CONSUMPTION AND OTHER OPERATING ISSUES. ACCEPTANCE REQUIREMENTS ARE CLEARLY IDENTIFIED IN CONSTRUCTION COMMISSIONING MEASURES OR REQUIREMENTS ARE REFLECTED IN THE CONSTRUCTION DOCUMENTS REQUIREMENTS FOR FUNCTIONAL PERFORMANCE TESTS ARE REFLECTED IN THE CONSTRUCTION DOCUMENTS. COOLING SYSTEMS IDENTIFIED IN TABLE 140.4-D SHALL HAVE FAN CONTROLS TO VARY THE INDOOR FAN AIRFLOW AS A FUNCTION OF LOAD: A. DX AND CHILLED WATER COOLING SYSTEMS THAT CONTROL CAPACITY BASED ON OCCUPIED SPACE TEMPERATURE SHALL HAVE A MINIMUM OF 2 STAGES OF CONTROL. B. SYSTEMS THAT CONTROL SPACE TEMPERATURE BY MODULATING AIRFLOW TO THE SPACE SHALL HAVE PROPORTIONAL FAN CONTROL. C. SYSTEMS WITH AIR SIDE ECONOMIZER SHALL HAVE A MINIMUM OF 2 SPEEDS OF FAN CONTROL DURING ECONOMIZER OPERATION. FAN CABINET ENCLOSURE AND INTERNAL COMPONENTS SHALL BE ELECTED TO MINIMIZE PRESSURE DROP, E.G. FACE VELOCITY IS LESS THAN 500 FPM, LOW PRESSURE DROP COILS, FILTERS, ETC. FAN WHEEL SHALL BE SELECTED FOR EFFICIENT OPERATION, E.G. LARGER

GENERAL NOTES MEP COMPONENT ANCHORAGE NOTE 1. ALL WORK SHALL BE IN CONFORMANCE WITH TITLE 24, 2022 CALIFORNIA CODE OF REGULATIONS (CCR), 2022 CALIFORNIA BUILDING CODE, PART 2, TITLE 24 CCR, 2022 CALIFORNIA MECHANICAL CODE, PART 4, TITLE 24 CCR, ALL OTHER ALL MECHANICAL, PLUMBING AND ELECTRICAL COMPONENTS SHALL BE ANCHORED AND INSTALLED PER THE DETAILS ON APPLICABLE CODES AND REGULATIONS, SMACNA AND ASHRAE GUIDELINES, AND LOCAL CODES. THE DSA APPROVED CONSTRUCTION DOCUMENTS. THE FOLLOWING COMPONENTS SHALL BE ANCHORED OR BRACED TO 2. ALL HVAC EQUIPMENT SHALL BE COMPLIANT WITH EFFICIENCY STANDARDS PER TITLE-24, PART 6 MEET THE FORCE AND DISPLACEMENT REQUIREMENTS PRESCRIBED IN THE 2022 CBC. SECTIONS 1617A.1.18 THROUGH 3. ALL FRESH AIR INTAKES SHALL BE AT LEAST 10 FEET IN A HORIZONTAL DIRECTION FROM ALL EXHAUST, FLUE, FUEL 1617A.1.26 AND ASCE 7-16 CHAPTER 13, 26 AND 30: BURNING APPLIANCE AND PLUMBING VENT OUTLETS. FOR GAS/ELECTRIC AIR CONDITIONING UNITS WHERE THE CODE REQUIRED CLEARANCES ARE NOT MET, A FACTORY FLUE GAS DEFLECTOR AND EXTENSION SHALL BE USED TO MINIMIZE ALL PERMANENT EQUIPMENT AND COMPONENTS. THESE CLEARANCES. CONTRACTOR SHALL DETERMINE LOCATIONS WHERE REQUIRED PRIOR TO BID. THIS SHALL BE PROVIDED AT NO ADDITIONAL COST TO THE OWNER. 2. TEMPORARY, MOVABLE OR MOBILE EQUIPMENT THAT IS PERMANENTLY ATTACHED (e.g. HARD WIRED) TO THE 4. AIR FILTERS SHALL BE STATE FIRE MARSHAL APPROVED AND LISTED. PREFORMED FILTERS HAVING COMBUSTIBLE BUILDING UTILITY SERVICES SUCH AS ELECTRIC, GAS OR WATER. "PERMANENTLY ATTACHED" SHALL INCLUDE FRAMING SHALL BE TESTED AS A COMPLETE ASSEMBLY. AIR FILTERS IN ALL OCCUPANCIES SHALL BE PER TITLE-24 PART 6 ALL ELECTRICAL CONNECTIONS EXCEPT PLUGS FOR 110/220 VOLT RECEPTACLES HAVING A FLEXIBLE CABLE. AND APPLICABLE ASHRAE REQUIREMENTS. FILTERS SHALL BE ACCESSIBLE REVIEW THESE PLANS AND SPECIFICATIONS PRIOR TO BID. REVIEW PLANS AND SPECIFICATIONS OF OTHER RELATED TEMPORARY, MOVABLE OR MOBILE EQUIPMENT WHICH IS HEAVIER THAN 400 POUNDS OR HAS A CENTER OF TRADES INCLUDING ARCHITECTURAL, STRUCTURAL, ELECTRICAL, AND FIRE PROTECTION. MASS LOCATED 4 FEET OR MORE ABOVE THE ADJACENT FLOOR OR ROOF LEVEL THAT DIRECTLY SUPPORT THE 6. REFER TO SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS AS THESE ARE PART OF THE CONTRACT DOCUMENTS. COMPONENT IS REQUIRED TO BE RESTRAINED IN A MANNER APPROVED BY DSA. WHERE A CONFLICT OCCURS BETWEEN THIS SPECIFICATION AND OTHER SPECIFICATIONS ISSUED AS A PART OF THE CONTRACT DOCUMENTS, THE MORE STRINGENT REQUIREMENT SUPERCEDES. THE FOLLOWING MECHANICAL AND ELECTRICAL COMPONENTS SHALL BE POSITIVELY ATTACHED TO THE STRUCTURE BUT THESE DRAWINGS ARE DIAGRAMMATIC ONLY AND NOT INTENDED TO INDICATE ALL REQUIRED OFFSETS, BENDS, ELBOWS. NEED NOT DEMONSTRATE DESIGN COMPLIANCE WITH THE REFERENCES NOTED ABOVE. THESE COMPONENTS SHALL TRANSITIONS, FITTINGS AS REQUIRED TO CONFORM TO THE BUILDING STRUCTURE, CLEARANCE INSIDE CEILINGS, HAVE FLEXIBLE CONNECTIONS PROVIDED BETWEEN THE COMPONENT AND ASSOCIATED DUCTWORK, PIPING, AND AVOIDANCE OF OBSTRUCTIONS, AND MAINTAINING HEAD CLEARANCE. CONDUIT. FLEXIBLE CONNECTIONS MUST ALLOW MOVEMENT IN BOTH TRANSVERSE AND LONGITUDINAL DIRECTIONS: 8. COORDINATE INSTALLATION WITH ALL OTHER TRADES PRIOR TO INSTALLATION OF EQUIPMENT OR MATERIALS, INCLUDING BUT NOT LIMITED TO, STRUCTURAL, ARCHITECTURAL, ELECTRICAL, AND PLUMBING COMPONENTS WEIGHING LESS THAN 400 POUNDS AND HAVE A CENTER OF MASS LOCATED 4 FEET OR LESS COORDINATE THE LOCATIONS OF ALL CEILING DIFFUSERS, REGISTERS, AND GRILLES WITH THE ARCHITECTURAL ABOVE THE ADJACENT FLOOR OR ROOF LEVEL THAT DIRECTLY SUPPORT THE COMPONENT. REFLECTIVE CEILING PLANS, ELECTRICAL LIGHTING LAYOUT, AND ARCHITECTURAL ROOM ELEVATIONS. THE ARCHITECT AND ENGINEER SHALL BE IMMEDIATELY NOTIFIED OF ANY CONFLICTS PRIOR TO FABRICATION AND INSTALLATION. COMPONENTS WEIGHING LESS THAN 20 POUNDS, OR IN THE CASE OF DISTRIBUTED SYSTEMS, LESS THAN 5 10. COORDINATE THE LOCATION OF ALL ROOF OPENINGS AND THE LOCATIONS OF ALL ROOF MOUNTED EQUIPMENT WITH THE POUND PER FOOT, WHICH ARE SUSPENDED FROM A ROOF OR FLOOR OR HUNG FROM A WALL. STRUCTURAL AND ARCHITECTURAL WEIGHTS FOR PLATFORM AND CURB SIZES. FOR ROOF AND WALL PENETRATION DETAILS AND REQUIREMENTS, SEE ARCHITECTURAL AND STRUCTURAL DRAWINGS. REQUIRED PLATFORMS AND THE ANCHORAGE OF ALL MECHANICAL, ELECTRICAL AND PLUMBING COMPONENTS SHALL BE SUBJECT TO THE APPROVAL FLASHINGS FOR MECHANICAL EQUIPMENT SHALL BE AS INDICATED ON THE STRUCTURAL AND ARCHITECTURAL PLANS, OF THE DESIGN PROFESSIONAL IN GENERAL RESPONSIBLE CHARGE OR STRUCTURAL ENGINEER DELEGATED UNLESS NOTED OTHERWISE. RESPONSIBILITY AND ACCEPTANCE BY DSA. THE PROJECT INSPECTOR WILL VERIFY THAT ALL COMPONENTS AND I. HIRE A TEST AND BALANCE AGENCY TO PERFORM THE TESTING PROCEDURES. REQUIRED BY THE MECH-2A THROUGH EQUIPMENT HAVE BEEN ANCHORED IN ACCORDANCE WITH ABOVE REQUIREMENTS. MECH-11A CERTIFICATE OF ACCEPTANCE FORMS. AS APPLICABLE FOR ALL NEWLY INSTALLED HEATING AND COOLING SYSTEMS. THE CONTRACTOR AND TEST AND BALANCE AGENCY ARE RESPONSIBLE FOR OBTAINING THE CERTIFICATE OF ACCEPTANCE FORMS REQUIRED BY THE IOR. THE TEST AND BALANCE AGENCY SHALL BE WELL VERSED WITH ALL THE REQUIREMENTS OF THESE CERTIFICATE OF ACCEPTANCE FORMS. AND SHALL COORDINATE AND WORK WITH THE EQUIPMENT AND CONTROLS INSTALLERS TO COMPLY WITH THESE REQUIREMENTS IN A TIMELY MANNER WITHIN THE PROJECT SCHEDULE. THE AIR BALANCE CONTRACTOR SHALL BE A MEMBER OF AABC (ASSOCIATED AIR BALANCE 12. PAINT ALL EXPOSED DUCTWORK, DUCT SUPPORTS, ACCESSORIES, REGISTERS, GRILLES, DIFFUSERS, AND APPURTENANCES, WHETHER OR NOT COLORS ARE DESIGNATED IN SCHEDULES, EXCEPT WHERE A SURFACE OR MATERIAL IS SPECIFICALLY INDICATED NOT TO BE PAINTED OR IS TO REMAIN NATURAL. WHERE AN ITEM OR SURFACE IS NOT SPECIFICALLY MENTIONED. PAINT THE SAME AS SIMILAR ADJACENT MATERIALS OR SURFACES. IF COLOR OR FINISH IS NOT DESIGNATED, THE ARCHITECT WILL SELECT FROM STANDARD COLORS OR FINISHES AVAILABLE. PAINTING INCLUDES FIELD PAINTING EXPOSED BARE AND COVERED PIPES AND DUCTS (INCLUDING COLOR CODING), HANGERS, EXPOSED STEEL AND IRON WORK, AND PRIMED METAL SURFACES OF MECHANICAL EQUIPMENT 13. PROVIDE ALL LABOR, MATERIAL, INSURANCE, EQUIPMENT, INSTALLATION, CONSTRUCTION TOOLS, TRANSPORTATION, AND OTHER WORK AS REQUIRED. FOR A COMPLETE AND PROPERLY OPERATING MECHANICAL SYSTEM. PIPING, DUCTWORK, AND ELECTRICAL 14. ALL MATERIALS SHALL BE NEW AND OF THE SAME MANUFACTURER FOR EACH CLASS OR GROUP OF EQUIPMENT DISTRIBUTION SYSTEM BRACING NOTE EQUIPMENT SHALL BE LISTED AND APPROVED BY UNDERWRITER'S LABORATORIES, AND SHALL BEAR THE INSPECTION LABEL WHERE SUBJECT TO SUCH APPROVAL. MATERIALS SHALL MEET WITH THE APPROVAL OF THE GOVERNING BODIES HAVING JURISDICTION. MATERIALS SHALL BE MANUFACTURED AND INSTALLED IN ACCORDANCE WITH APPLICABLE STANDARDS ESTABLISHED BY THE LATEST EDITION OF CMC, CBC U.L., SMACNA AND ASHRAE GUIDELINES. INSTALL PER MANUFACTURERS' RECOMMENDATIONS, AND INSTALLATION INSTRUCTIONS. 15. OBTAIN AND PAY FOR ALL NECESSARY BUILDING PERMITS AND VARIANCES. COORDINATE TEMPORARY CONSTRUCTION PIPING, DUCTWORK, AND ELECTRICAL DISTRIBUTION SYSTEMS SHALL BE BRACED TO COMPLY WITH THE FORCES AND REQUIREMENTS WITH ALL TRADES PRIOR TO CONSTRUCTION. INCLUDE ALL COSTS IN THE BID. DISPLACEMENTS PRESCRIBED IN ASCE 7-16 SECTION 13.3 AS DEFINED IN ASCE 7-16 SECTION 13.6.5, 13.6.6, 13.6.7, 13.6.8; AND 16. IF THE CONTRACTOR PROPOSES ALTERNATE EQUIPMENT OR MATERIAL, THE CONTRACTOR SHALL BE RESPONSIBLE TO 2022 CBC, SECTION 1617A.1.24, 1617A.1.25, AND 1617A.1.26. OBTAIN ALL DSA APPROVALS, PAY ALL RELATED FEES AND OBTAIN APPROVAL FROM OWNER & ENGINEER OF RECORD. PROVIDE TITLE-24 COMPLIANCE CERTIFICATION AND ALL ASSOCIATED FEES REQUIRED. COORDINATE SUBMITTED THE METHOD OF SHOWING BRACING AND ATTACHMENTS TO THE STRUCTURE FOR THE IDENTIFIED DISTRIBUTION SYSTEM ARE EQUIPMENT WITH OTHER TRADES. INCLUDE IN THE SHOP DRAWINGS THE EQUIPMENT SUBMITTED FOR APPROVAL WITH A AS NOTED BELOW. WHEN BRACING AND ATTACHMENTS ARE BASED ON A PREAPPROVED INSTALLATION GUIDE (E.G., OSHPD DIFFERENT PHYSICAL SIZE OR ARRANGEMENT FROM THAT SHOWN. OPM FOR 2022 CBC OR LATER). COPIES OF THE BRACING SYSTEM INSTALLATION GUIDE OR MANUAL SHALL BE AVAILABLE ON PROVIDE SHOP DRAWINGS PER PROJECT SCHEDULE, SEE 23 00 00 SPECIFICATIONS FOR REQUIREMENTS. IF SHOP THE JOBSITE PRIOR TO START OF AND DURING THE HANGING AND BRACING OF DISTRIBUTION SYSTEMS. THE STRUCTURAL DRAWINGS ARE NOT PROVIDED TO THE ENGINEER FOR REVIEW, AND ANY CONFLICTS OCCUR BETWEEN TRADES. DURING CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL WORK NECESSARY TO RESOLVE THE CONFLICT AND | ENGINEER OF RECORD SHALL VERIFY ADEQUACY OF THE STRUCTURE TO SUPPORT THE HANGER AND BRACE LOADS. BEAR ALL COSTS INCURRED FOR ALL REVISIONS, AT NO ADDITIONAL COST TO THE DISTRICT. THE DISTRICT AND ENGINEER MECHANICAL PIPING (MP), MECHANICAL DUCTS (MD), PLUMBING PIPING (PP), ELECTRICAL DISTRIBUTION SYSTEMS (E): SHALL BE NOTIFIED IMMEDIATELY PRIOR TO FABRICATION AND INSTALLATION OF ALL WORK THAT CAUSES CONFLICTS BETWEEN TRADES. 18. PROVIDE ALL MANUFACTURER'S PRODUCT DATA CLEARLY INDICATING MODEL NUMBERS, CAPACITIES, CONSTRUCTION, MP MD PP E OPTION 1: DETAILED ON THE APPROVED DRAWINGS WITH PROJECT SPECIFIC NOTES & DETAILS. ELECTRICAL INFORMATION, AND OPTIONAL ACCESSORIES, PER PROJECT SCHEDULE AND PRIOR TO THE START OF WORK. THESE SHALL BE REVIEWED BY THE MECHANICAL ENGINEER PRIOR TO PURCHASING. 19. SUBMIT TO THE OWNER ALL BROCHURES, OPERATING MANUALS, CATALOGS, SHOP DRAWINGS, "AS-BUILTS", ETC. AT THE COMPLETION OF THE JOB. PROVIDE THE OWNER WITH COMPLETE MECHANICAL "AS-BUILTS" INDICATING FINAL EQUIPMENT | MP MDM PP E OPTION 2: SHALL COMPLY WITH THE APPLICABLE OSHPD PRE-APPROVAL (OPM #) # 0203-13. LOCATIONS, DUCTWORK AND PIPE ROUTING, ETC. 20. OBTAIN APPROVAL FROM THE OWNER ON ALL ADDENDA AND CONSTRUCTION CHANGE DOCUMENT (CCD) PRIOR TO DOING 21. INSTALL ALL EQUIPMENT, ACCESSORIES, AND MATERIAL IN STRICT ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS AND RECOMMENDATIONS. 22. PROVIDE FIRESTOPPING FOR PIPE AND DUCT PENETRATIONS THROUGH RATED WALLS. CONTRACTOR SHALL COORDINATE WITH OTHER TRADES AS NECESSARY PRIOR TO INSTALLATION. 23. ANY MATERIAL EXPOSED WITHIN A PLENUM OR DUCT MUST HAVE A FLAME SPREAD INDEX OF NOT MORE THAN 25, AND A SMOKE DEVELOPED RATING OF NOT MORE THAN 50, AND A MOLD/HUMIDITY RESISTANCE PER U.L. 181. 24. ALL EQUIPMENT, DUCTS, PIPING, AND OTHER DEVICES AND MATERIALS OUTSIDE OF THE BUILDING OR OTHERWISE EXPOSED TO THE WEATHER SHALL BE COMPLETELY WEATHERPROOFED. 25. LOCATE ALL EQUIPMENT SUCH THAT CODE REQUIRED ACCESS IS MAINTAINED, INCLUDING N.E.C. REQUIREMENTS. ACCESS PANELS WHERE REQUIRED, SHALL BE COORDINATED WITH ARCHITECT, AND PROVIDED BY FACTORY OR BE FIELD-PROVIDED. FOR ATTIC EQUIPMENT, G.C. TO PROVIDE A CATWALK & LIGHT PER CMC FOR ATTIC EQUIPMENT. 26. FOR INACCESSIBLE AREAS THE CONTRACTOR SHALL PROVIDE ACCESS PANELS FOR ALL DAMPERS, EQUIPMENT, SMOKE DETECTORS, AND CONTROL DEVICES. THESE PANELS SHALL MATCH THE RATING OF THE WALL AND/OR CEILING WHERE THEY ARE LOCATED IN. MINIMUM ACCESS PANEL SIZES SHALL BE AS FOLLOWS: 1) HAND ACCESS: 12"x12" MIN. 2) BODY ACCESS: 30"x30" MIN. 27. ALL EQUIPMENT WITH MOVING PARTS SHALL BE PROVIDED WITH FLEXIBLE DUCT AND PIPE CONNECTIONS. 28. LABEL ALL EQUIPMENT AS TO THE SPACE IT SERVES. SEE SPECIFICATIONS FOR IDENTIFICATION STANDARDS. LABEL DUCT SMOKE DETECTOR LOCATIONS (AT CEILING) AS TO THE EQUIPMENT IT SERVES. 29. A/C UNITS PROVIDED WITH ECONOMIZER CYCLE DAMPERS SHALL HAVE OSA DAMPERS SET UP TO CLOSE AUTOMATICALLY 30. PROVIDE MANUAL VOLUME DAMPERS AND BACKDRAFT DAMPERS FOR FRESH AIR INTAKES ON ALL AIR HANDLING EQUIPMENT AND EXHAUST FANS SERVING CONDITIONED SPACES. EXCEPTION: EQUIPMENT WITH FACTORY-31. DRAWINGS ARE FOR REFERENCE ONLY. CONTRACTOR TO FIELD VERIFY EXISTING CONDITION PRIOR TO BID DATE. 32. OWNER RETAINS SALVAGE RIGHTS, PROVIDE A MINIMUM OF 72 HOURS NOTICE PRIOR TO REMOVAL OF ROOF TOP UNITS 33. PATCH AND SEAL ALL SLAB, ROOF AND WALL OPENINGS WITH LIKE MATERIAL WHERE MECHANICAL EQUIPMENT ONCE 34. REMOVE EXISTING AND PROVIDE ALL NEW DUCT AND PIPE HANGER SUPPORTS WHERE DUCT AND PIPE IS BEING 35. PROVIDE ALL NEW PIPE SUPPORTS WHERE PIPING IS SCHEDULED TO BE REPLACED. 36. OUTDOOR REFRIGERANT PIPING TO BE INSULATED AND ALUMINUM WRAPPED. 37. CONTRACTOR IS RESPONSIBLE FOR COMPLETE AND OPERABLE SYSTEM. 38. ALL MECHANICAL EQUIPMENTS, PIPES AND DUCTS SHALL BE SUPPORTED AND BRACED PER THE CURRENT CALIFORNIA BUILDING CODE. ALL MECHANICAL COMPONENTS SHALL BE ABLE TO RESIST THE EFFECTS OF SEISMIC FORCES. 39. MECHANICAL WORK SHALL COMPLY WITH ALL FEDERAL, STATE, AND LOCAL CODES AND REGULATIONS. 40. CONTRACTOR SHALL PROTECT EXISTING BUILDING INFRASTRUCTURE DURING CONSTRUCTION FROM OUTDOOR ELEMENT. IF DAMAGED, CONTRACTOR SHALL REPLACE DAMAGED BUILDING COMPONENTS WITH NEW AT NO ADDITIONAL 41. ALL DUCTWORK SHALL BE FABRICATED AND INSTALLED IN ACCORDANCE WITH THE LATEST EDITION OF THE SMACNA LOW PRESSURE DUCT CONSTRUCTION STANDARDS. 42. ALL DUCT JOINTS SHALL BE MADE WITH MASTIC SEALANT, SHEET METAL SCREWS AND TAPED AIR TIGHT WITH HARDCAST 43. WHERE BRACING DETAILS ARE NOT SHOWN ON THE DRAWINGS OR IN THE GUIDELINES, THE FIELD INSTALLATION SHALL BE SUBJECT TO THE APPROVAL OF THE ARCHITECT, MECHANICAL ENGINEER AND DSA FIELD ENGINEER. 44. A COPY OF THE GUIDELINES PUBLISHED BY SMACNA AND APPROVED BY DSA SHALL BE PROVIDED BY THE CONTRACTOR

CAL GREEN NOTES

TESTING AND ADJUSTING. TESTING AND ADJUSTING OF SYSTEMS SHALL BE REQUIRED FOR NEW BUILDING LESS THAN 10,000 SQUARE FEET OR NEW SYSTEMS TO SERVE IN ADDITION OR ALTERATION SUBJECT TO SECTION 303.1

2. SYSTEMS. DEVELOP A WRITTEN PLAN OF PROCEDURES FOR TESTING AND ADJUSTING SYSTEMS. SYSTEMS TO BE INCLUDED FOR TESTING AND ADJUSTING SHALL INCLUDE, AS APPLICABLE TO THE PROJECT:

B. INDOOR AND OUTDOOR LIGHTING AND CONTROLS.

C. WATER HEATING SYSTEMS.

AND KEPT ON THE JOB AT ALL TIMES.

REQUIRED TO AVOID CONFLICT WITH PIPING, LIGHT FIXTURES, TRUSSES, ETC.

E. LANDSCAPE IRRIGATION SYSTEMS F. WATER REUSE SYSTEMS.

PROCEDURES. PERFORM TESTING AND ADJUSTING PROCEDURES IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS AND APPLICABLE STANDARDS ON EACH

A. HVAC BALANCING. IN ADDITION TO TESTING AND ADJUSTING, BEFORE A NEW SPACE-CONDITIONING SYSTEM SERVING A BUILDING OR SPACE IS OPERATED FOR NORMAL USE, BALANCE THE SYSTEM IN ACCORDANCE WITH THE PROCEDURES DEFINED BY THE TESTING ADJUSTING AND BALANCING BUREAU NATIONAL STANDARDS; THE NATIONAL ENVIRONMENTAL BALANCING BUREAU PROCEDURAL STANDARDS; ASSOCIATED AIR BALANCE COUNCIL NATIONAL STANDARDS OR AS

REPORTING. AFTER COMPLETION OF TESTING, ADJUSTING AND BALANCING, PROVIDE A FINAL REPORT OF TESTING SIGNED BY THE INDIVIDUAL RESPONSIBLE FOR

OPERATION AND MAINTENANCE (O & M) MANUAL. PROVIDE THE BUILDING OWNER OR REPRESENTATIVE WITH DETAILED OPERATING AND MAINTENANCE INSTRUCTIONS D COPIES OF GUARANTIES/WARRANTIES FOR EACH SYSTEM. O & M INSTRUCTIONS SHALL BE CONSISTENT WITH OSHA REQUREMENTS IN CCR, TITLE 8, SECTION 5142,

A. INSPECTIONS AND REPORTS. INCLUDE A COPY OF ALL INSPECTION VERIFICATIONS AND REPORTS REQUIRED BY THE ENFORCING AGENCY.

B. HALONS. INSTALL HVAC REFRIGERATION AND FIRE SUPPRESSION EQUIPMENT THAT DO NOT CONTAIN HALONS.

TEMPORARY VENTILATION. THE PERMANENT HVAC SYSTEM SHALL ONLY BE USED DURING CONSTRUCTION IF NECESSARY TO CONDITION THE BUILDING WITHIN THE REQUIRED TEMPERATURE RANGE FOR MATERIAL AND EQUIPMENT INSTALLATION. IF THE HVAC SYSTEM IS USED DURING CONSTRUCTION, USE RETURN AIR FILTERS WITH A MINIMUM REPORTING VALUE (MERV 13) OF 13, BASED ON ASHRAE 52.2-1999 OR AN AVERAGE EFFICIENCY OF 30 PERCENT BASED ON ASHRAE 52.1-1992. REPLACE ALL FILTERS IMMEDIATELY PRIOR TO OCCUPANCY, OR, IF THE BUILDING IS OCCUPIED DURING ALTERATIONS, AT THE CONCLUSION OF CONSTRUCTION.

COVERING OF DUCT OPENINGS AND PROTECTION OF MECHANICAL EQUIPMENT DURING CONSTRUCTION. AT THE TIME OF ROUGH INSTALLATION AND DURING STORAGE ON CONSTRUCTION SITE UNTIL FINAL STARTUP OF THE HEATING, COOLING AND VENTILATION EQUIPMENT, ALL DUCT AND OTHER RELATED AIR DISTRIBUTION COMPONENT OPENINGS SHALL BE COVERED WITH WRAP, PLASTIC, SHEET METAL OR OTHER METHODS ACCEPTABLE TO THE ENFORCING AGENCY TO REDUCE THE AMOUNT OF DUST, WATER AND DEBRIS WHICH MAY ENTER THE SYSTEM.

FILTERS. IN MECHANICALLY VENTILATED BUILDINGS, PROVIDE REGULARLY OCCUPIED AREAS OF THE BUILDING WITH AIR FILTRATION MEDIA FOR OUTSIDE AND RETURN AIR PRIOR TO OCCUPANCY THAT PROVIDE AT LEAST A MINIMUM EFFICIENCY REPORTING VALUE (MERV 13) OF 13. MERV 13 FILTERS SHALL BE INSTALLED PRIOR TO OCCUPANCY AND RECOMMENDATIONS FOR MAINTENANCE WITH FILTERS OF THE SAME VALUE SHALL BE INCLUDED IN THE OPERATION AND MAINTENANCE MANUAL.

A. AN ASHRAE 10-PERCENT TO 15-PERCENT EFFICIENCY FILTER SHALL BE PERMITTED FOR AN HVAC UNIT MEETING THE 2019 CALIFORNIA ENERGY CODE HAVING 60,000 BTU/H OR LESS CAPACITY PER FAN COIL, IF THE ENERGY USE OF THE AIR DELIVERY SYSTEM IS 0.4 W/CFM OR LESS AT DESIGN AIR FLOW. B. EXISTING MECHANICAL EQUIPMENT.

OZONE DEPLETION AND GREENHOUSE GAS REDUCTIONS. INSTALLATIONS OF HVAC, REFRIGERATION AND FIRE SUPPRESSION EQUIPMENT SHALL COMPLY WITH SECTIONS A. CHLOROFLOUROCARBONS (CFCS). INSTALL HVAC, REFRIGERATION AND FIRE SUPPRESSION EQUIPMENT THAT DO NOT CONTAIN CFCS.

10. ADHESIVES, ADHESIVE BONDING PRIMERS, ADHESIVE PRIMERS, SEALANTS, SEALANT PRIMERS AND CAULKS SHALL COMPLY WITH LOCAL OR REGIONAL AIR POLLUTION CONTROL OR AIR QUALITY MANAGEMENT DISTRICT RULES WHERE APPLICABLE, OR SCAQMD RULE 1168 VOC LIMITS, AS SHOWN IN TABLES 5.504.4.1.

SECTION CALLOUT POINT OF CONNECTION POINT OF DISCONNECTION $\sqrt{1}$ HUMIDIFIER **NEW LINEWORK** ////// LOUVER **EXISTING LINEWORK** ACCESS DOOR OR ACCESS PANEL $\mathcal{H}/\mathcal{H}/\mathcal{H}/\mathcal{H}/\mathcal{R}$ DEMOLITION LINEWORK (AP) IN DUCTWORK STATIC PRESSURE CHANGE TAG 16"x12" SHEET METAL DUCT 16"x12" HIDDEN SHEET METAL DUCT STATIC PRESSURE TAG INTERNALLY INSULATED SHEET METAL DUCT 16"x12" TURNING VANES (RECTANGULAR) DIRECTION OF FLOW ___ DRAIN, FUNNEL STANDARD BRANCH FOR SUPPLY AND RETURN CENTRIFUGAL FAN ROUND ELBOW DOWN ANALOG SIGNAL DIGITAL SIGNAL ROUND ELBOW UP ELECTRIC LEAD INSTRUMENT CAPILLARY TUBING RECTANGULAR TO ROUND TRANSITION **ELECTRONIC 3-WAY VALVE** FLEXIBLE DUCT **ELECTRONIC 2-WAY VALVE** FLEX CONNECTION DDC INPUT BACK DRAFT DAMPER DDC OUTPUT LOCALLY MOUNTED INSTRUMENT CARBON DIOXIDE SENSOR COMBINATION FIRE AND SMOKE DAMPER DIFFERENTIAL PRESSURE SENSOR FLOW METER MOTORIZED DAMPER AIRFLOW SENSOR SUPPLY DIFFUSER: 2-WAY/3-WAY/4-WAY RELATIVE HUMIDITY SENSOR GRILLE: RETURN/EXHAUST TEMPERATURE SENSOR 1'x2' RETURN AIR GRILLE AVERAGING TEMPERATURE SENSOR 2'x2' RETURN AIR GRILLE METAL DUCT EMS CO2 SENSOR SUPPLY AIR DUCT SECTION THERMOSTAT RETURN AIR DUCT SECTION PRESSURE SWITCH EXHAUST AIR DUCT SECTION SMOKE DETECTOR POWER OR GRAVITY ROOF VENTILATOR - EXHAUST STATIC PRESSURE SENSOR REFRIGERANT SENSOR POWER OR GRAVITY ROOF VENTILATOR - SUPPLY DEW POINT SENSOR UNDERCUT DOOR SPACE HUMIDITY SENSOR TRANSFER GRILLE OR LOUVER FIRE WALL PENETRATION DOOR GRILLE OR LOUVER MOUNTING OVER OBSTRUCTION DETAIL

MECHANICAL LEGEND

<u>SYMBOL</u>

DESCRIPTION

KEY NOTES

DEMOLITION KEY NOTES

SHEET NO. WHERE SHOWN

EQUIPMENT DESIGNATION

UNIT ABBREVIATION

S GRILLE DESIGNATION

FIRE/SMOKE DAMPER WHERE REQ'D

NECK SIZE & BLOW

NUMBER

DETAIL DESIGNATION

DETAIL NUMBER

DESCRIPTION

DX COOLING COIL

HEATING COIL

DAMPER, OPPOSED BLADE

DAMPER, PARALLEL BLADE

24" MAX ── TOP OF BOX OF SWITCH, DEVICE, OUTLET FA TOP OF BOX OF MICROPHONE SWITCH, DEVICE, OUTLET FA **MICROPHONE** 48" MAX 46" MAX SIDE APPROACH. 44" MAX FRONT APPROACH WITH KNEE AND TOE 34" MAX **CLEARANCE** FINISHED FLOOR — 15" MIN TO BOT. OF BOX 2022 CBC 2022 CBC 2022 CBC FIG. 11B-308.2.1 11B-308.2.2 11B-308.3.2 1. THIS DETAIL APPLIES TO MOUNTING OF ANY MECHANICAL AND ELECTRICAL DEVICE WHICH CONTAINS AN OPERABLE

PART THAT IS ADJUSTABLE BY THE OCCUPANT. THIS DOES NOT APPLY TO SENSORS OR CONTROLS THAT ARE ONLY

ADJUSTABLE THROUGH THE BUILDING AUTOMATION SYSTEM (IE: TEMPERATURE AND HUMIDITY SENSORS).

M2.01 MECHANICAL FLOOR PLANS M3.01 MECHANICAL ENLARGED PLANS M5.01 MECHANICAL SCHEDULES M6.01 MECHANICAL DETAILS B202301766 City of Ontario | Building Department **APPROVED & REVIEWED** FOR CODE COMPLIANCE The issuance of a permit and approval of these plans shall not be construed to permit or approve any violation of the applicable codes or ordinances. Date: 01/16/2024 1:34:38 PM

DRAWING INDEX

MECHANICAL SYMBOLS, LEGENDS & GENERAL NOTES

DESCRIPTION

MECHANICAL TITLE 24

MECHANICAL TITLE 24

MECHANICAL SITE PLAN

SHEET

M0.00

M0.02

M1.01

ALUM

BLDG

BSMT

BTU

CFM

CLG

EWC

FLA

FLR

FOB

GALV

HWP

HWR

HWS

HEAT PUMP

HEIGHT

HERTZ

INCHES

HORSEPOWER

HEATING AND VENTILATING

HOT WATER CONVERTER

HOT WATER PUMP

MOTOR STATUS

INSIDE DIAMETER

INDIRECT WASTE

HEATING HOT WATER RETURN

HEATING HOT WATER SUPPLY

INDUSTRIAL COLD WATER

EXIST / (E

ABBREVIATIONS DESCRIPTION ABBREVIATION DESCRIPTION AUTOMATIC AIR VENT KILOWATTS ABOVE LEAVING AIR TEMPERATURE AIR CONDITIONING UNIT POUNDS ACCESS DOOR LINEAR DIFFUSER ABOVE FINISHED FLOOR LINEAR FEET AIR HANDLING UNIT LEAVING WATER ANALOG INPUT TEMPERATURE ALUMINUM ANALOG OUTPUT MAXIMUM ACCESS PANEL THOUSAND BTU PER HOUR MECHANICAL CONTRACTOR BOILER MINIMUM CIRCUIT AMPS **BACK DRAFT DAMPER** MANHOLE BELOW MINIMUM **BELOW FINISHED CEILING** MAXIMUM OVERLOAD CIRCUIT BACK FLOW PREVENTER PROTECTION BLAST GATE MOTOR OPERATED DAMPER BREAK HORSEPOWER MOUNTED BUILDING MUA MAKE-UP AIR UNIT BOTTOM OF BEAM BOTTOM OF PIPE NEW BASEMENT NORMALLY CLOSED **BRITISH THERMAL UNIT** NOT IN CONTRACT NORMALLY OPEN **CEILING DIFFUSER CUBIC FEET PER MINUTE** OUTSIDE AIR TEMPERATURE CAST IRON OPPOSED BLADE DAMPER CENTER LINE ON CENTER OUTSIDE DIAMETER CLEANOUT OUTSIDE AIR COLUMN CONDENSATE PUMP PARALLEL BLADE DAMPER COOLING TOWER PRESSURE DROP CONDENSING UNIT PERFORATED CONSTANT VOLUME BOX PHASE PRESSURE RELIEF PRESSURE SWITCH POUNDS PER SQUARE INCH DRY BULB DIFFERENTIAL DEGREES POUNDS PER SQUARE INCH DIGITAL INPUT DIAMETER PRESSURE TRANSMITTER DOOR LOUVER PTAC PACKAGED TERMINAL AIR DOWN CONDITIONER **DIGITAL OUTPUT** POLYVINYL CHLORIDE DIFFERENATIAL PRESSURE **DUCT SILENCER** RETURN AIR DIRECT EXPANSION RETURN AIR REGISTER ROOF DRAIN RETURN FAN ENTERING AIR TEMPERATURE RETURN AIR GRILLE ELECTRICAL CONTRACTOR RELATIVE HUMIDITY EXHAUST FAN REHEAT COIL EFFICIENCY RATED LOAD AMPS EGGCRATE GRILLE REVOLUTIONS PER MINUTE **EXPANSION JOINT** ELEVATION SUPPLY AIR EQUAL SUPPLY AIR REGISTER EXHAUST REGISTER STAGED AIR VOLUME EXTERNAL STATIC PRESSURE SMOKE DAMPER EXPANSION TANK SUPPLY FAN ELECTRIC WATER COOLER SPEED INDICATOR **EXISTING** SPEED CONTROL SENSIBLE MBH DEGREES FAHRENHEIT STATIC PRESSURE FREE AREA SPECIFICATION FAN COIL UNIT STAINLESS STEEL FIRE DAMPER STD STANDARD FILTER GRILLE **FULL LOAD AMPS** FLOOR TRANSFER AIR DUCT FLAT ON BOTTOM TEFC TOTALLY ENCLOSED FAN FLAT ON TOP COOLED FIRE PUMP TEMPERATURE FINS PER INCH TRANSFER GRILLE FEET PER MINUTE TEMPERATURE INDICATOR FLOW SWITCH TOTAL MBH FEET / FOOT TOTAL STATIC PRESSURE FLEXIBLE CONNECTION TYP TYPICAL GAUGE UNDERCUT GALVANIZED UNIT HEATER GENERAL CONTRACTOR UNLESS OTHERWISE NOTED UON GALLONS PER HOUR UP THROUGH ROOF UTR GALLONS PER MINUTE DAMPER/VALVE ACTUATOR HEAD VARIABLE AIR VOLUME UNIT HANDS OFF AUTO VOLUME DAMPER


8163 Rochestser Avenue, Suite 100 Rancho Cucamonga California 91730 P 909-987-0909 CONSULTANT LEAF Engineers

> 8163 Rochester Avenue, Suite 100 Rancho Cucamonga, CA 91730 909.987-0909 leafengineers.com

REVIEWED CODE COMPLIANCE Dec 15, 2023


BPR CONSULTING GROUP





KEY PLAN NORTH: PLAN TRUE





	No. C-31162 No. C-31162 OF CALIFORNIA
	CLIENT
ONITABIO	MONTOL AID COLLOCI DICTRIC

ONTARIO - MONTCLAIR SCHOOL DISTRIC PROJECT NUMBER 220316 REVISIONS

VARIABLE FREQUENCY DRIVE

VELOCITY PRESSURE

WITH

WITHOUT

WEIGHT

WET BULB

WATER COLUMN

WATER GAUGE

VENT THROUGH ROOF

|MECHANICAL SYMBOLS **LEGENDS & GENERAL**

CitySubmittal - Rgistration #B202301766

DIAMETER ROTATING AT LOWER SPEED.

CONSTRUCTION DOCUMENTS.

SYSTEMS THAT SERVE MULTIPLE ZONES SHALL HAVE CONTROLS THAT

AUTOMATICALLY RESET SUPPLY AIR TEMPERATURE. ZONES WITH HIGH

INTERNAL LOADS WITH NEAR CONSTANT AIRFLOW SHALL BE DESIGNED FOR

IN RESPONSE TO BUILDING LOADS OR TO OUTDOOR AIT TEMPERATURE AND

DESIGN ROOM AIR TEMPERATURE. CONTROL SEQUENCES ARE IDENTIFIED IN

SAT RESET SHALL BE ESTABLISHED WITH AN AGGRESSIVE RESET SCHEDULE OF

SHALL BE AT LEAST 25% OF THE DIFFERENCE BETWEEN SUPPLY AIR AND

10F, E.G. 55F DURING WARM WEATHER AND 65F DURING COOL WEATHER.

THE ELEVATED RESET SUPPLY AIR TEMPERATURE. RESET CONTROLS SHALL BE

A.	A. GENERAL INFORMATION							
01	Project Location (city)	Ontario	04	Total Conditioned Floor Area	4800			
02	Climate Zone	10	05	Total Unconditioned Floor Area	0			
03	Occupancy Types Within Project:		06	# of Stories (Habitable Above Grade)	2			
• (Office							

B. PROJE	CT SCOPE				
1	Includes mechanical systems or components that ar 0.2(b) or 141.0(b)2 and 180.2(b)2 for alterations.	e within ti	he scope of the permit application and are demonst	rating com	npliance using the prescriptive path outlined in
	01		02		03
	Air System(s)		Wet System Components		Dry System Components
\boxtimes	Heating Air System		Water Economizer		Air Economizer
\boxtimes	Cooling Air System		Pumps		Electric Resistance Heat
	Mechanical Controls		System Piping	\boxtimes	Fan Systems
×	Mechanical Controls (existing to remain, altered or new)		Cooling Towers	⊠	Ductwork (existing to remain, altered or new)
			Chillers	\boxtimes	Ventilation
			Boilers		Zonal Systems/ Terminal Boxes

Registration Number:	Generated Date/Time:	Documentation Software: Energy Code Ace
CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance	Report Version: 2022.0.000 Schema Version: rev 20220101	Compliance ID: 87928-0223-0003 Report Generated: 2023-02-07 16:43:50

state of California Mechanical Systems			CALIFORNIA ENERGY COMMISSION
CERTIFICATE OF COMPLIANCE			NRCC-MCH-E
Project Name:	Transportation Center	Report Page:	(Page 4 of 12)
Project Address:	1442 South Bon View Ontario, CA 91761	Date Prepared:	2023-02-07T19:43:46-05:00

ry System Equipment Efficiency (other than Package Terminal Air Conditioners (PTAC) and Package Terminal Heat Pumps (PTHP), DX-DOAS and Dual Fuel Heat Pumps)									
01	02	03	04	05	06	07	08	09	
			Heating Mode Cooling Mode						
Name or Item Tag	Size Category (Btu/h)	Rating Condition (°F)	Efficiency Unit	Minimum Efficiency Required per Tables 110.2 / Title 20	Design Efficiency	Efficiency Unit	Minimum Efficiency Required per Tables 110.2 / Title 20	Design Efficience	
FC-1	<65,000		HSPF	8.19	9.9	SEER	14	17.6	
FC-2	<65,000		HSPF	8.19	10.3	SEER	14	22.7	

G. PUMPS

Registration Number:

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

This section does not apply to this project.

Generated Date/Time:

Report Version: 2022.0.000

Schema Version: rev 20220101

Documentation Software: Energy Code Ace

Report Generated: 2023-02-07 16:43:50

Compliance ID: 87928-0223-0003

STATE OF CALIFO				
Mechani	cal Systems			CALIFORNIA ENERGY COMMISSION
CERTIFICATE C	OF COMPLIANCE			NRCC-MCH-E
Project Name	:	Transportation Center	Report Page:	(Page 7 of 12)
Project Addre	ss:	1442 South Bon View Ontario, CA 91761	Date Prepared:	2023-02-07T19:43:46-05:00

FC-2	1	< 8,000	706	30	0.04	No Exemptions Apply	Not Required	Sensible Energy Recovery Ratio	0.6	Recovery Bypass provided
n Energy Ind	ex (FEI)									,
01				02				03		
	Name or Item Tag FEI Exception			FEI						
	FC-1			Embedded Fan <5HP or <4.1kW						
	FC-2			Embedded Fan <5HP or <4.1kW						

I. SYSTEM CONTROLS								
This table is used to demo 141.0(b)2E 180.2(b)2 for a	•		atory controls in 110.2 and 1 ems.	20.2 and preso	criptive control	ls in 140.4(f) and (n), 170.2(c	r)4D 170.2(c)4L	or requirements in
01	02	03	04	05	06	07	08	09
System Name	System Zoning	Conditioned Floor Area Being Served (ft ²)	Thermostats 110.2(b) & (c) ¹ , 120.2(a) 160.3(a)2A or 141.0(b)2E & 180.2(b)2	Shut-Off Controls 120.2(e) & 160.3(a)2D	Isolation Zone Controls 120.2(g) & 160.3(a)2F	Demand Response 110.12 120.2(b) & 160.3(a)2B	Supply Air Temp. Reset 140.4(f) & 170.2(c)4D	Window Interlocks per 140.4(n) & 170.2(c)4D
FC-1	Single zone	<= 25,000 ft ²	Setback	NA: Altered per 141.0(b)2E	NA: Single Zone	DR Tstat per 110.12	NA: Single Zone	NA: No operable window
FC-2	Single zone	<= 25,000 ft ²	Setback	NA: Altered per 141.0(b)2E	NA: Single Zone	DR Tstat per 110.12	NA: Single Zone	NA: No operable windows

				141.0(5)21					
¹ FOOTNOTES: Gravity gas wo	all heaters, gro	avity floor heat	ters, gravity room heaters, no	on-central elec	tric heaters, fir	eplaces or decorative gas ap	pliances, wood	d stoves are not required t	:0
have setback thermostats.									

Registration Number:	Generated Date/Time:	Documentation Software: Energy Cod
CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance	Report Version: 2022.0.000	Compliance ID: 87928-0223
	Schema Version: rev 20220101	Report Generated: 2023-02-07 16:

STATE OF CALIFORNIA			
Mechanical Systems			CALIFORNIA ENERGY COMMISSION
CERTIFICATE OF COMPLIANCE			NRCC-MCH-E
Project Name:	Transportation Center	Report Page:	(Page 2 of 12)
Project Address:	1442 South Bon View Ontario, CA 91761	Date Prepared:	2023-02-07T19:43:46-05:00

01 System Summary	r "COMPLIES with 02 Pumps	Ехсерт	03	ns" reje	· · ·	or the t	abie inaicatea	as not	compilant for	auiaar	ICP.			
Summary	Pumps	1			04		05		06	<i>y</i> =	07		08	09
110.1, AN 110.2, 140.4, 170.2(c)	ND 140.4(k), 170.2(c)41	AND	Fans/ Economizers 140.4(c), 140.4(e), 170.2(c)	AND	System Controls 110.2, 120.2, 140.4(f), 170.2(c)	AND	Ventilation 120.1, 160.2	AND	Terminal Box Controls 140.4(d), 170.2(c)4B	AND	Distribution 120.3, 140.4(I), 160.2, 160.3	AND	Cooling Towers 110.2(e)2	Compliance Results
See Table F)	(See Table G		(See Table H)		(See Table I)		(See Table J)		(See Table K)		(See Table L)		(See Table M)	
Yes AN	ND	AND	Yes	AND	Yes	AND	Yes	AND		AND	Yes	AND		COMPLIES with Exceptional Conditions
			Mandatory	Measu	res Complian	ce (See	Table Q for D	etails)				СОМР	LIES	

his table is auto-filled with uneditable comments because of selections made or data entered in tables throughout the form.	
he permit applicant has indicated on Table J that ventilation calculations have been attached or included elsewhere on the plar	is.

HVAC SYSTEM SUMMARY	(DRY & WEI SYSTEMS)				
pace Conditioning System Info	ormation				
01	02	03	04	05	06
System Name	Quantity	System Serving	System Status	Space Type	Utilizing Recovered Hea
FC-1	1	Single zone	Alteration		

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

STATE OF CALIFORNIA		
Mechanical Systems		CALIFORNIA ENERGY COMMISSION
CERTIFICATE OF COMPLIANCE		NRCC-MCH-E
Project Name:	Transportation Center Report Page:	(Page 5 of 12)

1442 South Bon View Ontario, CA 91761 Date Prepared:

Report Version: 2022.0.000

Schema Version: rev 20220101

Compliance ID: 87928-0223-0003

2023-02-07T19:43:46-05:00

STATE OF CALIFORNIA

Mechanical Systems

Report Generated: 2023-02-07 16:43:50

				mpliance with property					c), 140.4(e), 140. H.	.4(m), 170.2(c)3	, and 170.2 ₍	(c)4A for fan	systems. Fo	ın systems ser	ving only
System Name	FC-1	Quantit y	1	Fan System Status	New	System Zoning	all other system s	Serving Dwelling Units	Not Serving Dwelling Units	Fan System Airflow (cfm)	1,130	Site Elevation	934	Economizer	Fixed Temperatu re
01	02	03			04				05	06	07	08	09	10	11
									Allov	vance		Design			
Fan Name or Item Tag	Fan Type	Qty			Compo	onent			Airflow through Component (%)	Water Gauge (w.g)	Compone nt Allowance	Fan Allowance (watt/cfm)	Design Electrical Input Power Method	Motor Nameplate Horsepower	Design Electrical Input Power (kW)
				Hydronic/D	X cooling c	oil or hea	nt pump o	coil	100		0.13		Manufactu		
FC-1	Supply	1										0.139	rer provided		0.33
									Fan System All	owance (kW) ³	0.	42	•	m Electrical ut (kW)	0.33

Registration Number:	Generated Date/Time:	Documentation Software: Energy Code Ace
CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance	Report Version: 2022.0.000 Schema Version: rev 20220101	Compliance ID: 87928-0223-0003 Report Generated: 2023-02-07 16:43:50

STATE OF CALIFORNIA			
Mechanical Systems			CALIFORNIA ENERGY COMMISSION
CERTIFICATE OF COMPLIANCE			NRCC-MCH-E
Project Name:	Transportation Center	Report Page:	(Page 8 of 12)
Project Address:	1442 South Bon View Ontorio, CA 01761	Date Prenared:	2023-02-07T19·43·46-05·00

. VENTILATIO	ON AND INDO	OOR AIR QUALITY										
d:t24refnolink,	/]160.2, 160.3 ₍ ed to be docun	(a)3D, 170.2(a)4N, 170.2	?(a)40 for high	-rise residen	tial occupan	cies. For al	(e)3B 140.4(p) and 140.4(q) for all no terations, only ventilation systems be ates and airflows may be shown on t	eing altered within the	scope of the permit			
01		Check the box if the pro	ject is showing	yentilation	calculations	on the pla	ns, or attaching the calculations inst	ead of completing this t	able.			
02		Check this box if the pro	ject included I	Nonresidenti	ial, Hotel/M	otel Spaces	or Multifamily Common Use Spaces	5				
02												
03		Check the box if the pro	ck the box if the project is using natural ventilation in any nonresidential or hotel/motel spaces to meet required ventilation rates per 120.1(c)2.									
Multifamily D	welling Unit V	entilation Systems										
	Check the box	c if the system is using co	ontinuous vent	ilation to me	et the venti	lation requ	irements per 160.2(b)2Aivb2					
19	20	21	22	23	24	25	26	2	7			
Chasa Nama	Mechanica	al Ventilation Required p	er 120.1(b) & 1	160.2(b)2	Ventilation per Design							
Space Name or Item Tag	Conditioned Floor Area (ft²)	# of Bedrooms	# of Dwelling Units	Required Min OA CFM ¹	Supply Air CFM	Exhaust CFM	Local Exhaust	Air Filtration per 12	20.1(c) & 160.2(b)1			
28		s this a balanced system	4		29		Meeting Outside Air Requiren	nents?				

15 this a balanced system 25 Meeting outside Air nequirements.												
	¹ FOOTNOTES: Uniform Mechanical Code may have more stringent ventilation requirements; the most stringent code requirement takes precedence.											
	² Kitchen range	e hood will be verified per NA7.18.1 to confirm model	is rated by H	IVI or AHAN	1.							
	2											

This section does not apply to this project.

³ Air filtration requirements apply to the following three system types per 120.1(c)1A: space conditioning systems utilizing duc	its to supply air to occupiable space; supply-only ventilation
systems providing outside air to occupiable space; supply side of balanced ventilation systems including heat recovery and ene	ergy recovery ventilation systems providing outside air to
occupiable space.	
	and and a factorization which has been about the same because the same because the same and the same because

⁴ A balanced ventilation system provides ventilation airflow to each dwelling-unit at a rate equal to or greater than the required minimum rate, but not more than twenty percent.

Registration Number:	Generated Date/Time:	Documentation Software: Energy Code Ac
CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance	Report Version: 2022.0.000 Schema Version: rev 20220101	Compliance ID: 87928-0223-000 Report Generated: 2023-02-07 16:43:5

state of california Mechanical Systems			CALIFORNIA ENERGY COMMISSION
CERTIFICATE OF COMPLIANCE			NRCC-MCH-E
Project Name:	Transportation Center	Report Page:	(Page 3 of 12)
Project Address:	1442 South Bon View Ontario, CA 91761	Date Prepared:	2023-02-07T19:43:46-05:00

Space Condition	ing System Information											
01	0	2	03		04		C)5		06		
System Name Quar		ntity	System Serving	Sy	stem Status		Space Type			Utilizing Recovered Heat		
FC-2	2	L	Single zone		Alteration							
Dry System Equi	pment Sizing (includes air co	nditioners, con	densers, heat pumps, VR	F, furnaces and	unit heaters	and DOAS s	ystems)					
01	02		03	04	05	06	07	08	09	10	11	
				Smallest Size	Equipment Sizing per Mechanical Schedule (kBtu/h) 140.4(a&b), 170.2(c)1 & 170.2(c)2 Heating Output ^{2,3} Cooling Output ^{2,3} Load Calculation					ulations		
Name or Item Tag	Liables Liu.Z. 140.4(a)Z and L		pe per Tables 110.2 and Title 20	Available ¹ 140.4(a) and 170.2(c)1	Per Design (kBtu/h)	Rated (kBtu/h)	Supp. Heating Output (kBtu/h)	Sensible Per Design (kBtu/h)	Rated	Total Heating Load (kBtu/h)	Tota Sensib Coolir Load (kBtu/	
FC-1	Unitary Heat Pumps (no elec. resistance)	I Air-cooled split Libna		Yes	40,000	36,000	0	36,000	36,000	8900	26,00	
FC-2	Unitary Heat Pumps (no elec. resistance)	Air-cool	ed, split (1phase)	Yes	27,000	24,000	0	24,000	24,000	3400	14,30	

140.4(a) and 170.2(c)1. Healthcare facilities are excepted. ²It is common practice to show rated output capacity on the equipment schedule. Sensible cooling output comes from specification sheet tables.

³ If equipment is heating only, leave cooling output and load blank. If equipment is cooling only, leave heating output and load blank. ⁴ Authority Having Jurisdiction may ask for load calculations used for compliance per 140.4(b) and 170.2(c).

B202301766 City of Ontario | Building Department
APPROVED & REVIEWED FOR CODE COMPLIANCE The issuance of a permit and approval of these plans shall not be construed to permit or approve any violation of the applicable codes or ordinances.

Date: 01/16/2024 1:34:38 PM

CALIFORNIA ENERGY COMMISSION

Registration Number:	Generated Date/Time:	Documentation Software: Energy Code Ace
CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance	Report Version: 2022.0.000 Schema Version: rev 20220101	Compliance ID: 87928-0223-0003 Report Generated: 2023-02-07 16:43:50

CERTIFICA	ATE OF CON	/IPLIANCE												ı	NRCC-MCH-E
Project Name: Transportation Cent								ortation Center	Report Page: (Page 6 of :					Page 6 of 12)	
Project A	Project Address: 1442 South Bon View Ontario, CA 9170							ntario, CA 91761	1 Date Prepared: 2023-02-07T19:43:46-05:						:43:46-05:00
H. FAN SYSTEMS & AIR ECONOMIZERS															
System Name	FC-2	Quantit y	1	Fan System Status	New	System Zoning	l '	Serving Dwelling Units	Not Serving Dwelling Units	Fan System Airflow (cfm)	706	Site Elevation	934	Economizer	Fixed Temperatu re
01	02	02			0.4	•			ОГ	00	07	00	00	10	11

System Name	FC-2	Quantit y	1	Fan System Status	New	System Zoning	all other system s	Serving Dwelling Units	Not Serving Dwelling Units	Fan System Airflow (cfm)	706	Site Elevation	934	Economizer	Fixed Temperat re
01	02	03		04					05	06	07	08	09	10	11
											Allow	ance	Design		
Fan Name or Item Tag	Fan Type	Qty			Compo	onent			Airflow through Component (%)	Water Gauge (w.g)	ı nı ı	Fan Allowance (watt/cfm) ³	i inniit i	Motor Nameplate Horsepower	Design Electrica Input Power (kW)
				Hydronic/D	cooling c	oil or hea	it pump (coil	100		0.13		Manufactu	1	
FC-2	Supply											0.139	rer provided		0.03
•									Fan System All	owance (kW) ³	0	26		m Electrical ut (kW)	0.03

¹ FOOTNOTES: Fans serving spaces with design background noise goals below NC35	
² Low-turndown single-zone VAV fan system must be capable of and configured to reduce airflow to 50 percent of design airflow and use no more than 30 percent of the design wattage	
at that airflow. No more than 10 percent of the desian load served by the equipment shall have fixed loads.	

I. EXHAUST AI	R HEAT RECOV	ERY 140.4(q), 1	70.2(c)4O							
01	02	03	04	05	06	07	08	09	10	11
Fan System Name	Qty	Hours of Operation per Year	Design Supply Airflow Rate	Outdoor Airflow	% Outdoor Air at Full Design Airflow	I Heat Recovery	140.4(q) & ´	Type Of Heat Recovery Rating	Required Recovery Ratio	Energy Recovery Bypass
FC-1	1	< 8,000	1,130	125	0.1	No Exemptions Apply	Not Required	Sensible Energy Recovery Ratio	I () 6 I	Recovery Bypass provided

Registration N	umber:	Generated Date/Time:	Documentation Software: Energy Code Ace
CA Building Er	ergy Efficiency Standards - 2022 Nonresidential Compliance	Report Version: 2022.0.000 Schema Version: rev 20220101	Compliance ID: 87928-0223-0003 Report Generated: 2023-02-07 16:43:50

STATE OF CALIFORNIA			
Mechanical Systems			CALIFORNIA ENERGY COMMISSION
CERTIFICATE OF COMPLIANCE			NRCC-MCH-E
Project Name:	Transportation Center	Report Page:	(Page 9 of 12)
Project Address:	1442 South Bon View Ontario, CA 91761	Date Prepared:	2023-02-07T19:43:46-05:00

	ed to show complian	ce with mandatory pipe insulation requ	irements foun	d in 120.3 and mandatory requirements found in 120.4(g) for duct sealing.						
01		weather shall be installed with a cover	suitable for o	g that due to sunlight, moisture, equipment maintenance, and wind. Insulation utdoor service. Insulation covering chilled water piping and refrigerant suction Class II vapor retarder. All penetrations and joints of which shall be sealed.						
Duct Leakage T	Testing									
				NR/ Common Use: Duct leakage testing shall not exceed 6% per NA7.5.3 required for these systems?	No					
The answers to	the questions belov	v apply to the following duct systems:	Supply and Return	Dwelling Units: Total duct leakage of duct system shall not exceed 12% or duct system to outside shall not exceed 6% per RA3.1.4 required for systems?						
				Duct leakage testing per CMC Section 603.10.1 required for these systems?	Yes					
11	No	The scope of the project includes only duct systems serving healthcare facilities								
12	Yes	Duct system provides conditioned air t	Duct system provides conditioned air to an occupiable space for a constant volume, single zone, space-conditioning system.							
13	Yes	The space conditioning system serves I	ess than 5,000	Oft ² of conditioned floor area.						
14	No	The combined surface area of the duct	s is more than	n 25% of the total surface area of the entire duct system:						
15	No	The scope of the project includes exter	nding an existi	ng duct system, which is constructed, insulated or sealed with asbestos.						
16	No			stem that is documented to have been previously sealed as confirmed throug s in the Reference Nonresidential Appendix NA2.	n field verificati					
17	Exposed Ductwork located in occupied space	All Ductwork and plenums with pressure class ratings shall be constructed to Seal Class A								
18		All ductwork is an extension of an exist	ing duct syste	m						
19		Ductwork serving individual dwelling u	nit							
20		< 25 ft of new or replacement space co	nditioning du	cts installed						
21	R-8	Dust Insulation R-value								

Registration Number:	Generated Date/Time:	Documentation Software: Energy Code Ace
CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance	Report Version: 2022.0.000 Schema Version: rev 20220101	Compliance ID: 87928-0223-0003 Report Generated: 2023-02-07 16:43:50







8163 Rochester Avenue, Suite 100 Rancho Cucamonga, CA 91730 909.987-0909 leafengineers.com


REVIEWED CODE COMPLIANCE Dec 15, 2023


BPR CONSULTING GROUP

CENTER RANSPORTATION









ONTA		ENT IR SCHOOL DIS
011171	PROJECT NUM 220316	
REVISION	ONS	
No.	Descript	ion [
		l
0:4.4	Submittel Daie	tration #D20220
	Submittai - Kaisi	tration #B20230 [,]

STATE OF CALIFORNIA Mechanical Systems CALIFORNIA ENERGY COMMISSION CERTIFICATE OF COMPLIANCE NRCC-MCH-E Project Name: Transportation Center Report Page: (Page 10 of 12) 1442 South Bon View Ontario, CA 91761 Date Prepared: 2023-02-07T19:43:46-05:00 Project Address:

M. COOLING TOWERS This section does not apply to this project. N. DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION Form/Title NRCI-MCH-01-E - Must be submitted for all buildings

O. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE Systems/Spaces To Be Field Form/Title Verified NRCA-MCH-02-A - Outdoor Air must be submitted for all newly installed HVAC units. Note: MCH-02-A can be performed in conjunction with MCH-07-A Supply Fan VFD Acceptance (if applicable) since testing activities overlap. NRCA-MCH-05-A - Air Economizer Controls FC-1; FC-2

Generated Date/Time:

Report Version: 2022.0.000

Schema Version: rev 20220101

Documentation Software: Energy Code Ace

Compliance ID: 87928-0223-0003

Report Generated: 2023-02-07 16:43:50

P. DECLARATION OF REQUIRED CERTIFICATES OF VERIFICATION

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

There are no NRCV forms required for this project.

Registration Number:

STATE OF CALIFORNIA Mechanical Systems CALIFORNIA ENERGY COMMISSION CERTIFICATE OF COMPLIANCE NRCC-MCH-E Transportation Center Report Page:
1442 South Bon View Ontario, CA 91761 Date Prepared: Project Name: (Page 11 of 12) Project Address: 2023-02-07T19:43:46-05:00

O. MANDATORY MEASURES DOCUMENTATION LOCATION This table is used to indicate where mandatory measures are documented in the plan set or construction documentation. Compliance with Mandatory Measures documented through MCH Plan sheet or construction document location Mandatory Measures Note Block **Mandatory Measure** Plan sheet or construction document location Heating Equipment Efficiency per 110.1 Cooling Equipment Efficiency per 110.1 M5.01 Furnace Standby Loss Control per 110.2(d) N/A Duct Insulation per 120.4 Specifications Heat Pump with Supplemental electric Resistance Heater Controls per 110.2(b) M5.01 The air duct and plenum system is designed per 120.4(a)-(f) M3.01 and Specifications Kitchen range hoods shall be rated for sound in accordance with Section 7.2 of ASHRAE 62.2 N/A

Generated Date/Time: Registration Number: Documentation Software: Energy Code Ace CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance Report Version: 2022.0.000 Compliance ID: 87928-0223-0003 Schema Version: rev 20220101 Report Generated: 2023-02-07 16:43:50

STATE OF CALIFORNIA **Mechanical Systems** CALIFORNIA ENERGY COMMISSION CERTIFICATE OF COMPLIANCE NRCC-MCH-E Project Name: (Page 12 of 12) Transportation Center Report Page: 1442 South Bon View Ontario, CA 91761 Date Prepared: 2023-02-07T19:43:46-05:00

DOCUMENTATION AUTHOR'S DECLARATION STATEMENT I certify that this Certificate of Compliance documentation is accurate and complete. Documentation Author Name: Maher Dandachi signature Date: 02/08/2023 LEAF Engineers CEA/ HERS Certification Identification (if applicable): dddress: 8163 Rochester Ave., Ste 100 ity/State/Zip: Rancho Cucamonga, CA 91730 RESPONSIBLE PERSON'S DECLARATION STATEMENT I certify the following under penalty of perjury, under the laws of the State of California: The information provided on this Certificate of Compliance is true and correct. I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer) The energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the California Code of Regulations. 4. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application. 5. I will ensure that a completed signed copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections. I understand that a completed signed copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy. Responsible Designer Name: Rex Wang LEAF Engineers Address: 8163 Rochester Ave., Ste 100
City/State/Zip: Rancho Cucamonga, CA 91730

Generated Date/Time:

Report Version: 2022.0.000

Schema Version: rev 20220101

Registration Number:

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

B202301766 City of Ontario | Building Department
APPROVED & REVIEWED FOR CODE COMPLIANCE The issuance of a permit and approval of these plans shall not be construed to permit or approve any violation of the applicable codes or ordinances. Date: 01/16/2024 1:34:38 PM

Documentation Software: Energy Code Ace Compliance ID: 87928-0223-0003 Report Generated: 2023-02-07 16:43:50




RANCHO CUCAMONGA 8163 Rochestser Avenue, Suite 100 Rancho Cucamonga California 91730 P 909-987-0909 CONSULTANT LEAF Engineers


8163 Rochester Avenue, Suite 100


Rancho Cucamonga, ĆA 91730 909.987-0909 leafengineers.com


REVIEWED CODE COMPLIANCE Dec 15, 2023 BPR CONSULTING GROUP

CENTER









CitySubmittal - Rgistration #B202301766 MECHANICAL TITLE 24

M0.02


1 AREA OF SCOPE OF WORK.

KEY NOTES

B202301766 City of Ontario | Building Department
APPROVED & REVIEWED
FOR CODE COMPLIANCE The issuance of a permit and approval of these plans shall not be construed to permit or approve any violation of the applicable codes or ordinances.

Date: 01/16/2024 1:34:38 PM

8163 Rochester Avenue, Suite 100 Rancho Cucamonga, CA 91730 909.987-0909 leafengineers.com **REVIEWED** CODE COMPLIANCE Dec 15, 2023 BPR CONSULTING GROUP TRANSPORTATION CENTER




RANCHO CUCAMONGA 8163 Rochestser Avenue, Suite 100


Rancho Cucamonga California 91730 P 909-987-0909


CONSULTANT





	CLI	ENT	
ONTA	ARIO - MONTCLA		DISTRICT
	NUMBER 316		
REVIS	IONS		
No.	Descript	ion	Date
City	Submittal - Rgis	tration #B20	2301766
ME	CHANICA	L SITE	PLAN






RANCHO CUCAMONGA 8163 Rochestser Avenue, Suite 100 Rancho Cucamonga California 91730 P 909-987-0909 CONSULTANT LEAF Engineers LEAF


8163 Rochester Avenue, Suite 100 Rancho Cucamonga, CA 91730 909.987-0909 leafengineers.com

REVIEWED CODE COMPLIANCE Dec 15, 2023

BPR CONSULTING GROUP







ONT		LIENT	DIOTE
ONT	ARIO - MONTCL		
	T NUMBE		
	3/3/23		0316
	SIONS		
No.	Descrip	otion	Da
City	ySubmittal - Rgi	stration #B2	023017
City	ySubmittal - Rgi MECH		

	SPLIT SYSTEM INDOOR FAN COIL UNIT SCHEDULE												
			CAPACI	ITY (MBH)	OSA TEMP. (°F)	5AT (05)		SUPPLY FAN		ELECTRICAL			
UNIT	MANUFACTURER AND MODEL NO.	SERVICE/ LOCATION	TYPE	TOTAL	HEATING	SUMMER WINTER	EAT (°F)	LAT (°F)	CFM	E.S.P.	VOLTAGE UNIT UNIT MOCP	OPER. WT. (LBS.)	REMARKS
71110				COOLING	TILATING	(DB/WB) (DB)	(DB/WB)		(H/M/L)	(IN.)	FLA MCA MOCP	, ,	
FC	CARRIER/TOSHIBA RAV-SM362BTP-UL	STORAGE ROOM 100	SUSPENDED DUCTED	36.0	40.0	101.0/69.0 33.0	77.8/66.2	56.6	1,130 920	0.6	SEE OUTDOOR HP UNIT	95.0	
			500125						790				

NOTES:

1. PROVIDE WITH CONDENSATE DRAIN PAN (PRIMARY AND SECONDARY) FOR FAN COIL UNIT AND ASSOCIATED PIPING.
2. PROVIDE WITH FACTORY FURNISHED & INSTALLED CONDENSATE DRAIN LIFT PUMP (CONDENSATE PUMP SHALL BE POWERED THRU INDOOR FAN COIL UNIT).

 SIZE REFRIGERANT LINES PER MANUFACTURERS RECOMMENDATIONS.
 PROVIDE T-24 COMPLIANT PROGRAMMABLE THERMOSTAT AND CONNECT TO EXISTING EMS. 5. SUSPENDED/DUCTGED FAN COIL UNIT.

6. PROVIDE DISCONNECT SWITCH.
7. PROVIDE WITH HIGH STATIC MOTOR.

8. PROVIDE WITH MERV 13 FILTER.

9. INDOOR UNIT SHALL BE POWERED BY OUTDOOR UNIT.

	SPLIT SYSTEM OUTDOOR UNIT SCHEDULE															
			COOLING CAP. (MBH)			AMB. TEMP.(°F)			ELECTRICAL							
UNIT	MANUFACTURER AND MODEL NO.		COOLING (TOTAL/SENSIBLE)	HEATING	COP/ HSPF	SUMMER (DB/WB)	WINTER (DB)		COMPF QTY.	RESSOR RLA	OUTDOOR FAN QTY./FLA	MCA	MOCP	VOLTAGE	OPER WT. (LBS)	REMARKS
HP 1	CARRIER/TOSHIBA RAV-SP362AT2P-UL	MOUNTED ON GRADE	36.0	40.0	3.5/ 9.9	101.0/69.0	33.0	11.0 17.6	1	-	1/-	30.0	40	208V / 1Ø / 60HZ	220.0	

NOTES:
1. PROVIDE CRANKCASE HEATER, HIGH & LOW PRESSURE SWITCHES.
2. PROVIDE LOW AMBIENT KIT.

PROVIDE LOW AMBIENT KTT.
 PROVIDE 3/4" EXPAND METAL CONDENSING COIL GUARD.
 PROVIDE MINIMUM CLEARANCE AROUND EACH UNIT PER THE MANUFACTURER'S RECOMMENDATIONS.
 SIZE REFRIGERANT (R410A) LINES PER MANUFACTURERS RECOMMENDATIONS. PROVIDE LONG LINE KIT IF REQUIRED.

PROVIDE HAIL-GUARD. 7. PROVIDE WITH 6" CONCRETE HOUSEKEEING PAD.

	SPLIT SYSTEM INDOOR FAN COIL UNIT (COOLING ONLY) SCHEDULE												
	UNIT MANUFACTURER SERVICE/ AND MODEL NO. LOCATION		00011110	004 TEMP (0E)	EAT (9E)		SUPPI	LY FAN	ELECTI	RICAL			
UNIT		COOLING CAPACITY (MBH)	OSA TEMP. (°F) (DB/WB)	EAT (°F)	LAT (°F)	CFM	E.S.P.	VOLTAGE	UNIT	MOOD	OPER. WT. (LBS.)	REMARKS	
					(DB/WB)		(H, M, L)	(IN.)	VOLTAGE	MCA	MOCP		
FC	CARRIER/TOSHIBA	DATA ROOM 200	24.0	101.0/69.0	80.0/67.0	57.4	706 530	0.25	SEE OUTDOOR CU UNIT		35.0		
2	RAV-SM242KRTP-UL	<i>5</i> /1//1100M 200	24.0	101.0/09.0	00.0/07.0	07.4	353	0.20		OK 00 OKT		00.0	

NOTES:

1. PROVIDE WITH CONDENSATE DRAIN PAN (PRIMARY AND SECONDARY) FOR FAN COIL UNIT AND ASSOCIATED PIPING.

2. PROVIDE WITH FACTORY FURNISHED & INSTALLED CONDENSATE DRAIN LIFT PUMP (CONDENSATE PUMP SHALL BE POWERED THRU INDOOR FAN COIL UNIT).

3. SIZE REFRIGERANT LINES PER MANUFACTURERS RECOMMENDATIONS.

4. CONNECT TO EXISTING EMS FOR CONTROLS. 5. WALL MOUNTED FAN COIL UNIT.

6. PROVIDE WITH HIGH STATIC MOTOR.

7. PROVIDE WITH TITLE 24 COMPLIANT THERMOSTAT. 8. INDOOR UNIT SHALL BE POWERED BY OUTDOOR UNIT.

	SPLIT SYSTEM OUTDOOR CONDENSING UNIT (COOLING ONLY) SCHEDULE																
UNIT	MANUFACTURER AND MODEL NO.	COOLING CAPACITY (MBH)	AMB. TEMP.(°F) (DB/WB)	E.E.R. S.E.E.R.	COMPRESSOR OUTDOOR FAN		OUTDOOR		OR OUTDOOR		MPRESSOR OUTDOOR		CAL MCA			OPER WT. (LBS)	REMARKS
					QTY.	RLA	QTY.	FLA	iiio/ (702///(02						
CU 2	CARRIER/TOSHIBA RAV-SP242AT2P-UL	24.0	101.0/69.0	11.8 22.7	1	-	1	-	17.0	25	208V / 1Ø / 60HZ	145.0					

NOTES:
1. PROVIDE CRANKCASE HEATER, HIGH & LOW PRESSURE SWITCHES.

PROVIDE LOW AMBIENT KIT.
 PROVIDE 3/4" EXPAND METAL CONDENSING COIL GUARD.
 PROVIDE MINIMUM CLEARANCE AROUND EACH UNIT PER THE MANUFACTURER'S RECOMMENDATIONS.
 SIZE REFRIGERANT (R410A) LINES PER MANUFACTURERS RECOMMENDATIONS. PROVIDE LONG LINE KIT IF REQUIRED.

6. PROVIDE HAIL-GUARD.


7. PROVIDE WITH 6" CONCRETE HOUSEKEEPING PAD.
8. CONDENSING UNIT IS A FLOOR MOUNTED. 9. BLANK-OFF HEATING SECTION.

	AIR DISTRIBUTION SCHEDULE										
SYMBOL	TYPE	MAKE & MODEL	DESCRIPTION								
(A)	CEILING SUPPLY	TITUS MODEL MCD	MODULAR CORE DIFFUSER WITH FRAME FOR LAY-IN T-BAR CEILING, FLUSH FACE MOUNTING.								
₿	CEILING RETURN	TITUS MODEL PAR	PERFORATED FACE DIFFUSER WITH FRAME FOR LAY-IN T-BAR CEILING, FLUSH FACE MOUNTING.								
©	CEILING SUPPLY	TITUS MODEL MCD	MODULAR CORE DIFFUSER WITH RAPID MOUNT FRAME MODEL TRM FOR SURFACE MOUNTING.								
(D)	CEILING RETURN/EXHASUT	TITUS MODEL 50F	EGG CRATE GRILLE REGISTER WITH RAPID MOUNT FRAME TRM FOR SURFACE MOUNTING.								
€	SIDEWALL SUPPLY	TITUS MODEL 1700	DOUBLE DEFLECTION HORIZONTAL 5° DOWN FRONT GRILLE WITH 1/2" BLADE SPACING, FRAME FOR WALL MOUNTING.								
F	CEILING SUPPLY	TITUS MODEL ML-38-2B	ALUMINUM LINEAR SLOT DIFFUSER, 3/4" SLOT,4-SLOT, PATTERN CONTROLLER, FLANGED BORDER FOR SURFACE MOUNTING, OPTIONAL PLENUM IN 2,3,4 OR 5 FOOT SECTIONS PER PLANS, COLOR PER ARCHITECT.								

REFER TO THE FLOOR PLANS FOR NECK SIZE, CFM, AIR DIFFUSION PATTERN AND FIRE/DAMPER, IF REQUIRED.
 PROVIDE AIR CONTROL GRID FOR ALL CEILING SUPPLY DIFFUSERS SET AT 90°.












8163 Rochester Avenue, Suite 100 Rancho Cucamonga, CA 91730 909.987-0909 leafengineers.com

REVIEWED CODE COMPLIANCE

Dec 15, 2023 BPR CONSULTING GROUP







	CLIE	ENT								
ONTARIO - MONTCLAIR SCHOOL DISTRICT										
DATE PROJECT NUMBER										
	3/3/23 220									
REVI	REVISIONS									
No.	No. Description									
Cit	ySubmittal - Rgist	tration #B20	2301766							
	MECHANICAL									
SCHEDULES										
	• • • • • • • • • • • • • • • • • • •									

