

TWO-POST GENERAL PURPOSE LIFTS

10K



EELR731A

Shown with optional
accessory 3" stack extension



10K



LIFTING HEAVY LOADS ARE MADE EASIER WITH THE HOFMANN® 10K TWO-POST LIFT

Hofmann 10k 2-Post Combo automotive/general purpose lifts are packed with premium features: industrial-strength columns, low-friction lift carriage slides, low-wear components with plated arm pins, steel pulleys and more. Vehicles can be positioned and lifted symmetrically or asymmetrically.

THREE STAGE ARMS FRONT ARMS

- Provides versatile vehicle positioning for symmetric/asymmetric lifting

VERSATILE POWER COLUMN PLACEMENT

- Power column can be arranged on either the driver or passenger side at the time of installation

SINGLE POINT LOCK RELEASE

- Single point, mechanical lock release allow the technician to disengage both columns simultaneously

SCREW PADS

- Double telescoping lifting pads minimize the need for truck adapters by meeting a wider range of OEM recommended pick up points

OVERHEAD SHUT OFF

- The padded overhead shut off system prevents vehicle damage from being raised too high

ADJUSTABLE COLUMN HEIGHT

- Adjustable column height accommodates higher profile vehicles and provides maximum headroom to work underneath vehicles

ANSI/ALI ALCTV:2011

- Independently Tested and Validated, ALI Certified to the current Automotive lift standard

AVAILABLE MODELS

12K Two-Post	EELR731A
--------------	----------

TECHNICAL SPECIFICATIONS

Capacity	10,000 lbs (4,536 kg)
Rise height*	77.75" (200 cm)
Overall height - adjustable	147.5"/137.5" (375-350 cm)
Overall width	131.75" (335 cm)
Drive thru width	98.375" (250 cm)
Floor to overhead shut off	140.5"/130.5" (357/331 cm)
Three stage front arm reach	21.75" to 39.25" (55-100 cm)
Rear arm reach	38.25" to 55.375" (97-141 cm)
Lowered pad height	4.25" to 6.75" (11-17 cm)
Width between columns	110.25" (280 cm)
Rise time	52 Seconds
Power requirements	208-230V 1Ph 60Hz
Max load per arm	2,500 lbs (1,134 kg)

OPTIONAL ACCESSORIES

Extension Adapter Kit Includes: Four 3" stack extensions, two 6" stack extension and two organizer brackets with mounting hardware	EAK0299T22A
Two 6" stack adapter extensions	EAK0299T23A
Air/Electric workstation with filter/lubrication/regulator	EAK0299T27A
Four u-shaped frame truck adapters	EAK0299T25A***
Two u-shaped frame truck adapters	EAK0299T24A***
24" blue height extension	EAK0299T26A
Adapter kit (includes EAK0299T22A and EAK0299T25A)	EAK0299T29A

*Rise height is measured with screw pad adjusted to maximum height

**Optional three phase electrical also available, specify at time of order

***Frame engaging adapters EAK099T24A or EAK0200T25A are required when lifting vehicles with frame construction

For more information regarding the 10K Two-Post Lift, call 800.251.4500 (US) or 501.505.2662 (Canada) www.hofmann-usa.com / www.hofmann.ca

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet piece may change without notice. ©2016 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. 05/16 SS143385A

