



PRODUCT CATALOGUE

EMPOWERING INTELLIGENT CONTROL SYSTEMS

FR CONTROLS



Company Profile

At FR CONTROLS, we empower businesses to achieve operational excellence by simplifying complex automation challenges. Our intelligent control systems and programmable solutions are designed to unlock new efficiencies, enhance reliability, and streamline performance across industrial and building environments.

We combine proven engineering with forward-thinking innovation—investing in R&D to develop advanced, flexible controllers that adapt to your needs. Our scalable product range, from compact PLCs to high-capacity control hubs, ensures seamless integration and future-ready automation.

Backed by dedicated support and a growing global reach, FR CONTROLS is your trusted partner in smart automation. With us, you gain not just powerful tools—but a commitment to helping your next project run smoother, smarter, and stronger.

Vision

To become the leading provider of intelligent automation and control solutions, enabling smarter, more efficient, and sustainable environments across industries worldwide.

Mission

At FR Controls, our mission is to deliver high-quality, reliable, and customizable control systems that empower businesses to optimize performance, reduce operational costs, and achieve seamless integration in building and industrial automation.

We are committed to:

- Innovating user-friendly, scalable automation solutions
- Supporting clients with expert technical guidance and responsive service
- Building long-term partnerships through trust, quality, and performance

Product and Services

- Building Management System (BMS)
- Energy Monitoring and Control Systems
- System Integration and Automation Solutions
- Remote Monitoring and IOT Solutions
- Technical Support and Troubleshooting
- Training and Consultation
- Programmable Logic Controller and Sensors

Industry Applications



**Building
Automations**



Industrial 4.0



Construction



**Smart
Home/Cities**

Certification



BORANG D (KAEDAH 13)



PERAKUAN PENDAFTARAN AKTA PENDAFTARAN PERNIAGAAN 1956

Dengan ini diperakui bahawa perniagaan yang dijalankan dengan nama

FR CONTROLS ENTERPRISE
NO. PENDAFTARAN: 202403043053 (003576894-H)

telah didaftarkan dari hari ini sehingga **13 FEBRUARI 2026** di bawah Akta Pendaftaran Perniagaan 1956, beralamat di **62 PERSIARAN SEKSYEN 2/5 BANDAR PUTRA BERTAM, 13200 KEPALA BATAS, PULAU PINANG**

Bil. Cawangan: TIADA

Bertarikh di **SISTEM EZBIZ** pada **3 JULAI 2025**.



DATUK NOR AZIMAH ABDUL AZIZ
Pendaftar Perniagaan
Semenanjung Malaysia

Contents

T3 Series Bacnet Programmable Controller	2-1
• Specifications	2-2 - 2-3
• T3-BB	2-4
• T3-TB	2-5
Sensors	
• Humidity and Temperature Sensor With Waterproof Connector	3-1 - 3-5
Thermostats	
• Tstat1OE	4-1 - 4-4

When reliability, quick setup, and minimal maintenance matter most, you need a partner you can count on. Our solutions are designed for durability and performance, ready to meet tough demands and deliver consistent results—day in and day out.

Your single point of contact, inquiries, customer services, sales office information and product inquiries

012-936 0735 | 017-461 7923
frcontrolsenterprise@gmail.com

T3 Series

Bacnet Programmable Controller



T3000 controller is a multi-user, T3-BB and T3-TB. It can stand DDC panel alone or in a multiple network system with full communication capabilities. The multiple communication ports allow the controller to operate on a network or host sub networks and to communicate with local and remote operators simultaneously.

Setup and programming are done on a PC not necessary to connect to live hardware as it is the case with many systems. When the program is ready for on-site testing, connect it to a live panel and download the T3000 software. Programming can be done remotely over the network and modem connections as well. The network system is very flexible and economical for the installation.



T3-BB



T3-TB



T3 Series Bacnet Programmable Controller Specifications

Industry Standard	Bacnet & Modbus Protocols
Control Basic Programs	16
User screen displays	16
User variables	128
Schedule & Holidays	8 Weekly Routines, 4 Annual Routines
PID Controllers	16
Passwords and Users	8
RS485 Sub Baudrates	9600 Thru to 115k
RS485 Main Baudrates	1200 - 921600
Main CPU Capacity	512K Flash/ 512k Ram
Highly Configurable	Any Combination of Input/Output Cards Totaling Up to 64 Points
Digital Output	5A/30VAC, 1A/30VDC
Analog Output	0-10V
Universal Input	Thermistor, 0-10V, 0-5V, 0-20mA
Mechanical Relays	2A, 24VAC/DC
Diagnostic LEDS	Hands Off Auto Switches
SD Disk Slots	Trend Logs, Alarms, Graphics
Ethernet Ports	Bacnet & Modbus Supported Simultaneously
RS485 Ports	2
USB Ports	T3-BB, T3-LB
RS232 Ports	T3-BB
Hardware Options	Several Optional Modules are Available to Support Zigbee, Wifi, 1k Pt Sensor Inputs
Wifi Security	WEP/WPA-PSK/WPA2-PSK
Operating Temperature	-30 to 70 Celsius (-22 to 158 Fahrenheit)
Maximum Power Consumptions	T3-BB : 10W , T3-TB : 6W
Case Color	Black


T3 Series Bacnet Programmable Controller Specifications

- * Surge-protected Universal Inputs with 12-bit resolution
- * UL listed ABS enclosure with rubberized texture creates a high end feel.
- * Software configure the I/O ranges with the free T3000 software or by writing to the registers with your own software.
- * Each output has a hand-off-auto switch for easy troubleshooting and overrides.
- * Each I/O as well as the RS485 connections have a separate screw terminal, there's no need to gang two wires under one terminal for any of the terminations.
- * High/Low speed input pulse counters
- * Communication methods are RS485, Ethernet, USB, Zigbee but it can, at the same time, support Modbus and Bacnet.




T3-BB Controller

Specifications




Specifications	T3-BB
Total Channels	56
Universal Input	32
Analog Output	12
Relay Output	12
Comm Port	
RS485	2
RS232	1
Ethernet	1
USB	1
Option Port	1




T3-TB Controller

Specifications



Specifications	T3-TB
Total Channels	22
Universal Input	8
Analog Output	6
Relay Output	6
Comm Port	
RS485	2
RS232	0
Ethernet	1
USB	0
Option Port	0



Sensors

Humidity and Temperature Transmitter with Waterproof Connector



Humidity & Temperature transmitters are designed for environment monitoring and controlling in industrial, commercial and other buildings. These transmitters can be used for indoor air temperature and humidity monitoring in various industrial plant, clean room, lab, machine room, office and commercial building, airport, station, library and stadium. The modbus interface is documented and integrator friendly. They also have transducer outputs for connecting as analog inputs to all popular control systems. Various models are available:Duct Mount,Wall Mount,Room Mount and 2 meter cable.

BACnet MS/TP and Modbus RTU protocols



HUM-D1



HUM-W1



HUM-C1



Humidity and Temperature Transmitter with Waterproof Connector Specifications

Power	15V to 24V AC or DC, +/-10%
Current Output Load	< 500Ω
Display	LCD Screen for Wall Outdoor/ Room Mount and Duct Mount
Display Resolution	0-1 Celcius, 0.1%RH
Temperature Limit	-30 to 70 Celcius, 0-95% RH (Non Condensing)
Plastic Housing	Flammability Rating UL94HB
Connector	UL File E365137, Vol 1
Protection	IP65, Outdoor Rated for Duct and Wall Mount Models; IP30 for Room Mount
Filter	Sintered Stainless Steel, 60µm

	Relative Humidity	Temperature
Sensors	Capacitance Polymer	10k internal
Range	0 to 100% Non Condensing	-30 to 70 Celcius (-22 to 158 Farenheit)
Output	4-20mA, 0-5V or 0 to 10V, RS 485	4-20mA, 0-5V or 0 to 10V, RS 485
Accuracy	+/-2% @ (0-90%)	+/-0.2Celcius @ 5-6 Celcius
Hysteresis	< +/-1% RH	
Response Time	<10s	
Drift	<0.5% RH/year	

Humidity and Temperature Transmitter with Waterproof Connector Specifications

- High performance digital sensors and circuits, ensure accurate measurement and temperature compensation
- Good long term stability and reliability
- 100% field changeable sensors, no recalibration needed
- Fast response
- Multiple output signals selectable: 4-20mA, 0-5V or 0-10V
- Display in degrees Fahrenheit or Celsius (connection to Modbus)
- HUM-C is same as HUM-W but with extended cable to connect the sensor
- Featured as pluggable sensor pipe
- Dew point and enthalpy can be configured by register list
- BACnet MS/TP and Modbus RTU protocols over RS485, with an ethernet port.



Sensors

Humidity and Temperature Transmitter with Waterproof Connector



Humidity & Temperature transmitters are designed for environment monitoring and controlling in industrial, commercial and other buildings. These transmitters can be used for indoor air temperature and humidity monitoring in various industrial plant, clean room, lab, machine room, office and commercial building, airport, station, library and stadium. The modbus interface is documented and integrator friendly. They also have transducer outputs for connecting as analog inputs to all popular control systems. Various models are available:Duct Mount,Wall Mount,Room Mount and 2 meter cable.

BACnet MS/TP and Modbus RTU protocols




HUM-N-LCD



Humidity and Temperature Transmitter with Waterproof Connector Specifications

Power	15V to 24V AC or DC, +/-10%
Display	LCD Screen for Wall mount indoor
Display Resolution	0-1 Celcius, 0.1%RH
Temperature Limit	-30 to 60 Celcius, 0-95% RH (Non Condensing)
Plastic Housing	Flammability Rating UL94HB
Connector	RS485 1 Port
Protection	Flammability rating UL94V0 file E194560

	Relative Humidity	Temperature
Sensors	Capacitance Polymer	10k internal
Range	0 to 100% Non Condensing	-30 to 70 Celcius (-22 to 158 Farenheit)
Output	4-20mA, 0 to 5V or 0 to 10V, RS 485	4-20mA, 0 to 5V or 0 to 10V, RS 485
Accuracy	+/-2% @ (0-90%)	+/-0.2Celcius @ 5-60 Celcius



Thermostat

Tstat10E



Tstat10 Bacnet programmable controller is a low cost high performance programmable controller. With an I/O configuration, it can be extended through external I/O modules to form a complete building automation solution. There are five relays and two analog outputs as well as 8 universal inputs. These i/o can be configured using the free software. There are more than 300 settings with many options for each of the settings so its possible to configure these devices for most any application. Once the unit is configured, save the config file for copying to other controllers and backing up project settings. Options are available for occupancy sensor, zigbee, and humidity / enthalpy. Supports Bacnet MSTP and Modbus RTU for the RS485 model.

Wifi version supports Bacnet IP and Modbus IP



Tstat10E



Tstat10E

Specifications



- Software configure the I/O ranges with the free T3000 software or by writing to the registers with your own software
- Universal I/O can be configured for nearly any sensor, no jumper settings required
- Well documented register list for easy integration with other systems.
- 8 universal inputs for external temperature sensors, contacts, etc.
- 5 relay outputs, each rated at 12~24vac, 2 amps
- 2 analog outputs, 0-10V @ 100ma.
- Color LCD display with scroll bar.
- Each I/O as well as the RS485 connections have a separate screw terminal
- Clock with infinite life supercap battery backup.
- Supports Modbus RTU and Bacnet protocols simultaneously.



Tstat10E


Specifications

Outputs	5 Relay Outputs, 2 Analog Outputs 10V@100mA
8 Universal Inputs	10k Therm, contacts, 4-20mA, 0-5V, 0-10V
Operating Range	-30 Celcius to 70 Celcius / 0 to 99% Relative Humidity
Supply Voltage	12 to 24 VAC/VDC +- 20%, 50-60Hz
Power Consumptions	100mA at 12VDC
Relay Contacts	5 relays, 2A @ 24VAC UL File : E169380
Plastic Housing	Flammability rating UL94 file E56070
Enclosure Rating	IP31
Protocols	Bacnet MSTP and Modbus RTU
Baudrate	9600, 19200, 38400, 57600, 115200
Temperature Sensors	10K Thermistor +-0.5 Celcius
Setup Software	Free, No Licensing, Open Source



Tstat10E

Specifications





FR CONTROLS

202403043053

62 Persiaran Seksyen 2/5
Bandar Putra Bertam
13200 Kepala Batas
Pulau Pinang

Contact Details

012-936 0735 | 017-461 7923

frcontrolsentreprise@gmail.com

All product designations used in this catalog may be trademarks or registered trademarks of their respective owners. Unauthorized use by third parties for their own purposes may violate the rights of the trademark owners.

Specifications and product details are subject to change without prior notice.

Printed in Malaysia.

©2024 FR Controls Enterprise