

DA-40 ST

Specification

| Thermal efficiency | |
|--|--|
| Uw*: Coefficient value for reference design | 1,7 W/m²K |
| U factor*: | --- |
| *: | --- |
| Profile | |
| Profile name: | DA-40 |
| Installation depth: | Sash: 40 mm Frame: 65 mm |
| Number of chambers: | 3 |
| Thermal break: | Thermal breaks 22 mm made of fiber glass reinforced by polyamide |
| Number of seals: | Two brush seals |
| Glass | |
| Glazing package: | 4/16/4 |
| Ug value: | 1,0 W/m²K |
| Glazing Package Thickness: | from 24 to 32 mm |
| Sound insulation of available glazing: | --- |
| Fittings | |
| Type: | A sliding window roll |
| Hinges: | do not apply |
| Anti-theft protection: | do not apply |
| Microventilation: | do not apply |
| Other: | do not apply |
| Handle | |
| Colors: | --- |
| Handle model: | Grip made of aluminium |
| Sash size | |

| | |
|-------------------|---------|
| Min. sash width: | 500 mm |
| Max. sash width: | 2000 mm |
| Min. sash height: | 360 mm |
| Max. sash height: | 2550 mm |
| Max. sash weight: | 160 kg |
| Max. sash area: | --- |