

# DA-77



## Specification

| Thermal efficiency  |   |
|---|---|
| U <sub>w</sub> *:<br>Coefficient value for reference design | 1,0 W/m <sup>2</sup> K  |
| U factor*:  | 0,18 Btu/h·ft <sup>2</sup> ·F   |
| *:  | Glass 4/18/4/18/4 window size 48 7/16 in x 58 4/16 in (1230 mm x 1480 mm) |
| Profile   |   |
| Profile name:   | DA-77   |
| Installation depth:   | Frame 77 mm   Sash 86 mm  |
| Number of chambers:   | 4   |
| Thermal break:  | yes: 43 mm  |
| Number of seals:  | 2   |
| Glass   |   |
| Glazing package:  | 4/18/4/18/4 warm spacer bar   |
| U <sub>g</sub> value:                                       | 0,5 W/m <sup>2</sup> K  |
| Glazing Package Thickness:                                  | from 21 to 67 mm  |
| Sound insulation of available glazing:                      | ---   |
| Fittings  |   |

|   |  |
|---|--|
| Type:   | Winkhaus circumferential   |
| Hinges:   | surface  |
| Anti-theft protection:  | anti-theft catches   |
| Microventilation:   | yes  |
| Other:  | Four-stage tilt and slide mechanism   Handle rotation lock with a lifter |
| <b>Handle</b>   |  |
| Colors:   | ---  |
| Handle model:   | 1006   |
| <b>Dimensions</b>   |  |
| Maximum window width - single sash:   | 1700 mm  |
| Maximum window height - single sash:  | 2800 mm  |
| Maximum window width - double sash with a movable post:   | 3400 mm  |
| Maximum window height - double sash with a movable post:  | 2800 mm  |
| Maximum sash area:  | 3 m <sup>2</sup>   |
| Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg): | 3500 x 2900 mm lub 2900 x 3500 mm  |

## Photos

