

DA-FerroLine



Specification

Thermal efficiency	
Uw*: Coefficient value for reference design	1,0 W/m ² K
U factor*:	0,18 Btu/h·ft ² ·F
*:	---
Profile	
Profile name:	DA-FerroLine
Installation depth:	Frame : 77-110 mm Sash: 86-93,5 mm
Number of chambers:	4
Thermal break:	Thermal break: 43 mm i 42 mm
Number of seals:	3
Glass	
Glazing package:	4x18x4x18x4 black warm spacer
Ug value:	0,5 W/m ² K
Glazing Package Thickness:	48 mm
Sound insulation of available glazing:	---
Fittings	
Type:	ROTO perimeter fittings

Hinges:	Visible hinge fitting , concealed hinge fitting optional
Anti-theft protection:	none
Microventilation:	none
Other:	-
Handle	
Colors:	---
Handle model:	1006
Dimensions	
Maximum window width - single sash:	1600 mm
Maximum window height - single sash:	2400 mm
Maximum window width - double sash with a movable post:	3200 mm
Maximum window height - double sash with a movable post:	2400 mm
Maximum sash area:	3 m ²
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg):	---

Photos

