

DA-SkyLine TYPE-R

Specification

Thermal efficiency	
Uw*: Coefficient value for reference design	od 0,85 W/(m²K)*
U factor*:	---
*:	for doors with sash dimensions of 2070 x 3444 mm, with a triple-glazed filling with a Ug coefficient of 0.5 W/(m²K) and a warm edge spacer
Profile	
Profile name:	DA- SkyLine
Installation depth:	Sash: 71 mm Frame: 190 mm (2-rail) and 292 mm (3-rail)
Number of chambers:	3
Thermal break:	yes
Number of seals:	2
Glass	
Glazing package:	6ESGx16x6ESGx16x6ESG
Ug value:	0,5 W/m²K
Glazing Package Thickness:	52 to 60 mm
Sound insulation of available glazing:	31 to 47dB
Maximum construction dimensions	
Width:	max. 14 m
Height:	max. 4 m
Sash size	
Min. sash width:	---
Max. sash width:	---
Min. sash height:	---
Max. sash height:	---
Max. sash weight:	1200 kg

Max. sash area:	6,5 m ²
Technical parameters	
Watertightness:	up to class 8A (450 Pa), EN 12208
Air permeability:	class 4 PN, EN 12207
Wind load resistance:	class C3 (1200 Pa)/B3(1200 Pa), PNEN 12210
Other	
Other:	Visible sash joint width 25 mm