

# Profiled doors DA-45 (internal system)



## Specification

Thermal efficiency	
Uw*: Coefficient value for reference design	6,0 W/m <sup>2</sup> K
U factor*:	---
*:	doors reference 1230 mm x 2180 mm
Profile	
Profile name:	DA-45
Installation depth:	Sash: 45 mm   Frame: 45 mm
Number of chambers:	1
Thermal break:	none
Number of seals:	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package:	Single 33,1 mm
Ug value:	5,7 W/m <sup>2</sup> K
Glazing Package Thickness:	Glazing thickness available from 4 to 25 mm
Sound insulation of available glazing:	---
Fittings	
Type:	---
Hinges:	SURFACE HINGES Durable and stable hinges adjustable in three planes. They guarantee smooth door operation and increase safety. Standard color: white, brown, silver   Optional colors: Joinery color
Anti-theft protection:	---
Microventilation:	---
Other:	---
Handle	
Colors:	Standard color: white, brown, silver   Optional color: stainless steel, old gold, woodwork color

Handle model:	Handle on a long backplate made of high quality aluminum.
<b>Insert</b>	
Insert type:	Construction insert
<b>Lock</b>	
Lock type:	1-point locking system with a classic latch-bolt mechanism
<b>Sash size</b>	
Min. sash width:	900 mm
Max. sash width:	1250 mm
Min. sash height:	2050 mm
Max. sash height:	2400 mm
Max. sash weight:	180 kg
Max. sash area:	---