

Profiled doors DA-65



Specification

Thermal efficiency	
Uw*: Coefficient value for reference design	1,7 W/m2K
U factor*:	---
*:	doors reference 1230 mm x 2180 mm
Profile	
Profile name:	DA-65
Installation depth:	Sash: 65 mm Frame: 65 mm
Number of chambers:	3
Thermal break:	24 mm glass-fibre reinforced polyamide thermal breaks
Number of seals:	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package:	Double glazing package 33,1x16x33,1
Ug value:	1,1 W/m2K
Glazing Package Thickness:	glazing thickness available: from 4 to 51 mm
Sound insulation of available glazing:	---
Fittings	
Type:	Door fittings
Hinges:	SURFACE HINGES Durable and stable hinges adjustable in three planes. They guarantee smooth door operation and increase safety. Standard color: white, brown, silver Optional colors: Joinery color
Anti-theft protection:	anti-theft bolts
Microventilation:	---
Other:	---
Handle	
Colors:	Standard color: white, brown, silver
Handle model:	Handle on a long backplate made of high quality aluminum.

Insert	
Insert type:	Construction insert
Lock	
Lock type:	1-point locking system with a classic latch-bolt mechanism
Sash size	
Min. sash width:	900 mm
Max. sash width:	1300 mm
Min. sash height:	2050 mm
Max. sash height:	2400 mm
Max. sash weight:	180 kg
Max. sash area:	---