

Profiled doors DA-90 Thermo



Specification

Thermal efficiency	
Uw*: Coefficient value for reference design	0,9 W/m2K
U factor*:	---
*:	doors reference 1230 mm x 2180 mm
Profile	
Profile name:	DA-90 Thermo
Installation depth:	Sash: 90 mm Frame: 90 mm
Number of chambers:	3
Thermal break:	34 mm wide thermal break made of glass fibre reinforced polyamide additional insulating insert in the middle chamber
Number of seals:	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package:	Triple glazing package 33,1x18x4x18x33,1 warm black border TGI
Ug value:	0,5 W/m2K
Glazing Package Thickness:	glazing thickness available: from 14 to 73 mm
Sound insulation of available glazing:	Rw: from 31 to 47 dB
Fittings	
Type:	Door fittings
Hinges:	ROLLER HINGES A durable and stable solution with an elegant appearance. Adjustable in three planes. They guarantee smooth door operation and increase the level of security. Standard color: white, brown, silver Optional color: the color of the joinery
Anti-theft protection:	anti-theft bolts
Microventilation:	---
Other:	---
Handle	

Colors:	Standard color: white, brown, silver
Handle model:	Handle on a long backplate made of high quality aluminum.
Insert	
Insert type:	Class B insert
Lock	
Lock type:	3-point locking system manual
Sash size	
Min. sash width:	900 mm
Max. sash width:	1300 mm
Min. sash height:	2050 mm
Max. sash height:	3000 mm
Max. sash weight:	180 kg
Max. sash area:	---