

SlideLine Patio Doors



Specification

Thermal efficiency	
Uw*: Coefficient value for reference design	0,76 W/(m²K)*
U factor*:	---
*:	for door of dimensions: 2460 x 2180 mm with 3-glass package of Ug value 0,5 W/(m2K) and the swisspacer
Profile	
Profile name:	SlideLine
Installation depth:	Sash: 76 mm Frame: 152 mm Bars: 76 mm
Number of chambers:	Frame: 7 Sashes and bars: 5
Thermal break:	does not apply
Number of seals:	2 EPDM seals
Glass	
Glazing package:	4/18/4/18/4
Ug value:	0,5 W/m²K
Glazing Package Thickness:	max. 48 mm
Sound insulation of available glazing:	from 31 to 45 dB
Fittings	

Type:	flush-sliding fitting
Hinges:	does not apply
Anti-theft protection:	does not apply
Microventilation:	yes
Other:	does not apply
Handle	
Colors:	Acc. to the equipment
Handle model:	501
Maximum construction dimensions	
Width:	max. 4000 mm min. 1600 mm
Height:	max. 2600 mm min. 1000 mm
Sash size	
Min. sash width:	814 mm
Max. sash width:	1950 mm
Min. sash height:	938 mm
Max. sash height:	2538 mm
Max. sash weight:	200 kg
Max. sash area:	4,4 m ²
Other	
Other:	Frame's construction - screwed

Photos

