

BESTLINE®

PREMIUM SYNTHETIC

HD

Patented

One Gallon
Treats
640
Gallons

DIESEL FUEL TREATMENT

Contains Sulfur Replacement Technology (SRT)®

BOOSTS CETANE RATING

- Improves power
- Improves efficiency & mileage
- Increases performance

STABILIZES FUEL

- Maintains optimum performance even when fuel is stored for long periods

COLD FLOW IMPROVER

- Bonds with the wax in diesel fuel and helps prevent it from clumping in cold weather
- Generally lowers the cloud point and pour point by 10° to 13° Fahrenheit
- With a good quality arctic blend of diesel fuel, the "cold flow improver" was proven effective to below -45° Fahrenheit

Directions: Use 2 ounces of BestLine's Diesel Fuel Treatment for each 10 gallons of fuel. In very cold weather use 3 ounces of BestLine's Diesel Fuel Treatment for each 10 gallons of fuel.

Available from:

SUPERIOR LUBRICATION

For fuel pumps, injectors, valves and cylinders. Specially formulated to reduce all issues created by Ultra Low Sulfur Diesel (ULSD) fuel:

- Cleans entire fuel system
- Minimizes wear & reduces repairs
- Contains Sulfur Replacement Technology (SRT)®
- Extends the life of your engine
- Using the diesel fuel industry standard HFRR test, BestLine's Diesel Fuel Treatment has been shown, using only 2 ounces per 10 gallons of fuel, to reduce wear by over 25%

BIOCIDES

- Stops the growth of algae and bacteria that degrade performance and clog filters



Available in:
16 oz/1/5/55 Gallons

www.bestlinelubricants.com

© 2015 BestLine Lubricants® All Rights Reserved