

# 5 REASONS TO USE TILE SPACERS

1

Aesthetics - Spacers provide uniform spacing between tiles. When filled with suitable grout, makes tile assembly appealing.

2

No lippage - Spacers minimize lippage and chipping of tile corners is reduced.

3

Uniform spacing between tiles - Allows expansion & contraction of tiles, thus no cracking of tiles.

4

Efficient tiling - Use of spacers help in efficient tile laying, maintaining uniform levels. Eliminates readjusting or redoing of tiling.

5

No water seepage- Uniform tile spacing filled with **FAVICRETE-100** Tile Joint doesn't allow water seepage through tile gaps.

RJS **FAVICRETE**™

## RJS Favicrete-100 Epoxy Grout

For Interior & Exterior Applications

**FAVICRETE-100** is a stain free epoxy grout for wall application on tile & stones.

Where hygiene is of utmost importance such as bathroom, kitchens, living room, airports and high traffic areas. It is water & chemical resistant joint filler which is available in 36 colors suitable for joints 2mm to 20mm, UV Resistant.

Advantages :

- 100% Stainfree
- Strong and durable
- Chemical and temperature resistant
- Anti bacterial & Anti Fungal
- Colour-Fast
- Easy to Install and Clean
- Water cleanable When Fresh
- Non-Cracking or Powdering
- Available in a Range of 36 Colours

Recommended For :

- Ceramic floor & Wall Tile
- Quarry tile
- Marble
- Stone
- Pavers
- Slate
- Porcelain tile/Vitrified tile

Coverage : Varies with Tile & Stone size and Grout Width

Packing : 1kg & 5kg units

Colour : 36 Colors

Compliance : Meets the Following Standards \*ANSI : 118.3 \*EN 13888: RG2 \*VOC : Very Low

| Tile Size X Thickness |       |     | Joint Width |     |     |     |      |      |  |
|-----------------------|-------|-----|-------------|-----|-----|-----|------|------|--|
| in mm                 | 1.5mm | 2mm | 3mm         | 4mm | 6mm | 8mm | 10mm | 12mm |  |
| 100x100x3             | 342   | 264 | 177         | 133 | 90  | 68  | 55   | 46   |  |
| 150x150x4             | 385   | 296 | 198         | 149 | 100 | 75  | 61   | 51   |  |
| 200x150x5             | 348   | 269 | 181         | 136 | 91  | 69  | 55   | 46   |  |
| 150x300x6             | 340   | 263 | 175         | 132 | 88  | 66  | 53   | 44   |  |
| 300x300x6             | 515   | 394 | 263         | 198 | 132 | 100 | 80   | 67   |  |
| 450x300x7             | 530   | 405 | 270         | 202 | 135 | 101 | 81   | 68   |  |
| 600x450x8             | 664   | 506 | 337         | 253 | 169 | 127 | 101  | 85   |  |
| 600x600x8             | 750   | 591 | 394         | 295 | 197 | 148 | 119  | 99   |  |
| 600x900x11            | 654   | 515 | 343         | 258 | 171 | 129 | 103  | 86   |  |
| 900x900x12            | 749   | 590 | 393         | 295 | 197 | 148 | 118  | 99   |  |

Approximate sq.ft. coverage for glass mosaic

| TILE SIZE   | JOINT WIDTH | JOINT DEPTH |
|-------------|-------------|-------------|
| 20mm x 20mm | 1.5mm       | 2mm         |

Coverage : Approximate Sq Feet coverage per # 1 unit (5 kg ) of Favicrete 100. As per the actual site the consumption vary accordingly. These Figures are for Inductive Purpose.

RJS **FAVICRETE**™

## RJS Favicrete Unsanded Grout

A carefully prepared blend of Portland cement, graded aggregates, polymer fortifiers and color-fast pigments. It is designed for joint width 1mm to 5mm, for porous & absorbent type tiles, non-vitreous clay tiles, and marble & glazed wall tiles. Suitable for internal and external applications.

**Applications :** Residential, commercial, external facades.

**Mixing Ratio :** Use approx.400 ml of water or **FAVICRETE** grout Admix for 1 kg of **FAVICRETE** Unsanded Grout.

**Coverage:** Varies with tiles size and grout width.

**Packaging:** 1kg

**For Tile Joints 1mm-5mm**

**Colour :** Available in a range of 36 colours

**Compliance :** Meets the following standards •ANSI : 118.6 •EN 13888: CGI •VOC : Very Low

**Advantages :**

- Colour-Fast
- Easy Maintenance
- Weather Resistant
- Non-Shrinking
- Non-Cracking
- Easy Application and Clean up
- Non Wet Curing Required When used with FAVICRETE Grout Admix
- Available in a Range of 36 Colours

**Recommended For :**

- Ceramic floor & Wall Tile
- Quarry tile
- Marble
- Stone
- Pavers
- Slate
- Porcelain tile/Vitrified tile

**Coverage :** Approximate sq.ft coverage per 10 kg Packet.

| Tile Size X Thickness |      |      | Joint Wdth |     |     |  |
|-----------------------|------|------|------------|-----|-----|--|
| in mm                 | 1mm  | 2mm  | 3mm        | 4mm | 5mm |  |
| 100x100x3             | 1057 | 539  | 366        | 278 | 227 |  |
| 150x150x4             | 1182 | 599  | 404        | 305 | 247 |  |
| 200x150x5             | 1079 | 545  | 368        | 277 | 224 |  |
| 150x300x6             | 1047 | 528  | 358        | 268 | 216 |  |
| 300x300x6             | 1566 | 788  | 529        | 397 | 319 |  |
| 450x300x7             | 1608 | 808  | 542        | 406 | 327 |  |
| 600x450x8             | 2007 | 1007 | 674        | 504 | 405 |  |
| 600x600x8             | 2341 | 1174 | 785        | 587 | 471 |  |
| 600x900x11            | 2041 | 1023 | 684        | 511 | 410 |  |
| 900x900x12            | 2338 | 1171 | 782        | 585 | 469 |  |

For Any Support Contact

☎ : +91 9560 870 630

✉ : sales@rjsfavicrete.com

Follow us on



Visit [www.rjsfavicrete.com](http://www.rjsfavicrete.com)

## Favicrete Chemie & Company

Office No.212, Parmesh Business Centre -1, Plot No.20, Karkardooma Community Centre , Delhi -110092



Find us!

RJS **FAVICRETE**™

Premium RJS Favicrete-100 Epoxy Grout & Unsanded Grout



Bright White

Quarry Red

Silk

Almond

Natural Grey

Sterling Silver

Platinum

Raven

Antique White

Sauterne

Dusty Rose

Parchment

Buff

Canyon Red

Mayan Red

Sable

Hemp

Mushroom

Mocha

Sandstone

Marble Beige

Midnight Black

Ivy

Sierra Sunrise

Inca Gold

Sage

Sky Blue

Alpine Bule

Burgundy

Silver Shadow

Slate Grey

Aqua Blue

Sapphire

Somme Grey

Cadmium Red

Saltillo