

RJS FAVICRETETM



RJS FAVICRETE Premium Floor And Wall Adhesives, Grouts & Cleaner

RJS FAVICRETE TA-01

Premium Floor and Wall Tile Adhesive

Polymer Fibre Modified Grey Cement Adhesive For Installing Wall & Floor Ceramics
Vitrified Tiles ,It Gives Excellent Bond on Cementitious Surfaces .

Applications: Designed For Interior Floor And Wall Tile Size Up To 1x1 Feet .

Advantages:

- Ready To Use . Needs Only Mixing With Water
- Flexible , Shock And Impact Resistant
- Fast & Economical
- High Bond Strength
- Adjustable
- Excellent Work Ability

Suitable Substrate:

- Concrete Mortar Beds
- Cement Plaster
- Brick Masonry
- Cement Terrazzo



Coverage : Approx 55-60 sq. Ft. Per 20 kg bag with a ¼ x ¼ (6mmx6mm) square notch trowel for a bed of 3 mm (Consumption may vary depending on the evenness on the substrate , trowel notch size ,type of tile and application technique)

Bed Thickness : Can be used up to 12 mm

Packing : 20 Kg

Color: Grey

Compliance: Indian Standard IS 15477 : 2019, C1 T / Type -1

Shelf Life: 15 Months from month & manufacturing for unopened bags, stored in dry conditions.

RJS FAVICRETE TA-02

Premium Floor and Wall Tile Adhesive

Polymer Fibre Modified Grey Cement Adhesive For Installing Wall & Floor Ceramics
Vitrified Tiles ,It Gives Excellent Bond on Cementitious Surfaces .

Applications: Designed For Interior Floor And Wall Tile Size Up To 2X4 Feet .

Advantages:

- Ready To Use . Needs Only Mixing With Water
- Flexible , Shock And Impact Resistant
- Fast & Economical
- High Bond Strength
- Adjustable
- Excellent Work Ability

Suitable Substrate:

- Concrete Mortar Beds
- Cement Plaster
- Brick Masonry
- Cement Terrazzo



Coverage : Approx 55-60 sq. Ft. Per 20 kg bag with a ¼ x ¼ (6mmx6mm) square notch trowel for a bed of 3 mm (Consumption may vary depending on the evenness on the substrate , trowel notch size ,type of tile and application technique)

Bed Thickness : Can be used up to 12 mm

Packing : 20 Kg

Color: Grey

Compliance: Indian Standard IS 15477 : 2019, C2TE/ TYPE-2

Shelf Life: 15 Months from month & manufacturing for unopened bags, stored in dry conditions.

RJS FAVICRETE TA-03

Premium Floor and Wall Tile Adhesive

High Polymer Fibre Modified Powder Offering Vast Utility Including Applications For Floor And Wall In Interior Areas . It is a Cementitious Thin Set Powder To Be Mixed Only With Water To Various Types of Verified , Ceramics Tiles And Large Format Stone on Floor , Can Be Fixed Any Tile Size In Interior Application on Wall And Stone Up To 2x4 Feet .

Applications: Designed For Interior Floor & Wall Installation of Any Tiles Size of Ceramic, Vitreous Tiles, Glass Mosaic Tiles And Stones Up To 2x4 Feet On Wall .

Advantages:

- Ready To Use . Needs Only Mixing With Water
- Also suitable for tile over tile / stone, stone over tile/stone
- Flexible , Shock And Impact Resistant
- Polymer modified bonds with various substrates.
- Excellent adhesion & low shrinkage
- Excellent Work Ability

Suitable Substrate:

- Concrete Mortar Beds
- Ceramic Tile and stone
- Cement Plaster
- Concrete / Brick Masonry
- Cement Terrazzo

Coverage : Approx 55-60 sq. Ft. Per 20 kg bag with a ¼ x ¼ (6mmx6mm) square notch trowel for a bed of 3 mm (Consumption may vary depending on the evenness on the substrate , trowel notch size ,type of tile and application technique)

Bed Thickness: Can be used up to 12 mm

Packing: 20 Kg

Color: Grey & White

Compliance: Indian Standard IS 15477 : 2019, C2 TE / Type -3

Shelf Life: 15 Months from month & manufacturing for unopened bags, stored in dry conditions.



RJS FAVICRETE TA-04

Premium Floor and Wall All Kind of Tiles for Exterior Wall & Floor

A Multipurpose High Fibre Polymer Modified Adhesive For Interior and Exterior for Any Tile Size Application

RJS FAVICRETE TA-04 Multipurpose Floor and wall Tiles and Stones Adhesive is designed to mix with water and has a convenient open time with high adhesion & workability .

Applications: Designed for interior & exterior floor and wall any tile Size applications..

Advantages:

- Ready To Use . Needs Only Mixing With Water
- Also suitable for tile over tile / stone , stone over Tile /stone
- Flexible , shock and impact resistant
- Polymer modified Bonds with various substrates.
- Excellent adhesion & Low shrinkage
- Excellent Work Ability
- High Performance in all types of Weather

Suitable Substrate:

- Concrete
- Concrete Mortar Beds
- Ceramic Tile and stone
- Cement Plaster
- Concrete / Brick Masonry
- Cement Terrazzo



RJS FAVICRETE FARALASTIK

It is a two component, modified Polyurethane Adhesive designed for the installation of ceramic tile, vitrified tile, metal tile, glass tile, agglomerates, glass mosaic tile and natural stone on any substrate. It is highly elastic, thixotropic and suitable to lay water sensitive tiles & stones on highly expandable, deformable, absorbent and non-absorbent substrates.

Application: Designed especially for interior and exterior floor and wall installations of all types of ceramic tile, vitreous, semi-vitreous tile, glass mosaic tiles, precast terrazzo, engineered stone, metal tiles and natural stones over concrete and on a variety of substrates including metal substrates and drywall boards.

Advantages:

- Highly flexible & superior bond strength
- Suitable for all the substrates including metal
- Good for vertical applications
- Ideal for agglomerates & moisture sensitive tiles / stones

Suitable Substrates:

- Concrete – VDF, Tremix and MIVON
- Concrete masonry & brick masonry
- Cement mortar beds & plaster
- Metal floors and walls
- Tile and stone
- Wood & Plywood*
- Cement backer board* & Gypsum board*
- Cement terrazzo
- Engineered stones & marbles
- Epoxy or PU resin based Substrates
- Rubber, PVC and Linoleum Substrates



Coverage:- 15 to 17 sq.ft per pack of 5 kg with ¼" x ¼" (6mm x 6mm) Square notch trowel for a bed of 3mm.

Coverage will vary depending on trowel notch size, type and size of tile and substrate and evenness and plumb.

Packaging:- 5 Kg Pail (Part A: 0.400 kg Part B: 4.600 kg)

Factory proportioned unit consisting of two conveniently packed components – Hardener, Resin (Part A and Part B)

Color: Off White

Compliance: Meets the following standards

- EN: 12004/ISO 13007 : R2T
- IS 15477 : 2019 : TYPE 5TS2
- VOC: Very Low

Shelf life: 12 months from date of manufacture when stored unopened in a cool, dry place between 10° C and 35° C

RJS FAVICRETE -100 EPOXY GROUT

For Interior & Exterior Applications

RJS Favicrete -100 is a stain free epoxy grout for wall application on tile & stones. Where is hygiene is of utmost importance such as bathroom, kitchens, living room, airports and high traffic areas. It is water & chemical resistant joint filler which is available in 36 colors suitable for joints 2mm to 20mm, UV Resistant.

Applications : Kitchens, bathrooms, swimming pools, fountains, water bodies, hospitals, restaurant, cafeterias, light industrial applications and high traffic areas .

Advantages :

- 100% Stainfree
- Strong and durable
- Chemical and temperature resistant
- Anti bacterial & Anti Fungal
- Colour-Fast
- Easy to Install and Clean
- Water cleanable When Fresh
- Non-Cracking or Powdering
- Available in a Range of 36 Colours

Recommended For :

- Ceramic floor & Wall Tile
- Quarry tile
- Marble
- Stone
- Pavers
- Slate
- Porcelain tile/Vitrified tile

Coverage : Varies with Tile & Stone size and Grout Width

Packing : 1kg & 5kg units

Colour : 36 Colors

Compliance : Meets the Following Standards °ANSI : 118.3 °EN 13888: RG2 °VOC : Very Low



Tile Size X Thickness						Joint Width		
in mm	1.5mm	2mm	3mm	4mm	6mm	8mm	10mm	12mm
100x100x3	342	264	177	133	90	68	55	46
150x150x4	385	296	198	149	100	75	61	51
200x150x5	348	269	181	136	91	69	55	46
150x300x6	340	263	175	132	88	66	53	44
300x300x6	515	394	263	198	132	100	80	67
450x300x7	530	405	270	202	135	101	81	68
600x450x8	664	506	337	253	169	127	101	85
600x600x8	750	591	394	295	197	148	119	99
600x900x11	654	515	343	258	171	129	103	86
900x900x12	749	590	393	295	197	148	118	99

Approximate sq.ft. coverage for glass mosaic

TILE SIZE	JOINT WIDTH	JOINT DEPTH
20mm x 20mm	1.5mm	2mm

Coverage : Approximate Sq Feet coverage per # 1 unit (5 kg) of Favicrete 100. As per the actual site the consumption vary accordingly. These Figures are for Inductive Purpose.

RJS FAVICRETE - 100 SPARKLE GROUT

For Interior & Exterior Applications

RJS FAVICrete -100 is a stain free Sparkle grout for wall application on tile & stones. Where is hygiene is of utmost importance such as bathroom, kitchens, living room, airports and high traffic areas. It is water & chemical resistant joint filler which is available in 10 in 3 Finish Gold, Silver and Copper suitable for joints 2mm to 20mm, UV Resistant.

Applications : Kitchens, bathrooms , swimming pools ,fountains, water bodies, hospitals ,restaurant, cafeterias, light industrial applications and high traffic areas .

Advantages :

- 100% Stainfree
- Strong and durable
- Chemical and temperature resistant
- Anti bacterial & Anti Fungal
- Colour-Fast
- Easy to Install and Clean
- Water cleanable When Fresh
- Non-Cracking or Powdering
- Available in Gold,Silver & Copper Finish-10 Colors each.

Recommended For :

- Ceramic floor & Wall Tile
- Quarry tile
- Marble
- Stone
- Pavers
- Slate
- Porcelain tile/Vitrified tile



Coverage : Varies with Tile & Stone size and Grout Width

Packing : 1kg & 5kg units

Color : Gold ,Silver and Copper Finish

Compliance : Meets the Following Standards °ANSI : 118.3 °EN 13888: RG2 °VOC : Very Low

RJS FAVICRETE UNSANDED GROUT

A carefully prepared blend of Portland cement, graded aggregates, polymer fortifiers and color-fast pigments. It is designed for joint width 1mm to 5mm, for porous & absorbent type tiles, non-vitreous clay tiles, and marble & glazed wall tiles. Suitable for internal and external applications.

Applications : Residential, commercial, external facades

Advantages : • For tile joints 1mm-5mm • Uniform colour • Hard and durable • Economical

Mixing Ratio : Use approx.400 ml of water or,FAVICRETE Grout Admix for 1 kg of „FAVICRETE Unsanded Grout.

Coverage : Varies tiles size and grout width.

Packaging : 1kg

Color : Available in a range of 36 colors

Compliance : Meet the following standards

• ANSI : 118.6 • EN 13888: CG1 • VOC : Very Low



RJS FAVICRETE™

Advantages :

- Colour-Fast
- Easy Maintenance
- Weather Resistant
- Non-Shrinking
- Non-Cracking
- Easy Application and Clean up
- Non Wet Curing Required When used with FAVICRETE Grout Admix
- Available in a Range of 36 Colours

Recommended For :

- Ceramic floor & Wall Tile
- Quarry tile
- Marble
- Stone
- Pavers
- Slate
- Porcelain tile/Vitrified tile

RJS FAVICRETE GROUT ADMIX

RJS FAVICRETE Grout Admix is specially designed Latex Admix to be used with Unsanded Grout.

Applications : It improves the performance of Portland cement grouts for all type of ceramic tile, brick, marble, natural stone and agglomerate stone installations.

Advantages : •Colour-fastness •Flexibility •Compressive strength • Shock and chemical resistance
•Reduces water absorption •Easy to clean

Coverage : Varies by application.

Packaging : 200ml, 400ml, 1Ltr, 5Ltr, 20Ltr.

Compliance : VOC : Very Low



RJS FAVICRETE TILE CLEANER

RJS FAVICRETE TILE CLEANER is a fast acting acid based cleaner for regular cleaning of dirt and stains on tile surfaces.

RJS Favicrete Tile Cleaner is designed for daily maintenance of tiles. It is ideal for interior and exterior use.

Applications :

- Unglazed Ceramic Tile
- Glazed ceramic Tile
- Vitrified Tile
- Porcelain Tile
- Glass Tile

Advantages :

- Cleans dirt and removes stains
- Easy to use
- Fastacting

Coverage : Depends on porosity of the substrate.

Packaging : 1Ltr. can



Favicrete Chemie & Company

Office No.212, Parmesh Business Centre -1, Plot No.20, Karkardooma
Community Centre, Delhi -110092

For Any Support Contact

☎ : +91 9560 870 630 | ✉ : sales@rjsfavicrete.com

Follow us on



Visit : www.rjsfavicrete.com



Find us!