

5 REASONS TO USE TILE SPACERS

1

Aesthetics - Spacers provide uniform spacing between tiles. When filled with suitable grout, makes tile assembly appealing

2

No lippage - Spacers minimize lippage and chipping of tile corners is reduced.

3

Uniform spacing between tiles - allows expansion & contraction of tiles, thus no cracking of tiles.

4

Efficient tiling - Use of spacers help in efficient tile laying, maintaining uniform levels. Eliminates readjusting or redoing of tiling.

5

No water seepage- Uniform tile spacing filled with ^{rjs}Favicrete-100 Sparkle Grout doesn't allow water seepage through tile gaps.

^{rjs}Favicrete-100 Sparkle Grout

For Interior & Exterior Applications

^{rjs}Favicrete -100 is a stain free Sparkle grout for wall application on tile & stones. Where hygiene is of utmost importance such as bathroom, kitchens, living room, airports and high traffic areas. It is water & chemical resistant joint filler which is available in 10 Colors in 3 Finish Gold, Silver and Copper suitable for joints 2mm to 20mm, UV Resistant.

Application : Kitchens, bathrooms, swimming pools, fountains, water bodies, hospitals, restaurant, cafeterias, light industrial applications and high traffic areas.

Advantage

- 100% Stain free
- Strong and durable
- Chemical and temperature resistant
- Anti bacterial & Anti Fungal

Coverage : Varies with Tile & Stone size and Grout Width

Packing : 1kg & 5kg units

Tile Size X Thickness			Joint Width						
in mm	1.5mm	2mm	3mm	4mm	6mm	8mm	10mm	12mm	
100x100x3	342	264	177	133	90	68	55	46	
150x150x4	385	296	198	149	100	75	61	51	
200x150x5	348	269	181	136	91	69	55	46	
150x300x6	340	263	175	132	88	66	53	44	
300x300x6	515	394	263	198	132	100	80	67	
450x300x7	530	405	270	202	135	101	81	68	
600x450x8	664	506	337	253	169	127	101	85	
600x600x8	750	591	394	295	197	148	119	99	
600x900x11	654	515	343	258	171	129	103	86	
900x900x11	749	590	393	295	197	148	118	99	

Approximate sq.ft coverage for glass mosaic

TILE SIZE	JOINT WIDTH	JOINT DEPTH
20mmx20mm	1.5mm	2mm

Compliance Meets the Following Standards ANSI : 118.3 EN 13888 : RG2 VOC : Very Low

Coverage Approximate Sq Feet coverage per # 1 unit (5kg) of ^{rjs}Favicrete-100 Sparkle epoxy grout. As per the actual site the consumption vary accordingly. These Figures are for Inductive Purpose.



Find us !

For Any Support Contact

☎ : +91 9560870630

✉ : sales@rjsfavicrete.com

Follow us on



Visit: www.rjsfavicrete.com

Favicrete Chemie & Company

Office No.212, Parmesh Business Centre-1, Plot No.20, Karkardooma Community Centre, Delhi-110092

^{RJS}FAVICRETE™



^{RJS}FAVICRETE-100 SPARKLE GROUT

PREMIUM SPARKLE GROUT





LIGHT WHEAT GOLD



MAJESTIC SUNRISE GOLD



AMAZON RED GOLD



DARK CHOCOLATE GOLD



DESERT SAND GOLD



SPRING GREEN GOLD



SILVER MELLOW GOLD




ASH GREY GOLD

gold



SERENE BLACK GOLD



OCEAN BLUE GOLD



LIGHT WHEAT SILVER



MAJESTIC SUNRISE SILVER



AMAZON RED SILVER



DARK CHOCOLATE SILVER




DESERT SAND SILVER



SPRING GREEN SILVER

gold

silver



SILVER MELLOW SILVER



ASH GREY SILVER



SERENE BLACK SILVER



OCEAN BLUE SILVER



LIGHT WHEAT COPPER



MAJESTIC SUNRISE COPPER



AMAZON RED COPPER



DARK CHOCOLATE COPPER

silver

copper



DESERT SAND COPPER



SPRING GREEN COPPER



SILVER MELLOW COPPER



ASH GREY COPPER



SERENE BLACK COPPER



OCEAN BLUE COPPER

copper