



DATA SHEET

INTRODUCTION

Yorkshire Gaskets Grade YG-100 is a Commercial / SBR Rubber. Generally resistant to Water, Air and some Acids. This grade of rubber is not recommended for high temperature applications.

General Purpose Rubber Sheetting YG- 100

PROPERTIES	TEST METHOD	VALUE
BASE POLYMER	NR/SBR	
HARDNESS	ASTM D2240 00	65° SHORE 'A'
TENSILE STRENGTH	ASTM D412	3 MPa
SPECIFIC GRAVITY	ASTM D792	1.5 g/cm ³
ELONGATION @ BREAK	ASTM D412	250% min
MIN CONTINUOUS WORKING TEMP		-30° C
MAX CONTINUOUS WORKING TEMP		70° C
MAX INTERMITTENT WORKING TEMP		90° C
COMPRESSION SET (70° FOR 22 HOURS)	ASTM D395 METHOD B	30% Max

GENERAL GUIDELINES FOR USE	
ABRASION RESISTANCE	MODERATE
GENERAL PURPOSE	EXCELLENT
FOOD USE	NOT RECOMMENDED
OZONE WEATHER RESISTANCE	NOT RECOMMENDED
FLAME RETARDENCY	NOT RECOMMENDED
ELECTRICAL RESISTANCE	NOT RECOMMENDED



Yorkshire
Gaskets Ltd



@gaskets247



CERTIFICATE NO. 14235
ISO9001

The information given is based upon average values and is in no way intended as a warranty. The purchaser shall be responsible for determining the suitability of the product for any particular application.