

**109-4L**

# Safety Data Sheet

## Section 1: Product and Company Identification

### Product Identifier and Other Means of Identification

**Product Identifier: 109-4L****Other Means of Identification:** Isopropyl Alcohol 50%**Related Part #** 109-500ML, 109-1L, 109-5G

### Recommended Use and Restriction on Use

**Use:** Multipurpose cleaner for electronic**Uses Advised Against:** Not for use on monitor screens or glass with anti-glare coatings.

### Details of Manufacturer or Importer

Dustronics Inc.  
10 Bramhurst Ave., Unit 18  
Brampton, ON L6T 5H1  
CANADA

Tel: 416-880-6772  
Email: [service@dustronics.com](mailto:service@dustronics.com)  
[www.dustronics.com](http://www.dustronics.com)

### Emergency Phone Number

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)

**For emergencies involving the transport of dangerous goods;** 24/7 service CANADA—  
Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

## 109-4L

### Section 2: Hazards Identification



#### Classification of Hazardous Chemical

##### GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Eye irritation	2A	Warning	Exclamation
Specific Target Organ Toxicity      Single Exposure	3	Warning	Exclamation

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories do not allow comparisons between classes.

#### Label Elements

<b>Signal Word</b>	<b>DANGER</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H225: Highly flammable liquid and vapor
	H319: Causes serious eye irritation H336: May cause drowsiness or dizziness
<b>Prevention</b>	<b>Precautionary Statements</b>
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof equipment.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist, vapors or spray.
P271	Use only outdoors or in a well-ventilated area.

*Section continued on the next page*

## 109-4L

*Continued...*

Prevention	Precautionary Statements
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves and eye protection.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
Storage	Precautionary Statements
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

### Other Hazards

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

### Section 3: Hazardous Ingredients

CAS #	Chemical Name	% (weight)
67-63-0	propan-2-ol <sup>a)</sup>	50%
7732-18-5	Distilled water	50%

a) Commonly known as isopropyl alcohol (IPA)

## 109-4L

### Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
<b>IF ON SKIN (or hair)</b>	P303 + P361 + P353
<b>Immediate Symptoms</b>	<i>dry skin, redness</i>
<b>Response</b>	Take off immediately all contaminated clothing. Rinse skin with water or shower.
<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>irritation, tearing, redness, pain</i>
<b>Response</b>	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
<b>IF INHALED</b>	P304 + P340 + P312
<b>Immediate Symptoms</b>	<i>cough, dizziness, drowsiness, headaches, weakness, unconsciousness</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing. If feeling unwell: Call a POISON CENTRE or doctor.
<b>IF SWALLOWED</b>	P301 + P330 + P331
<b>Immediate Symptoms</b>	<i>nausea, headaches, dizziness, weakness, unconsciousness</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting.

### Section 5: Fire-Fighting Measures

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, water fog, or chemical foam to extinguish. Use water spray to cool containers.
<b>Specific Hazards</b>	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion. Prevent fire-fighting wash from entering waterway or sewer system.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> )
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus for fire fighting

## 109-4L

### Section 6: Accidental Release Measures

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Avoid breathing vapors. Remove or keep away all sources of ignition or extreme heat.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
<b>Cleaning Methods</b>	Collect liquid in a sealable, solvent-resistant container. Wipe up further residue with paper towel and place dirty towels in container. Wash spill area with soap and water to remove the last traces of residue.  <b>RECOMMENDATION:</b> Use a grounded stainless steel or carbon steel container or a solvent resistant plastic container.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

### Section 7: Handling and Storage

<b>Prevention</b>	Keep out of reach of children.  Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  Ground and bond container and receiving equipment. Take action to prevent static discharges. Use explosion-proof electrical, ventilating, and lighting equipment.  Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area.  Keep container tightly closed.
<b>Handling</b>	Wear protective gloves, protective clothing, and eye protection.  Wash hands thoroughly after handling.
<b>Storage</b>	Store in a well-ventilated area. Keep cool.  Store locked up.

## 109-4L

### Section 8: Exposure Controls/Personal Protection

#### Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
propan-2-ol	ACGIH	200 ppm (TWA)	400 ppm
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	200 ppm	400 ppm
	Canada BC	200 ppm	400 ppm
	Canada ON	200 ppm	400 ppm
	Canada QC	400 ppm	500 ppm

*Note:* The ACGIH<sup>1</sup>, OSHA, and Canadian provinces exposure limits were consulted. Limits from the RTECS database<sup>2</sup> and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

#### Engineering Controls

**Ventilation** Keep airborne concentrations below the occupational exposure limits (OEL).

#### Personal Protective Equipment

**Eye protection** Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Use safety glasses with lateral protection (side shields).

**Skin Protection** For likely contacts, use of protective butyl rubber, nitrile, neoprene, polyethylene gloves or other chemically resistant gloves.

For incidental contacts, use disposable nitrile or neoprene gloves, or other chemically resistant gloves.

Do NOT use latex rubber, polyvinyl alcohol (PVA) or PVC gloves.

*Section continued on the next page*

## 109-4L

### Respiratory Protection

For over-exposures up to 10 x OEL of mist, vapors, and spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator, or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

### General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

### Section 9: Physical and Chemical Properties

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b>	2%
<b>Appearance</b>	Colorless	<b>Upper Flammability Limit</b>	12%
<b>Odor</b>	Alcohol like	<b>Vapor Pressure @20 °C</b>	4.2 kPa [32 mmHg]
<b>Odor Threshold</b>	0.44 ppm	<b>Vapor Density</b>	2.1 (Air = 1)
<b>pH</b>	Not available	<b>Relative Density @20 °C</b>	0.86–0.87
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Fully miscible
<b>Initial Boiling Point</b>	≥80.6 °C [≥177 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>a)</sup>	18 °C [64 °F]	<b>Auto-ignition Temperature</b>	≥425 °C [≥797 °F]
<b>Evaporation Rate</b>	1.5 (ButAc = 1)	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Highly Flammable	<b>Viscosity @25 °C</b>	≥2.4 mPa·s [≥3.1 mm <sup>2</sup> /s]

a) Tag closed cup

## 109-4L

### Section 10: Stability and Reactivity

<b>Reactivity</b>	Not available
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Ignition sources, excessive heat, and incompatible substances. Vapors may form explosive mixture with air.
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids, strong bases, halogenated compounds, aluminum at temperatures $\geq 49\text{ }^{\circ}\text{C}$ [ $\geq 120\text{ }^{\circ}\text{F}$ ]
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5

### Section 11: Toxicological Information

#### Summary of Effects and Symptoms by Routes of Exposure

<b>Eyes</b>	Causes serious eye irritation, tearing, redness or pain.
<b>Skin</b>	Cause dry skin and redness.
<b>Inhalation</b>	May cause drowsiness or dizziness. Excessive exposure may cause narcotic effects, weakness, headaches, and unconsciousness.
<b>Ingestion</b>	See inhalation symptoms.
<b>Chronic</b>	Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

#### Acute Toxicity (Lethal Exposure Concentrations)

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
propan-2-ol	3 600 mg/kg Rat	12 800 mg/kg Rabbit	16 000 ppm 8 h Rat

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier SDSs were also consulted.

*Section continued on the next page*



## 109-4L

### Other Toxicological Effects

<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.
<b>Serious eye damage/irritation</b>	Causes moderate to severe eye irritation based on Draize tests on rabbits
<b>Sensitization</b> (allergic reactions)	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b> (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	Propan-2-ol can affect the central nervous system by inhalation causing drowsiness or dizziness.
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	The liquid content does not meet the aspiration hazard criteria. The mixture doesn't contain category 1 substances.

### Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The 2-propanol component is not classifiable as an environmental toxicant with minimal LC50 of 9 640 mg/L 96 h for *Pimephales promelas* (fathead minnow); 5 102 mg/L 24 h *Daphnia magna* (water flea); >2 000 mg/L 24 h *Pseudokirchneriella subcapitata* (green algae).

*Section continued on the next page*

## 109-4L

### Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

### Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

### Biodegradability

Not available

### Other Effects

Volatile Organic Content (VOC)  $\leq 70\%$  (603 g/L)

## Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

## Section 14: Transport Information

### Ground

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes 1 L and under  
109-500ML, 109-1L  
**Limited Quantity**



Sizes greater than 1 L  
109-4L, 109-5G  
**UN number:** UN1219  
**Shipping Name:** ISOPROPANOL  
**Class:** 3  
**Packing Group:** II  
**Marine Pollutant:** No



*Section continued on the next page*

**109-4L****Air****Refer to ICAO-IATA Dangerous Goods Regulations.**

Sizes 0.5 L and under

*109-500ML***Limited Quantity**Max Net Qty/Outer Pkg  
= 1 LSizes 0.5 L up to 5 L (passenger),  
60 L (cargo)*109-500ML, 109-1L, 109-4L***UN number:** UN1219**Shipping Name:** ISOPROPANOL**Class:** 3**Packing Group:** II**Marine Pollutant:** No**Sea****Refer to IMDG regulations.**

Sizes 1 L and under

*109-500ML, 109-1L***Limited Quantity**

Sizes greater than 1 L

*109-1L, 109-4L, 109-5G***UN number:** UN1219**Shipping Name:** ISOPROPANOL**Class:** 3**Packing Group:** II**Marine Pollutant:** No

**Note:** Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

**Section 15: Regulatory Information****Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

*Section continued on the next page*

## 109-4L


### USA

#### Other Classifications

##### HMIS® RATING

HEALTH:	2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

##### NFPA® 704 CODES



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

##### CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

##### EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains propan-2-ol (CAS# 67-63-0) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

##### TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

##### California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA)

This product does not contain any of the listed substances.

### Europe

##### RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

##### WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

## 109-4L

### Section 16: Other Information

**MSDS Prepared by** Dustronics Inc. Regulatory Department  
**Date of Revision** 03 Jan 2024  
**Supersedes**  
**Reason for Changes:** NA

#### References

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®), MDL Information Systems, Inc.

#### Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.dustronics.com](http://www.dustronics.com)  
Email: [service@dustronics.com](mailto:service@dustronics.com)

*Section continued on the next page*

## 109-4L

**Mailing Addresses** *Head Office*

10 Bramhurst Ave. Unit 18  
Brampton, Ontario, Canada  
L6T 5H1

**Disclaimer**

This safety data sheet is provided as an information resource only. *Dustronics Inc.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.