Empack Spraytech Inc. 98 Walker Drive Brampton, Ontario, L6T 4H6 Canada 905-792-6571

# PRODUCT: Emzone 12a A/C Dye Charge - 114 g

spraytech inc.

## **SECTION 01: IDENTIFICATION**

Product Item Numbers Product Identity Manufacturer	EM-045853 Emzone 12a A/C Dye Charge - 114 g Empack Spraytech Inc. 98 Walker Drive Brampton Ontario Canada L6T 4H6 905-792-6571
24 hour emergency telephone number Recommended Use Chemical Family	CANUTEC: 1-613-996-6666. Universal oil lubricant for A/C systems. Mixture.

## **SECTION 02: HAZARD IDENTIFICATION**



Label Elements: Signal Word Hazard Classification:	DANGER.
Physical Hazards Health Hazards	Flammable Aerosols - Category 1. Gases Under Pressure - Liquefied Gas. Not Classified.
Environmental Hazards	Not Classified.
Hazard Statement	H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated (1). H280:Contains gas under pressure; may explode if heated (L).
Precautionary Statements:	(·). ··································
Prevention	P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use.
Response	None .
Storage	P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. P403:Store in a well ventilated place.
Disposal	P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.
Hazard(s) not otherwise classified (HNOC)	None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS				
CHEMICAL NAME AND SYNONYMS	CAS #	WT. %		
Isobutane	75-28-5	30-60		
Propane	74-98-6	30-60		

#### **SECTION 04: FIRST-AID MEASURES**

Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.
Skin Contact	Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.
Eye Contact	
Ingestion Most important symptoms/effects, acute	If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.
and delayed Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

# CODE: EM-045853

#### PRODUCT: Emzone 12a A/C Dye Charge - 114 g

#### SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Unsuitable Extinguishing Media Specific Hazards Arising from the Chemica	Dry chemical powder. Carbon dioxide. Foam, water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire. I Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special Protective Equipment and Precautions for Firefighters General Fire Hazards	Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Extremely flammable aerosol.

### SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).
Methods and Materials for Containment and Cleaning Up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13).
Environmental Precautions	

## SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling
Conditions for Safe Storage including any Incompatibilities

Read and observe all precautions and instructions on the label. Product is flammable. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid prolonged exposure. Use in well-ventilated areas. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

## SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	A( TWA	CGIH TLV STEL	PEL	SHA PEL STEL	NIOSH
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available
Propane	Not available	Not available	1,000 ppm	Not available	Not available
Appropriate Engineering Individual Protection Mea Eye/Face Protection Skin Protection Respiratory Protection Thermal Hazards General Hygiene Consid	asures:	Value if unprotected perso Do not get in eyes. Wear s Chemical resistant gloves appropriate chemical resis Use NIOSH approved res None Known. When using, do not eat, d	onnel are involved. safety glasses with are recommended stant clothing. pirator suitable for rink or smoke. Alw ndling the material	n side-shields. d. Avoid contact with the sk organic vapours. rays observe good persona and before eating, drinking	in. Wear I hygiene measures,

## SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES



www.trivalent.com

#### CODE: EM-045853

#### PRODUCT: Emzone 12a A/C Dye Charge - 114 g

#### SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Auto Ignition Temperature (°C)
Lower Flammable Limit (% Vol)
Upper Flammable Limit (% Vol) Coefficient of Water/Oil Distribution
Coefficient of Water/Oil Distribution
Viscosity

460°C (860°F). (Isobutane). 1.8. (Isobutane). 8.8. (Isobutane). N/A. N/A.

#### SECTION 10: STABILITY AND REACTIVITY

Reactivity
Chemical Stability
Possibility of Hazardous Reactions
Conditions to Avoid
Incompatible Materials
Hazardous Decomposition Products

Product not reactive under normal conditions of use.
Material is stable under normal conditions.
Will not occur.
Avoid sources of heat and flame, and electrostatic charge. Reacts with water and acid.
Oxidizing agents. Water. Acids. Bases.
Carbon Oxides.

#### SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50	
Isobutane	658 mg/L (Rat - 4 hrs)	Not available	
Propane Information on Likely Routes of Exposure: Routes of entry - Inhalation Routes of entry - Skin & Eye Routes of entry - Ingestion	No.	Not available	
Routes of entry - Skin Absorption Symptoms Related to the Physical, Chemical and Toxicological Characteristics Acute Toxicity Skin Corrosion/Irritation	No known significant effects. May cause mild skin irritation.		
Serious Eye Damage/Eye Irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity Carcinogenicity	May irritate eyes. Not expected to be a skin or respiratory sensitizers. No information is available, and no adverse effects are expected.		
Reproductive Toxicity STOT - Single Exposure STOT - Repeated Exposure Aspiration Hazard Chronic Effects	Contains no ingredient listed as toxic to reproduction. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.		

## **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity	Complete information is not yet available. This product has not been tested. Based on information available on its ingredients, no adverse environmental impact is anticipated under intended use in accordance with instructions.
Persistence and degradability Bioaccumulation Potential Mobility in Soil Other Adverse Effects	The product itself has not been tested. The product itself has not been tested. The product itself has not been tested.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

Appropriate Disposal Methods.....

Empty containers may be recycled. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with current local, provincial and federal regulations.

# **SECTION 14: TRANSPORT INFORMATION**

TDG (Canada- Road)	UN1950, AEROSOLS, Class 2.1, Ltd. Qty.
DOT (US-Road)	UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D.
IMDG (International- Marine)	UN1950, AEROSOLS, Class 2.1, Ltd. Qty.
IATA (International- Air)	UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

Powered by



CODE: EM-045853

# PRODUCT: Emzone 12a A/C Dye Charge - 114 g

# SECTION 15: REGULATORY INFORMATION

Canada Regulations: Canadian Environmental Protection Act	Refer to Section 2 for a WHMIS 2015 Classification for this product. All ingredients listed appear on the Domestic Substances List (DSL).
(CEPA) US Regulations	Environmental Protection Act: Constituents of this product are included on the TSCA inventory.
OSHA	This product is considered hazardous under the Federal OSHA hazard communication standard.

## **SECTION 16: OTHER INFORMATION**

Disclaimer	The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.
Abbreviations	
Prepared by Latest Revision	Regulatory Affairs 2022-03-11

CODE: EM-045853

Powered by