



Moneysworth & Best  
120 Midair Court  
Brampton, ON, L6T 5V1  
Canada  
905-790-0650

**PRODUCT: 16102\_Pro-tex Water&Stain Protector 300g/10.5oz - CA**

**CODE: P2-016102**

### SECTION 01: IDENTIFICATION

Product Item Numbers..... P2-016102  
 Product Identity..... 16102\_Pro-tex Water&Stain Protector 300g/10.5oz - CA  
 Supplier..... Moneysworth & Best  
 120 Midair Court  
 Brampton, ON  
 Canada  
 L6T-5V1  
 905-790-0650  
 24 hour emergency telephone number..... In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800) 424-9300.  
 Recommended Use..... Water and stain protector. Ideal for all outdoor fabrics and leather.  
 Chemical Family..... Mixture.

### SECTION 02: HAZARD IDENTIFICATION



Label Elements:  
 Signal Word..... DANGER.  
 Hazard Classification:  
 Physical Hazards..... Flammable Aerosols - Category 1. Gases Under Pressure - Liquefied Gas.  
 Health Hazards..... Skin Irritation - Category 2. Specific Target Organ Toxicity, Single Exposure - Category 3.  
 Environmental Hazards..... Not Classified.  
 Hazard Statement..... H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated (1). H280:Contains gas under pressure; may explode if heated (L). H315:Causes skin irritation. H336:May cause drowsiness or dizziness.

Precautionary Statements:  
 Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use. P264:Wash hand thoroughly after handling. P280:Wear protective gloves. P261:Avoid breathing dust/fume/gas/mist/vapours/spray. P271:Use only outdoors or in a well-ventilated area.

Response..... P302+P352:IF ON SKIN: Wash with plenty of water. P332+P313:If skin irritation occurs: Get medical advice/attention. P362+P364:Take off contaminated clothing and wash it before reuse. P321:For specific treatment see section 4 on this SDS. P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312:Call a POISON CENTER if you feel unwell.

Storage..... P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. P403+P233:Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

Disposal..... P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.

Hazard(s) not otherwise classified (HNOC) None Known.

### SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Heptane (including isomers)	64742-49-0	60-100
Propane	74-98-6	10-30
Mineral Spirits	8052-41-3	0.1-1

### SECTION 04: FIRST-AID MEASURES

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.  
 Skin Contact..... Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.

PRODUCT: 16102\_Pro-tex Water&amp;Stain Protector 300g/10.5oz - CA

CODE: P2-016102

**SECTION 04: FIRST-AID MEASURES**

Eye Contact..... Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if irritation persists.

Ingestion..... Ingestion is unlikely to occur. If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention.

Most important symptoms/effects, acute .. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct and delayed contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**SECTION 05: FIRE-FIGHTING MEASURES**

Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog.

Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special Protective Equipment and ..... Firefighters must use standard protective equipment including flame retardant coat, helmet Precautions for Firefighters with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

General Fire Hazards..... Extremely flammable aerosol.

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

Personal Precautions, Protective ..... No action shall be taken involving any personal risk or without suitable training. Evacuate Equipment and Emergency Procedures surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).

Methods and Materials for Containment .. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, and Cleaning Up earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Environmental Precautions..... Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

**SECTION 07: HANDLING AND STORAGE**

Precautions for Safe Handling..... Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.

Conditions for Safe Storage including any Incompatibilities Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV		OSHA PEL	NIOSH
		STEL	REL		
Heptane (including isomers)	1,600 mg/m3 (RCP-TWA)	Not available	Not available	Not available	Not available
Propane	Not available	Not available	1,000 ppm	Not available	Not available
Mineral Spirits	100 ppm	Not available	500 ppm	Not available	350 mg/m3
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Ensure that eyewash stations and safety showers are available.				
Individual Protection Measures:					
Eye/Face Protection.....	Do not get in eyes. Wear safety glasses with side-shields.				
Skin Protection.....	Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.				
Respiratory Protection.....	Use dust and mist respirator.				
Thermal Hazards.....	None Known.				

PRODUCT: 16102\_Pro-tex Water&amp;Stain Protector 300g/10.5oz - CA

CODE: P2-016102

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

General Hygiene Considerations..... When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Form..... Aerosol.  
 Physical Appearance..... Clear mist.  
 Odor..... Hydrocarbons.  
 Odor Threshold (ppm)..... N/A.  
 Specific Gravity (Liquid)..... 0.680-0.700.  
 Specific Gravity (Aerosol)..... 0.650-0.670.  
 Vapour Density (Air=1)..... >1.  
 Aerosol Vapour Pressure (psig, 21°C)..... 40-60.  
 pH..... N/A.  
 Evaporation Rate (n-Butyl Acetate = 1)..... > 1 (n-Butyl Acetate = 1).  
 Boiling Point liquid (°C)..... 93°C (199.4°F).  
 Melting/Freezing Point (°C)..... N/A.  
 Flashpoint (Method)..... Closed Cup.  
 Flash Point (propellant)..... -104°C (-155.2°F).  
 Flashback..... Yes.  
 VOC Content..... Not available.  
 Solubility in water..... Nil.  
 Aerosol Flame Projection..... > 45 cm but < 100 cm.  
 Auto Ignition Temperature (°C)..... 450°C (842°F). (Propellant).  
 Lower Flammable Limit (% Vol)..... 2.2. (Propellant).  
 Upper Flammable Limit (% Vol)..... 9.5. (Propellant).  
 Coefficient of Water/Oil Distribution..... N/A.  
 Viscosity..... 0.6 cSt (0.6 mm2/sec) at 20 deg C. (Heptane).

**SECTION 10: STABILITY AND REACTIVITY**

Reactivity ..... Product not reactive under normal conditions of use.  
 Chemical Stability..... Material is stable under normal conditions.  
 Possibility of Hazardous Reactions..... Will not occur.  
 Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.  
 Incompatible Materials..... Strong oxidizing agents. Strong acids.  
 Hazardous Decomposition Products..... Carbon Oxides.

**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Heptane (including isomers)	>23.3 mg/L (Rat - 4 hrs)	>5,840 mg/kg (Oral - Rat); >2,920 mg/kg (Dermal - Rat)
Propane	658 mg/L (Rat - 4 hrs)	Not available
Mineral Spirits	3,500 ppm (Rat - 4hrs)	>5,000 mg/kg (Oral - Rat)
Information on Likely Routes of Exposure:		
Routes of entry - Inhalation.....	No.	
Routes of entry - Skin & Eye.....	Yes.	
Routes of entry - Ingestion.....	No.	
Routes of entry - Skin Absorption.....	Yes.	
Symptoms Related to the Physical, .....	Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.	
Chemical and Toxicological Characteristics		
Acute Toxicity.....	Harmful or fatal if swallowed.	
Skin Corrosion/Irritation.....	Causes skin irritation.	
Serious Eye Damage/Eye Irritation.....	May irritate eyes.	
Respiratory or Skin Sensitization.....	May cause sensitization by skin contact.	
Germ Cell Mutagenicity.....	No data available to indicate product or any components present at greater than 0.1% are mutagenic.	
Carcinogenicity.....	None of the ingredients are listed as possibly carcinogenic to humans by IARC or ACGIH.	
Reproductive Toxicity.....	Contains no ingredient listed as toxic to reproduction.	
STOT - Single Exposure.....	Specific target organ toxicity single exposure Category 3. May cause drowsiness and dizziness.	
STOT - Repeated Exposure.....	No data available .	
Aspiration Hazard.....	Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.	

PRODUCT: 16102\_Pro-tex Water&amp;Stain Protector 300g/10.5oz - CA

CODE: P2-016102

**SECTION 11: TOXICOLOGICAL INFORMATION**

Chronic Effects..... Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Oral LD50-Rat (Mixture, calculated):..... ~7,000 mg/kg.

Dermal LD50-Rabbit (Mixture, calculated): 3,500 mg/kg.

Inhalation LC50-Rat 4hrs (Mixture, ..... 28.0 mg/L.  
calculated):

**SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity..... This product contains the following substances which is hazardous for the environment:  
Heptanes including isomers (CAS#: 64742-49-0): Toxicity to fish: LL50 > 13.4 mg/L, 96 hrs;  
Toxicity to other aquatic invertebrates: EL50 3 mg/L, 48 hrs; Toxicity to algae: EL50 10-30  
mg/L, 72 hrs. Chronic Toxicity Daphnia magna: NOEC 0.17 mg/L 21 days.

Persistence and degradability ..... The product itself has not been tested.

Bioaccumulation Potential..... The product itself has not been tested.

Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Appropriate Disposal Methods..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.

**SECTION 14: TRANSPORT INFORMATION**

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

DOT (US-Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D.

IMDG (International- Marine)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

IATA (International- Air)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

**SECTION 15: REGULATORY INFORMATION**

Canada Regulations:..... Refer to Section 2 for a WHMIS 2015 Classification for this product.

Canadian Environmental Protection Act ... All ingredients listed appear on the Domestic Substances List (DSL).  
(CEPA)

Domestic Substances List (DSL)..... Yes.

US Regulations..... Environmental Protection Act: Constituents of this product are included on the TSCA inventory. This product is considered hazardous under the OSHA Hazard Communication Standard.

**SECTION 16: OTHER INFORMATION**

Disclaimer..... The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

Prepared by ..... Regulatory Affairs

Latest Revision ..... 2021-02-24