

Safety Data Sheet

Section 1: Product and Company Identification

Product Identifier and Other Means of Identification

Product Identifier: Lacquer Thinner Cleaner **Other Means of Identification:** Not available **Related Part #** 20010, 55001, 20020-5G

Recommended Use and Restriction on Use

Use: Solvent

Uses Advised Against: Not applicable

Details of Manufacturer or Importer

Dustronics Inc. 10 Bramhurst Ave., Unit 18 Brampton, ON L6T 5H1 CANADA

Tel: 416-880-6772

Email: service@dustronics.com

www.dustronics.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures, or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones



Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Eye irritation	2A	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER		
Pictograms	Hazard Statements		
	H225: Highly flammable liquid and vapor		
	H319: Causes serious eye irritation		
(!)	H336: May cause drowsiness or dizziness		
Prevention	Precautionary Statements		
Prevention P210	Precautionary Statements Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.		
-	Keep away from heat, hot surfaces, sparks, open flames, and other		
P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.		
P210 P240	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Ground and bond container and receiving equipment.		
P210 P240 P241	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof equipment.		
P210 P240 P241 P243	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof equipment. Take action to prevent static discharges.		

Section continued on the next page

Page **2** of **14**



Со			

Prevention	Precautionary Statements
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves, protective clothing, eye protection.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
Storage	Precautionary Statements
P403 + P235	Store in well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS#	Chemical Name	%(weight)
67-64-1	acetone	10-15%
67-56-1	Methanol	10-15%
108-88-3	Toluene	40-50%
1330-20-7	Xylene	5-10%
78-93-3	Methyl Ethyl Ketone	5-10%



Section 5: Fire-Fighting Measures

Fire-Fighter

LACQUER THINNER CLEANER-20020

Section 4: First-Aid Measures				
Exposure Condition	GHS Code: Precautionary Statement			
IF ON SKIN (or hair)	P303 + P361 + P353			
Immediate Symptoms	dry skin			
Response	Take off immediately all contaminated clothing. Rinse skin with water or shower.			
IF IN EYES	P305 + P351 + P338, P337 + P313			
Immediate Symptoms	severe irritation, redness, pain			
Response Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.				
	If eye irritation persists: Get medical advice or attention			
IF INHALED	P304 + P340, P312			
Immediate Symptoms	cough, sore throat, nausea, headache, drowsiness, dizziness, unconsciousness			
Response	Remove person to fresh air and keep comfortable for breathing.			
	Call a POISON CENTRE or doctor if you feel unwell.			
IF SWALLOWED	P301 + P330, P331			
Immediate Symptoms	nausea, dizziness, headaches, weakness			
Response	Rinse mouth. Do NOT induce vomiting.			

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
	Use water spray to cool containers.
Specific Hazards	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
Combustion Products	Produces carbon oxides (CO, CO ₂).

Wear self-contained breathing apparatus and full fire-fighting
turn-out gear.



Section 6: Accidental Release Measures

Personal Protection See personal protection equipment in Section 8.

Precautions for Response

Avoid breathing the mist, vapors, spray. Remove or keep away

all sources of ignition or extreme heat.

Environmental Precautions

Prevent spill from entering drains.

Containment Contain with inert absorbent (such as soil, sand, vermiculite).

Cleaning Collect the liquid in a sealable, chemical-resistant container.

Sprinkle inert absorbent compound onto spill, then sweep into the container. Use soap and water to remove the last traces of

residue.

RECOMMENDATION: Use a grounded stainless steel or carbon steel

container.

Disposal Methods Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames, and

other ignition sources. No smoking.

Ground and bond container and receiving equipment. Take action to prevent static discharges. Use explosion-proof equipment.

Keep container tightly closed.

Avoid breathing mist, vapors, or spray. Use only outdoors or in a

well-ventilated area.

Handling Wear protective gloves, protective clothing, eye protection.

Wash hands thoroughly after handling.

Storage Store in a well-ventilated area. Keep cool.

Store locked up.



Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
Lacquer Thinner Cleaner	ACGIH	500 ppm	750 ppm
•	U.S.A. OSHA PEL	1 000 ppm	Not established
	Canada AB	500 ppm	750 ppm
	Canada BC	250 ppm	500 ppm
	Canada ON	500 ppm	750 ppm
	Canada QC	750 ppm	1 000 ppm

Note: The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS² database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Engineering Controls

Ventilation Keep airborne concentrations below the occupational exposure

limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

RECOMMENDATION: Use safety glasses with lateral protection

(side shields).

Skin Protection For likely contacts, use of protective butyl rubber, fluorinated

rubber, or other chemically resistant gloves.

For incidental contacts, use neoprene, natural latex rubber, or

other chemically resistant gloves.



Respiratory Protection

For over-exposures up to 10 x OEL of mist, vapors, or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator, or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	2.5%
Appearance	Colorless	Upper Flammability Limit	12.8%
Odor	Ketone-like	Vapor Pressure @20°C	243 hPa [182 mmHg]
Odor Threshold	4.58 ppm	Vapor Density	2.01 (Air = 1)
рН	Not available	Relative Density @25 °C	0.79
Freezing/Melting Point	-94 °C [-137 °F]	Solubility in Water	Miscible
Initial Boiling Point	≥56 °C [≥133 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point a)	-17°C [1.4 °F]	Auto-ignition Temperature	465 °C [869 °F]
Evaporation Rate	6.3 (ButAc = 1)	Decomposition Temperature	Not available
Flammability	Highly Flammable	Viscosity @40 °C	<20.5 mm ² /s

a) Closed cup value



Section 10: Stability and Reactivity

Reactivity Lacquer Thinner Cleaner reacts exothermically with

phosphorous oxychloride, which can lead to an explosion.

Chemical Stability

Chemically stable at normal temperatures and pressures

Conditions to

Avoid flames, sparks, other ignition sources and incompatible

Avoid substances.

Incompatibilities Phosphorous oxychloride, strong oxidizing agents, strong bases

Polymerization Will not occur

Decomposition Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.

Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes Causes redness, serious eye irritation, and pain.

Skin May cause dry skin.

Inhalation May cause cough, sore throat, nausea, headache, and drowsiness,

dizziness. Severe overexposure may lead to unconsciousness.

Ingestion May cause nausea, weakness, headaches (see also inhalation

symptoms).

Chronic Prolonged or repeated exposure may cause skin dryness,

cracking, as well as defatting the skin.



Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
Lacquer Thinner	5 800 mg/kg	20 mL/kg	16 000 ppm
Cleaner	Rat	Rabbit ^{a)}	4 h Rat ^{a)}

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier SDSs were also consulted.

a) Supplier safety data sheet

Other Toxicological Effects

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Lacquer Thinner Cleaner is a known serious eye irritant.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Based on available data, the classification criteria are not met.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Lacquer Thinner Cleaner can affect the central nervous system by inhalation causing drowsiness or dizziness.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met. There are no category 1 components.



Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable sources.

Lacquer Thinner Cleaner does not meet classification criteria for aquatic environmental toxicants with LC50 and EC50 of >100 mg/L.

 Lacquer Thinner Cleaner has a minimal LC50 96 h of 5 540 mg/L for Oncorhynchus mykiss (rainbow trout) and an EC50 48 h of 13 500 mg/L for Daphnia magna (water flea).

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Biodegradability

Not available

Other Effects

Volatile Organic Content (VOC) = 0% [0 g/L] by VOC-Exemption

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.



Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations**.

Sizes 1 L and under 20010, 55001 Limited Quantity



Sizes greater than 1 L 20020, 20020-5G **UN number**: UN1090

Shipping Name: Lacquer Thinner Cleaner

Class: 3

Packing Group: II Marine Pollutant: No



Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 0.5 L and under 55001

Limited QuantityMax Net Qty/Pkg =

1 L



Sizes up to 5 L (passenger), 60 L (cargo)

20010, 55001, 20020 UN number: UN1090 Shipping Name: Lacquer

Thinner Cleaner

Class: 3

Packing Group: II Marine Pollutant: No



Sea

Refer to IMDG regulations.

Sizes 1 L and under 20010, 55001

Limited Quantity



Sizes greater than 1 L 20020, 20020-5G

UN number: UN1090 Shipping Name: Lacquer

Thinner Cleaner

Class: 3

Packing Group: II Marine Pollutant: No



Note: Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.



Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA

Other Classifications

HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product contains acetone (CAS# 67-64-1), which is subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.



TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity)

This product does not contain any substances known to be listed in California.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

Section 16: Other Information

Prepared by theDustronics Inc. Regulatory Affairs Department

Date of Revision 05 January 2024 **Supersedes** 18 February 2022

Reason for Changes: Update to emergency contact information.

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)



Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists (USA)

ECHA European Chemicals Agency

EU European Union

EC50 Half maximal effective concentration

EL50 Half maximal effective loading

IARC International Agency for Research on Cancer

NOELR No observable effect loading ratio NTP National Toxicology Program

GHS Globally Harmonized System of Classification of Labeling of Chemicals

LC50 Lethal Concentration 50%

LCLo Lowest published lethal concentration

LD50 Lethal Dose 50%

OEL Occupational Exposure Limit
PEL Permissible Exposure Limit

SDS Safety Data Sheet

STEL Short-Term Exposure Limit

TCLo Lowest published toxic concentration

TWA Time Weighted Average VOC Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.dustronics.com

Email: service@dustronics.com

Mailing Addresses Head Office

10 Bramhurst Ave. Unit 18 Brampton, Ontario, Canada

L6T 5H1

Disclaimer This safety data sheet is provided as an information resource only.

Dustronics Inc. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and

international regulations.