

Empack Spraytech Inc. 98 Walker Drive Brampton, Ontario, L6T 4H6 Canada 905-792-6571

PRODUCT: emzone 12A A/C System Conditioner - 114 g CODE: EM-045855

SECTION 01: IDENTIFICATION

Product Item Numbers..... EM-045855

Product Identity..... emzone 12A A/C System Conditioner - 114 g

Manufacturer.... Empack Spraytech Inc. 98 Walker Drive

Brampton
Ontario
Canada
L6T 4H6
905-792-6571

905-792-657

24 hour emergency telephone number..... In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800)

424-9300.

Chemical Family...... Mixture.

SECTION 02: HAZARD IDENTIFICATION



Label Elements: Signal Word..... DANGER. Hazard Classification: Physical Hazards..... Flammable Aerosols - Category 1. Gases Under Pressure - Liquefied Gas. Skin Irritation - Category 2. Eye Irritation - Category 2A. Carcinogenicity - Category 2. Specific Target Organ Toxicity, Repeated Exposure - Category 2. Health Hazards..... Environmental Hazards..... Not Classified. Hazard Statement..... H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated (1). H280:Contains gas under pressure; may explode if heated (L). H315:Causes skin irritation. H319:Causes serious eye irritation. H351:Suspected of causing cancer. H373:May cause damage to organs through prolonged or repeated exposure. (Liver). Precautionary Statements: P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Prevention..... No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use. P264:Wash hand thoroughly after handling. P202:Do not handle until all safety precautions have been read and understood. P201:Obtain special instructions before use. P280:Wear protective gloves/ protective clothing/ eye protection/ face protection. P260:Do not breathe dust/ fume/ gas/ mist/ vapours /spray. P302+P352:IF ON SKIN: Wash with plenty of water. P332+P313:If skin irritation occurs: Response.....

P302+P352:IF ON SKIN: Wash with plenty of water. P332+P313:If skin irritation occurs: Get medical help. P362+P364:Take off contaminated clothing and wash it before reuse. P321:For specific treatment see section 4 on this SDS. P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313:If eye irritation persists: Get medical advice/attention. P308+P313:If exposed or concerned: Get medical advice/attention. P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F.

international regulations.

Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS			
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %	
Isobutane	75-28-5	30-60	
Propane	74-98-6	30-60	
Organochlorinated Compound	-	10-30	

CODE: EM-045855

PRODUCT: emzone 12A A/C System Conditioner - 114 g

SECTION 04: FIRST-AID MEASURES

Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain
	immediate medical assistance.
Skin Contact	Wear chemical protective clothing if necessary. Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or
	immediately with plenty of water for 15-20 minutes. Consult a poison control centre or
	physician immediately.
Eye Contact	
_, - ,	water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation
	occurs.
Ingestion	If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.
Most important symptoms/effects, acute	Provide general supportive measures and treat symptomatically. If exposed or concerned,
	see a doctor for medical advice. All first aid procedures should be periodically reviewed by
and delayed	see a doctor for life uccar advice. All first and procedures should be periodically reviewed by
Indication of immediate medical attention	a doctor familiar with the chemical and its conditions of use in the workplace. Provide general supportive measures and treat symptomatically. In case of shortness of
and special treatment needed	breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be
	delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Dry chemical powder. Carbon dioxide. Foam, water spray or fog.
Unsuitable Extinguishing Media	Forms corrosive chemicals on contact with water.
Specific Hazards Arising from the Chemica	Il Contents under pressure. Pressurized container may explode when exposed to heat or
•	flame.
Special Protective Equipment and	Firefighters must use standard protective equipment including flame retardant coat, helmet
Precautions for Firefighters	with water to prevent vapor pressure build up. For massive fire in cargo area, use
	unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
General Fire Hazards	Extremely flammable aerosol.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).
Methods and Materials for Containment and Cleaning Up Environmental Precautions	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling	Read and observe all precautions and instructions on the label. Do not pressurize, cut,
-	weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames.
	Product is flammable. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour
	of this product. Avoid prolonged exposure. Use in well-ventilated areas.
Conditions for Safe Storage including any	Do not handle or store near an open flame, heat or other sources of ignition. Store away
Incompatibilities	from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	CGIH TLV STEL	O PEL	SHA PEL STEL	NIOSH REL
			1		
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available
Propane	Not available	Not available	1,000 ppm	Not available	Not available
Organochlorinated Compound	50 ppm	Not available	25 ppm	125 ppm	Not available
Appropriate Enginee	ring Controls		tion required to maintal personnel are involved.	in the point of use belo	w the Threshold Limit
Individual Protection Eye/Face Protection Skin Protection	Measures:	Do not get in eyes. Wear safety glasses with side-shields.			
	on	Use NIOSH approved respirator suitable for organic vapours.			

PRODUCT: emzone 12A A/C System Conditioner - 114 g

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

General Hygiene Considerations..... When using, do not eat, drink or smoke. Always observe good personal hygiene measures,

such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

CODE: EM-045855

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Form..... Aerosol. Physical Appearance..... Light Brown. Characteristic. Odor Threshold (ppm)..... N/A. Specific Gravity N/A. Vapor Pressure (@ 20°C)..... Vapour Density (Air=1)..... Not applicable. N/A. -11.72°C (10.9°F). -82.8. Tag Closed Cup. (Isobutane). Flashback..... No data. Evaporation Rate (n-Butyl Acetate = 1)..... >1. VOC Content..... No data. Solubility in water..... Insoluble. Aerosol Flame Projection..... N/A Auto Ignition Temperature (°C)...... Lower Flammable Limit (% Vol)..... Upper Flammable Limit (% Vol)..... 460°C (860°F). (Isobutane). 1.8. (Isobutane). 8.8. (Isobutane). Coefficient of Water/Oil Distribution...... Viscosity.....

SECTION 10: STABILITY AND REACTIVITY

Product not reactive under normal conditions of use. Material is stable under normal conditions. Will not occur. Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge. Reacts with water and acid. Incompatible Materials..... Increased risk of fire and explosion on contact with: strong oxidizing agents (e.g. perchloric

acid), methanol, alkali metals (e.g. sodium or potassium). Oxidizing agents. Water. Acids. Bases.

Hazardous Decomposition Products...... Prolonged contact with water may form corrosive hydrochloric acid.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50	
Isobutane	658 mg/L (Rat - 4 hrs)	Not available	
Propane	658 mg/L (Rat - 4 hrs)	Not available	
Organochlorinated Compound	77.01 mg/L (Rat - 4 hrs)	1,400 mg/kg (Oral - Rat); >2,000 mg/kg (Dermal - Rabbit)	
Information on Likely Routes of Exposure: Routes of entry - Inhalation	Yes. No. No. No. No. No. No. No. No. No. No		

PRODUCT: emzone 12A A/C System Conditioner - 114 g

SECTION 12: ECOLOGICAL INFORMATION

Complete information is not yet available. This product has not been tested. Based on Ecotoxicity..... information available on its ingredients, no adverse environmental impact is anticipated

under intended use in accordance with instructions.

Persistence and degradability The product itself has not been tested. Bioaccumulation Potential..... The product itself has not been tested. Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Empty containers may be recycled. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate

ponds, waterways or ditches with chemical or used container. Dispose in accordance with current local, provincial and federal regulations.

CODE: EM-045855

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty. UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D. UN1950, AEROSOLS, Class 2.1, Ltd. Qty. DOT (US-Road).....IMDG (International- Marine)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty. IATA (International- Air).....

SECTION 15: REGULATORY INFORMATION

Refer to Section 2 for a WHMIS 2015 Classification for this product. Canada Regulations:..... Canadian Environmental Protection Act ... All ingredients listed appear on the Domestic Substances List (DSL). (CEPA)

ÙS Regulations..... Environmental Protection Act: Constituents of this product are included on the TSCA

inventory OSHA.....

This product is considered hazardous under the Federal OSHA hazard communication

standard.

SECTION 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information

required by the CPR.

ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abbreviations.....

Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

Regulatory Affairs Prepared by

Latest Revision 2020-08-11