

Empack Spraytech Inc. 98 Walker Drive Brampton, Ontario, L6T 4H6 Canada 905-792-6571

PRODUCT: Emzone Brake & Parts Cleaner - The BIG Can - 482g CODE: P6-045046

SECTION 01: IDENTIFICATION

Product Item Numbers..... P6-045046

Emzone Brake & Parts Cleaner - The BIG Can - 482g Product Identity.....

Empack Spraytech Inc. 98 Walker Drive Manufacturer.....

Brampton Ontario Canada

L6T 4H6 905-792-6571

24 hour emergency telephone number..... In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800)

424-9300.

Recommended Use..... Solvent degreaser.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER. Hazard Classification:

Physical Hazards.....

Flammable Aerosols - Category 1. Gases Under Pressure - Compressed gas. Aspiration Hazard - Category 1. Skin Irritation - Category 2. Specific Target Organ Toxicity, Single Exposure - Category 3. Health Hazards.....

Not Classified. Environmental Hazards.....

Hazard Statement..... H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated (1). H280:Contains gas under pressure; may explode if heated (C). H315:Causes skin

irritation. H336:May cause drowsiness or dizziness. H304:May be fatal if swallowed and

enters airways.

Precautionary Statements:

Label Elements:

P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use. P264:Wash hand thoroughly after handling. P280:Wear Prevention.....

protective gloves. P261:Avoid breathing dust/fume/gas/mist/vapours/spray. P271:Use

only outdoors or in a well-ventilated area.

P301+P310:IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331:Do NOT induce vomiting. P302+P352:IF ON SKIN: Wash with plenty of water. P332+P313:If Response.....

skin irritation occurs. Get medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse. P321:For specific treatment see section 4 on this SDS. P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312:Call a POISON CENTER if you feel unwell.

P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. Storage.....

P403+P233:Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

P501:Dispose of contents/container in accordance with local, regional, national, and/or Disposal..... international regulations.

Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS					
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %			
Heptane (includng isomers)	64742-49-0	80-100			
Isopropyl alcohol	67-63-0	5-10			
Carbon dioxide	124-38-9	1-5			

CODE: P6-045046

PRODUCT: Emzone Brake & Parts Cleaner - The BIG Can - 482g

SECTION 04: FIRST-AID MEASURES

If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance. If breathing is difficult, give oxygen and get medical Inhalation..... attention. Do not give adrenaline, epinephrine or similar drugs following exposure to this product. Wash thoroughly with soap and lukewarm water. Skin Contact..... Eye Contact..... Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if irritation persists.

Do not induce vomiting, get medical attention. Consult poison control center or physician Ingestion..... IMMEDIATELY. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. Provide general supportive measures and treat symptomatically. In case of shortness of Most important symptoms/effects, acute .. and delayed Indication of immediate medical attention and special treatment needed breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Dry chemical powder. Carbon dioxide. Foam, water spray or fog. Suitable Extinguishing Media..... Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire. Specific Hazards Arising from the Chemical Contents under pressure. Pressurized container may explode when exposed to heat or flame. Firefighters must use standard protective equipment including flame retardant coat, helmet Special Protective Equipment and Precautions for Firefighters with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. General Fire Hazards..... Extremely flammable aerosol.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective No action shall be taken involving any personal risk or without suitable training. Evacuate Equipment and Emergency Procedures surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08). Methods and Materials for Containment ..

and Cleaning Up

Conditions for Safe Storage including any

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent Environmental Precautions..... environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling..... Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material.

Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas. Store locked up. Pressurized container. Protect from sunlight and do not expose to

temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from Incompatibilities

incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	CGIH TLV STEL	PEL	SHA PEL STEL	NIOSH REL
Heptane (includng isomers)	1,600 mg/m3 (RCP-TWA)	Not available	Not available	Not available	Not available
Isopropyl alcohol	400 ppm (980 mg/	/m3) 500 ppm (1,225 mg/m3)	400 ppm (980 mg/m3)	500 ppm (1,225 mg/m3)	400 ppm (980 mg/m3)
Carbon dioxide	5000 ppm	30000 ppm	9000 mg/m3	Not available	STEL: 30000ppm; TWA: 5000ppm

Appropriate Engineering Controls..... Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.



PRODUCT: Emzone Brake & Parts Cleaner - The BIG Can - 482g

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Individual Protection Measures:

Eye/Face Protection..... Do not get in eyes. Wear safety glasses with side-shields.

Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing. Skin Protection.....

Use dust and mist respirator. Respiratory Protection.....

Thermal Hazards..... None Known.

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. General Hygiene Considerations.....

CODE: P6-045046

Routinely wash work clothing and protective equipment prior to use.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Aerosol.

Physical Appearance..... Narrow powerful stream.

Odor..... Heptane. N/À. 0.680-0.700. 0.620-0.660. Aerosol Vapour Pressure (psig, 21°C)..... 85-95.

Vapour Density (Air=1).....

98 °C (209°F). N/A

-4°C (25°F). Tag Closed Cup. (Heptane).

Flashback..... Yes. Evaporation Rate (n-Butyl Acetate = 1)..... N/A.

VOC Content..... 96wt% (669g/L - 5.59 lb/gal).

Solubility in water..... Nil. >100 cm. 245. (Heptane). 1.1. (Heptane). 6.7. (Heptane).

Coefficient of Water/Oil Distribution......

Viscosity..... 0.49 cSt (0.49 mm2/sec) at 40 °C. (Heptane).

SECTION 10: STABILITY AND REACTIVITY

Product not reactive under normal conditions of use.

Material is stable under normal conditions.

Possibility of Hazardous Reactions..... Will not occur.

Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge. Incompatible Materials.....

Strong oxidizing agents. Strong acids.

Hazardous Decomposition Products...... Carbon Oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

LD50 **INGREDIENTS** LC50 Heptane (including isomers) >23.3 mg/L (Rat - 4hrs) >5,840 mg/kg (Oral - Rat); >2,920 mg/kg (Dermal - Rat)

3,636 mg/kg (Oral - Rat); Isopropyl alcohol 73 mg/L (Rat - 4hrs) 4,059 mg/kg (Dermal - Rabbit)

Carbon dioxide Not available Not available

Information on Likely Routes of Exposure:

Routes of entry - Inhalation..... Yes. Routes of entry - Skin & Eye...... Routes of entry - Ingestion..... Yes. Yes. Routes of entry - Skin Absorption.....

Symptoms Related to the Physical, Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred Chemical and Toxicological Characteristics vision. Defatting of the skin. Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Acute Toxicity..... Toxic if inhaled. Skin Corrosion/Irritation..... Causes skin irritation. Serious Eye Damage/Eye Irritation...... Respiratory or Skin Sensitization..... May irritate eyes.

Inhalation may cause respiratory tract irritation.

Germ Cell Mutagenicity..... No information is available.

Carcinogenicity..... None known.

Reproductive Toxicity..... No information is available.



PRODUCT: Emzone Brake & Parts Cleaner - The BIG Can - 482g

SECTION 11: TOXICOLOGICAL INFORMATION

STOT - Single Exposure..... Specific target organ toxicity single exposure Category 3. May cause drowsiness and

dizziness.

STOT - Repeated Exposure.....Aspiration Hazard..... May cause damage to the liver and kidneys through prolonged or repeated exposure. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical

pneumonitis, which can be fatal.

Chronic Effects..... Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. Heptanes including isomers (CAS#: 64742-49-0):

Toxicity to fish: LL50 > 13.4 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EL50 3 mg/L, 48 hrs; Toxicity to algae: EL50 10-30 mg/L, 72 hrs. Chronic Toxicity Daphnia magna:

CODE: P6-045046

NOEC 0.17 mg/L 21 days. The product itself has not been tested. Persistence and degradability Bioaccumulation Potential..... The product itself has not been tested. The product itself has not been tested. Mobility in Soil.....

None Known. Other Adverse Effects.....

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)......DOT (US-Road).....

UN1950, AEROSOLS, Class 2.1, Ltd. Qty. UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D. UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

IMDG (International- Marine)..... IATA (International- Air)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

SECTION 15: REGULATORY INFORMATION

Canada Regulations:.... WHMIS Classification. A: Compressed gas. B5: Flammable aerosol. D2B: Material causing

other toxic Materials.

Domestic Substances List (DSL)..... US Regulations..... Environmental Protection Act: Constituents of this product are included on the TSCA

inventory. This product is considered hazardous under the OSHA Hazard Communication

Standard.

Yes.

SECTION 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No guarantee or

warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information

required by the CPR. .

ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Abbreviations.....

Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

Prepared by Regulatory Affairs

JUŇ 04/2018 Latest Revision