

Label Elements:

Empack Spraytech Inc. 98 Walker Drive Brampton, Ontario, L6T 4H6 Canada 905-792-6571

CODE: P8-088177

PRODUCT: Emzone SAR 707 Foam and Fabric Adhesive - 454 g

SECTION 01: IDENTIFICATION

Product Identity..... Emzone SAR 707 Foam and Fabric Adhesive - 454 g

Product Item Numbers..... P8-088177

Empack Spraytech Inc. 98 Walker Drive Manufacturer.....

Brampton Ontario

Canada L6T 4H6 905-792-6571

In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800) 24 hour emergency telephone number.....

424-9300.

Recommended Use..... Adhesive .

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... WARNING. Hazard Classification: Flammable Aerosols - Category 2. Gases Under Pressure - Liquefied Gas. Acute Toxicity Oral - Category 4. Skin Irritation - Category 2. Eye Irritation - Category 2. Physical Hazards..... Health Hazards..... Carcinogenicity - Category 2. Specific Target Organ Toxicity, Single Exposure - Category 3. Specific Target Organ Toxicity, Repeated Exposure - Category 2. H223:Flammable aerosol. H229:Pressurised container: may burst if heated (2). Hazard Statement..... H280:Contains gas under pressure; may explode if heated (L). H302:Harmful if swallowed . H315:Causes skin irritation. H320:Causes eye irritation. H351:Suspected of causing cancer. H336:May cause drowsiness or dizziness. H335:May cause respiratory irritation. H373:May cause damage to organs through prolonged or repeated exposure. Precautionary Statements: P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Prevention..... No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use. P264:Wash hand thoroughly after handling. P270:Do not eat, drink, or smoke when using this product. P271:Use only outdoors or in a well-ventilated area. P202:Do not handle until all safety precautions have been read and understood. P201:Obtain special instructions before use. P280:Wear protective gloves/protective clothing/eye protection/face protection. P260:Do not breathe dust/fume/gas/mist/vapours/spray. P301+P312:IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell Response..... P330:Rinse mouth. P302+P352:IF ON SKIN: Wash with plenty of water. P332+P313:If skin irritation occurs: Get medical advice/attention. P362+P364:Take off contaminated clothing and wash it before reuse. P321:For specific treatment see section 4 on this SDS. P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313:If eye irritation persists: Get medical advice/attention. P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312:Call a POISON CENTER if you feel unwell. P308+P313:If exposed or concerned: Get medical advice/attention. P314:Get medical advice/attention if you feel unwell.

P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. Storage..... P403+P233:Store in a well-ventilated place. Keep container tightly closed. P405: Store

locked up.

P501:Dispose of contents/container in accordance with local, regional, national, and/or Disposal.....

international regulations.

Hazard(s) not otherwise classified (HNOC) None Known.

PRODUCT: Emzone SAR 707 Foam and Fabric Adhesive - 454 g

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS					
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %			
Dichloromethane	75-09-2	45-70			
Isobutane	75-28-5	10-30			
Propane	74-98-6	10-30			

SECTION 04: FIRST-AID MEASURES

If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain Inhalation..... immediate medical assistance. If breathing is difficult, give oxygen and get medical attention.

Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Get medical attention if irritation persists. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids.

Immediately flush the contaminated skin with soap and water. If this chemical penetrates clothing, immediately remove the clothing and flush the skin with water. If irritation persists after washing, get medical attention. Remove contaminated clothing. Launder clothing before reuse. If irritation occurs consult with your doctor.

Not likely to be ingested. If occurs, do not give anything by mouth to an unconscious person. Do not induce vomiting, get medical attention. Obtain medical advice.

Most important symptoms/effects, acute .. Direct eye contact may cause temporary eye irritation.

and delayed

Ingestion.....

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

CODE: P8-088177

SECTION 05: FIRE-FIGHTING MEASURES

Dry chemical powder. Carbon dioxide. Foam, water spray or fog. Suitable Extinguishing Media..... Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical Contents under pressure. Pressurized container may explode when exposed to heat or

Firefighters must use standard protective equipment including flame retardant coat, helmet Special Protective Equipment and

Precautions for Firefighters

with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from immediate hazard area if it is safe to do.

General Fire Hazards..... Flammable.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective **Equipment and Emergency Procedures** Methods and Materials for Containment .. and Cleaning Up

Ensure adequate ventilation; avoid formation of dust. Wear protective equipment and keep unprotected persons away. Use respiratory protection against the effects of dust. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent

Environmental Precautions..... environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling..... Wash thoroughly after handling . Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or

any other incandescent material. Avoid contact with eyes. Avoid breathing vapours or spray mists of this product. Use with adequate ventilation. Keep away from heat, sparks,

and open flames.

Conditions for Safe Storage including any Incompatibilities

Store in a cool, dry, well-ventilated area away from incompatible substances. Do not store in direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

CODE: P8-088177

PRODUCT: Emzone SAR 707 Foam and Fabric Adhesive - 454 g

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA AC	CGIH TLV STEL	OSHA PEL	PEL STEL	NIOSH REL	
Dichloromethane	50 ppm (8 hrs)	Not available	25 ppm (8 hrs)	125 ppm (15 minutes)	Not available	
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available	
Propane	Not available	Not available	1,000 ppm	Not available	Not available	
Appropriate Engineering	Controls	Local exhaust ventilation r Value if unprotected persouse.	required to maintain the onnel are involved. Gro	e point of use below the und all equipment and	Threshold Limit cylinders before	
Eye/Face Protection	idual Protection Measures: Face Protection		ion is required; howeve ves conforming to appo meability and breakthro	tety glasses in the event that eye contact is possible. is required; however, prolonged or repeated contact with skin conforming to appropriate regulations. Observe the subility and breakthrough time that are provided by the supplier atex gloves when there is a potential for prolonged or		
Respiratory Protection		excessive skin contact. Use approved NIOSH response concentrations are above approved respiratory protes	ot require the use of res the applicable exposur	spiratory protection. If a	irborne	
Thermal Hazards General Hygiene Consid		None Known. When using, do not eat, do such as washing after han Routinely wash work cloth	dling the material and	before eating, drinking,		

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Aerosol.
Physical Appearance	
Odour	No odour.
Odour Threshold (ppm)	Not available.
pH	Not applicable.
Vapour Pressure (psig)	60-75 .
Vapour Density (Air=1)	>1.
Evaporation Rate (n-Butyl Acetate = 1)	Not available.
Boiling Point (Propellant), ° C	-11.72°C (10.9°F).
VOC Content	Not available.
Specific Gravity (Liquid)	1.225.
Specific Gravitý (Aerosól)	1.022.
Solubility in water	Slightly soluble.
Auto Ignition Temperature (°C)	556°C (1032.8 °F). (Propellant).
Flash Point (°C), Method	-104 °C (-156°F). Estimated. (Propellant).
Flashback	No.
Lower Explosive Limit (%, vol)	1.8. (Propellant).
Upper Explosive Limit (%, vol)	9.5. (Propellant).

SECTION 10: STABILITY AND REACTIVITY

Product not reactive under normal conditions of use. Stable at normal temperatures and pressures.

Possibility of Hazardous Reactions..... Will not occur.

Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.

Incompatible Materials.....Hazardous Decomposition Products..... Avoid contacting with oxidizers.

No hazardous decomposition products when stored and handled correctly.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Dichloromethane	76 mg/L (Rat - 4hrs)	985 mg/kg (Oral - Rat)
Isobutane	658 mg/L (Rat - 4 hrs)	Not available
Propane	658 mg/L (Rat - 4 hrs)	Not available
Information on Likely Routes of Exposure: Routes of entry - Inhalation		



CODE: P8-088177

PRODUCT: Emzone SAR 707 Foam and Fabric Adhesive - 454 g

SECTION 11: TOXICOLOGICAL INFORMATION

Routes of entry - Ingestion..... Yes. Routes of entry - Skin Absorption..... Symptoms Related to the Physical, Chemical and Toxicological Characteristics Irritant effects.

Acute Toxicity..... Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.

Skin Corrosion/Irritation.....Serious Eye Damage/Eye Irritation..... Causes skin irritation.

Direct contact with eyes causes temporary irritation.

Inhalation may cause respiratory tract irritation. May cause skin sensitization. Respiratory or Skin Sensitization.....

Germ Cell Mutagenicity..... No information is available, and no adverse effects are expected.

Has been classified as a carcinogen by IARC. Carcinogenicity.....

Reproductive Toxicity..... No information is available.

STOT - Single Exposure..... Specific target organ toxicity single exposure Category 3. May cause drowsiness and

dizziness

STOT - Repeated Exposure..... Specific Target Organ, Repeated Exposure- Category 2. No data available Aspiration Hazard.....

Chronic Effects.....

No long term chronic effects are known or anticipated.

SECTION 12: ECOLOGICAL INFORMATION

May be dangerous for the environment. No data is available on the product itself. Should Ecotoxicity..... not be released into the environment. This product contains the following substance which may also be hazardous for the environment:. Methylene Chloride: Toxicity to fish: LC50 193 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EC50 1682 mg/L, 48 hrs; Toxicity

to algae: EC50 >662 mg/L, 96 hrs.

Bioaccumulation Potential..... The product itself has not been tested. Mobility in Soil..... The product itself has not been tested. Other Adverse Effects..... None Known.

Persistence and degradability The product itself has not been tested.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods...... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road).....

DOT (US-Road).....

UN1950, AEROSOLS, Class 2.1, Ltd. Qty. UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D. UN1950, AEROSOLS, Class 2.1, Ltd. Qty. UN1950, AEROSOLS, Class 2.1, Ltd. Qty. IMDG (International- Marine)..... IATA (International- Air).....

SECTION 15: REGULATORY INFORMATION

Refer to Section 2 for a WHMIS 2015 Classification for this product. Canada Regulations:....

OSHA (29CFR 1910.1200).
*WARNING: This product contains a chemical known to the State of California to cause US Regulations..... California Proposition 65.....

cancer. (Dichloromethane).

SECTION 16: OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the CPR and the Disclaimer.....

SDS contains all the information required by the CPR. . The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with

the use of the material.

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical

Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous

Materials Information System STOT: Specific Target Organ Toxicity.

Regulatory Affairs Prepared by

Latest Revision 2019-06-03