SAFETY TOOLS

Safety **Helmet**

The exclusive smooth crown design contains a technically advanced suspension with eight load bearing points to stabilize and balance the hard hat during every day wear. On impact, the Superlight impact energy control system dissipates force by reducing it to smaller increments and spreading it over a greater area.

Welding Helmet

Techno:- provides a welding helmet for every process and application. Each model is designed for a specific application but all have a full complement of exclusive performance and comfort features to satisfy the needs of today's high production welders.



Safety Vest

We carry safety vests that are suitable for day and night environments that require ANSI high visibility clothing. Our reflective vests reflect the safety priority required in construction sites, airports, emergency response situations, and law enforcement operations, utility crews operations, and survey crews, railroad workers – anywhere workers are exposed to traffic and need the high visibility protection of a reflective safety vest.



Safety **Glass**

Sport style 3D curved single lens, Wraparound with angle side protection, Universal nose bridge, Hard coated lens as standard



Safety Shoes

Fire Hydrant Coveralls

flame resistant clothing that offered protection to those that are at risk for exposure to fire hazards.



Industrial Paint Marker

Our heavy duty Mighty Marker is used for making permanent identification marks in tools, assemblies, and finished metals. Also capable of marking on leather, stone, rubber, wood and many more. Paint Marker is an oil-based paint that will withstand indoor and outdoor conditions without fading, chipping and losing color or opacity outdoors. The marks also resist oil, salt water, alcohols, soap, water and many other liquids. Conforms to ASTM 4236.



Rebar Cap

Rebar Safety Caps provide protection from protruding rebar and are intended for at grade applications, Not intended for impalement protection, Brilliant orange color for higher visibility, Standard rebar safety cap recommended for rebar sizes #3 through #9



Larger cap fits up to 2" diameter

FC48 Polycarbonate, clear, 1.0 mm thick. Heat and impact









ELECTRICAL AND INSTRUMENT MATERIAL



INDUSTRIAL ADVERTISING

List of Product categories we are deals with:

- Safety Signboards
- Road Signboards
- SS Tags, Aluminum Tag
- Phenolic Tags
- Name Boards
- Banners, Flex
- Gift Items
- Roll up & Pop up
- Letterhead
- Visiting cards







Hexagon Crimping With telescopic handles

Indent Crimping (For Non-Insulated Open Barrel terminals)

Square Crimping (For Crimping Wire Ferrules)

Ratchet Cable Cutter

Hexagon Crimping

Quad-Point Crimping (For pre-insulated terminal And Connector)

Ratchet Cable Cutter

Ratchet Cable Cutter

Ratchet Cable Cutter

Quad-Point Crimping (For pre-insulated terminal)

Ratchet Cable Cutter

Ratchet Cable Cutter

Hexagon Crimping





3PTP (Three Point Traceability Padlock)

Color:RED with color coded Key Jacket. RED with color coded Key Jacket. Key Different (2 Unique Keys per Lock). DIMENSIONS: Regular Shackle 40mm- Body Width Body - 40.00 mm, Thickness Body - 20.00 mm, Length Shackle - 48.20 mm, Diameter Shackle - 5.00 mm, Height Total - 40.00 mm, Height - 94.20 mm

3PTP (Three Point Traceability Padlock)

Color: YELLOW with color coded Key Jacket. NON CONDUCTIVE REGULAR Shackle. Key Different (1 Unique Key per Lock). DIMENSIONS: Regular Shackle 40mm Body Width Body - 40.00 mm, Thickness Body - 20.00 mm, Height Body - 45.00 mm, Thickness Shackle - 20.00 mm, Diameter Vertical - 5.00 mm, Clearance - 40.00 mm























